

# ISO/IEC 7811-2:2001-02 (E)

## Identification cards - Recording technique - Part 2: Magnetic stripe; Low coercivity

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Conformance</b> .....	<b>1</b>
<b>3</b>	<b>Normative references</b> .....	<b>1</b>
<b>4</b>	<b>Terms and definitions</b> .....	<b>2</b>
<b>5</b>	<b>Physical characteristics of the identification card</b> .....	<b>3</b>
<b>5.1</b>	<b>Magnetic stripe area warpage</b> .....	<b>3</b>
<b>5.2</b>	<b>Surface distortions</b> .....	<b>3</b>
<b>6</b>	<b>Physical characteristics of the magnetic stripe</b> .....	<b>4</b>
<b>6.1</b>	<b>Height and surface profile of the magnetic stripe area</b> .....	<b>4</b>
<b>6.1.1</b>	<b>Surface profile of the magnetic stripe area</b> .....	<b>5</b>
<b>6.1.2</b>	<b>Height of the magnetic stripe area</b> .....	<b>6</b>
<b>6.2</b>	<b>Surface roughness</b> .....	<b>7</b>
<b>6.3</b>	<b>Adhesion of stripe to card</b> .....	<b>7</b>
<b>6.4</b>	<b>Wear of magnetic stripe from read/write head</b> .....	<b>7</b>
<b>6.5</b>	<b>Resistance to chemicals</b> .....	<b>7</b>
<b>7</b>	<b>Performance characteristics for the magnetic material</b> .....	<b>7</b>
<b>7.1</b>	<b>General</b> .....	<b>7</b>
<b>7.2</b>	<b>Testing and operating environment</b> .....	<b>7</b>
<b>7.3</b>	<b>Signal amplitude requirements for magnetic media</b> .....	<b>7</b>
<b>8</b>	<b>Encoding technique</b> .....	<b>9</b>
<b>9</b>	<b>Encoding specification, general</b> .....	<b>10</b>
<b>9.1</b>	<b>Angle of recording</b> .....	<b>10</b>
<b>9.2</b>	<b>Nominal bit density</b> .....	<b>11</b>
<b>9.3</b>	<b>Signal amplitude requirements for tracks 1, 2 and 3</b> .....	<b>11</b>
<b>9.4</b>	<b>Bit configuration</b> .....	<b>11</b>
<b>9.5</b>	<b>Direction of recording</b> .....	<b>11</b>
<b>9.6</b>	<b>Leading and trailing zeroes</b> .....	<b>11</b>
<b>10</b>	<b>Encoding specifications</b> .....	<b>12</b>
<b>10.1</b>	<b>Alphanumeric track, track 1</b> .....	<b>12</b>
<b>10.1.1</b>	<b>Average bit density</b> .....	<b>12</b>
<b>10.1.2</b>	<b>Flux transition spacing variation</b> .....	<b>12</b>
<b>10.1.3</b>	<b>Coded character set</b> .....	<b>13</b>
<b>10.1.4</b>	<b>Maximum number of characters for ID-1 type card</b> .....	<b>14</b>
<b>10.2</b>	<b>Numeric track, Track 2</b> .....	<b>15</b>
<b>10.2.1</b>	<b>Average bit density</b> .....	<b>15</b>
<b>10.2.2</b>	<b>Flux transition spacing variation</b> .....	<b>15</b>
<b>10.2.3</b>	<b>Coded character set</b> .....	<b>15</b>
<b>10.2.4</b>	<b>Maximum number of characters for ID-1 type card</b> .....	<b>16</b>
<b>10.3</b>	<b>Numeric track, Track 3</b> .....	<b>16</b>
<b>10.3.1</b>	<b>Average bit density</b> .....	<b>16</b>
<b>10.3.2</b>	<b>Flux transition spacing variation</b> .....	<b>16</b>
<b>10.3.3</b>	<b>Coded character set</b> .....	<b>16</b>
<b>10.3.4</b>	<b>Maximum number of characters for ID-1 type card</b> .....	<b>17</b>

<b>11</b>	<b>Error detection .....</b>	<b>17</b>
<b>11.1</b>	<b>Parity .....</b>	<b>17</b>
<b>11.2</b>	<b>Longitudinal redundancy check (LRC) .....</b>	<b>17</b>
<b>12</b>	<b>Location of encoded tracks .....</b>	<b>18</b>
<b>Annex B (normative) Signal amplitude measurements .....</b>		<b>20</b>
<b>Annex C (informative) Magnetic stripe abrasivity .....</b>		<b>21</b>