ISO/IEC 7811-2:2001-02 (E)

Identification cards - Recording technique - Part 2: Magnetic stripe; Low coercivity

Contents

Page

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 2

5 Physical characteristics of the identification card 3
5.1 Magnetic stripe area warpage 3
5.2 Surface distortions 3

6 Physical characteristics of the magnetic stripe 4
6.1 Height and surface profile of the magnetic stripe area 4
6.1.1 Surface profile of the magnetic stripe area 5
6.1.2 Height of the magnetic stripe area 6
6.2 Surface roughness 7
6.3 Adhesion of stripe to card 7
6.4 Wear of magnetic stripe from read/write head 7
6.5 Resistance to chemicals 7

7 Performance characteristics for the magnetic material 7
7.1 General 7
7.2 Testing and operating environment 7
7.3 Signal amplitude requirements for magnetic media 7

8 Encoding technique 9

9 Encoding specification, general 10
9.1 Angle of recording 10
9.2 Nominal bit density 11
9.3 Signal amplitude requirements for tracks 1, 2 and 3 11
9.4 Bit configuration 11
9.5 Direction of recording 11
9.6 Leading and trailing zeroes 11

10 Encoding specifications 12
10.1 Alphanumeric track, track 1 12
10.1.1 Average bit density 12
10.1.2 Flux transition spacing variation 12
10.1.3 Coded character set 13
10.1.4 Maximum number of characters for ID-1 type card 14
10.2 Numeric track, Track 2 15
10.2.1 Average bit density 15
10.2.2 Flux transition spacing variation 15
10.2.3 Coded character set 15
10.2.4 Maximum number of characters for ID-1 type card 16
10.3 Numeric track, Track 3 16
10.3.1 Average bit density 16
10.3.2 Flux transition spacing variation 16
10.3.3 Coded character set 16
10.3.4 Maximum number of characters for ID-1 type card 17

11 Error detection 17
11.1 Parity 17
11.2 Longitudinal redundancy check (LRC) 17

12 Location of encoded tracks 18

Annex B (normative) Signal amplitude measurements 20

Annex C (informative) Magnetic stripe abrasivity 21