

# ISO/IEC 18836:2001-02 (E)

## Information technology\_ - 8\_mm wide magnetic tape cartridge for information interchange\_ - Helical scan recording; Mammoth-Tape-2 format

---

### Contents

<b>Section 1 - General</b>	<b>1</b>
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridges	1
2.2 Generating drive	1
2.3 Receiving drive	1
3 References	1
4 Definitions	1
4.1 a.c. erase	1
4.2 algorithm	1
4.3 Average Signal Amplitude	1
4.4 azimuth	2
4.5 back surface	2
4.6 bit cell	2
4.7 byte	2
4.8 cartridge	2
4.9 Channel bit	2
4.10 Cyclic Redundancy Check (CRC) character	2
4.11 Error Correcting Code (ECC)	2
4.12 File Mark	2
4.13 Logical Beginning of Partition (LBOP)	2
4.14 Logical Block	2
4.15 magnetic tape	2
4.16 Master Standard Reference Tape	2
4.17 Partition	2
4.18 Physical Beginning of Partition (PBOP)	2
4.19 Physical Beginning of Tape (PBOT)	2
4.20 Physical End of Partition (PEOP)	2
4.21 Physical End of Tape (PEOT)	2
4.22 physical recording density	2
4.23 Read Back Check (RBC)	2
4.24 Reference Field	2
4.25 Secondary Standard Reference Tape (SSRT)	2
4.26 Set Mark	2
4.27 Standard Reference Amplitude (SRA)	2
4.28 Standard Reference Current (Ir)	2
4.29 Tape Reference Edge	2
4.30 Test Recording Current (TRC)	2
4.31 Track	3
4.32 Typical Field	3
5 Conventions and Notations	3
5.1 Representation of numbers	3
5.2 Names	3
6 Acronyms	3

7	Environment and Safety	4
7.1	Testing environment	4
7.2	Operating environment	4
7.3	Storage environment	4
7.4	Transportation	4
7.5	Safety	4
7.6	Flammability	4
<b>Section 2 - Requirements for the case</b>		<b>5</b>
8	Dimensional and mechanical characteristics of the case	5
8.1	General	5
8.2	Overall dimension	5
8.3	Holding areas	6
8.4	Cartridge insertion	6
8.5	Window	7
8.6	Loading grips	7
8.7	Label areas	7
8.8	Datum areas and datum holes	7
8.9	Support areas	8
8.10	Recognition holes	9
8.11	Write-inhibit hole	9
8.12	Pre-positioning surfaces	10
8.13	Cartridge lid	10
8.14	Cartridge reel lock	11
8.15	Reel access holes	12
8.16	Interface between the reels and the drive spindles	12
8.17	Light path	14
8.18	Position of the tape in the case	14
8.19	Tape path zone	14
8.20	Tape access cavity	15
8.21	Tape access cavity clearance requirements	15
<b>Section 3 - Requirements for the Unrecorded Tape</b>		<b>32</b>
9	Mechanical, physical and dimensional characteristics of the tape	32
9.1	Materials	32
9.2	Tape length	32
9.2.1	Length of the magnetic tape	32
9.2.2	Length of leader and trailer tapes	32
9.2.3	Length of the cleaning tape	32
9.2.4	Length of the splicing tape	32
9.3	Width	32
9.3.1	Width of magnetic, cleaning, leader and trailer tape	32
9.3.2	Width and position of the splicing tape	33
9.3.3	Edge weave	33
9.4	Discontinuities	34
9.5	Thickness	34
9.5.1	Thickness of the magnetic tape	34
9.5.2	Thickness of the cleaning tape	34
9.5.3	Thickness of leader and trailer tape	34
9.5.4	Thickness of the splice tape	35
9.6	Longitudinal curvature	35
9.7	Cupping	35
9.8	Coating adhesion	35
9.9	Layer-to-layer adhesion	36
9.10	Tensile strength	36

9.10.1	Breaking strength	36
9.10.2	Yield strength	36
9.11	Residual elongation	36
9.12	Electrical resistance of the recording surface	36
9.13	Tape winding	37
9.14	Light transmittance of tape	37
9.15	Abrasivity	37
10	Magnetic recording characteristics	37
10.1	Test conditions	37
10.2	Typical Field	37
10.3	Signal Amplitude	38
10.4	Resolution	38
10.5	Signal-to-Noise Ratio	38
10.6	Ease of erasure	39
10.7	Tape quality	39
10.7.1	Missing pulses	39
10.7.2	Missing pulse zone	39
10.7.3	Overwrite	39
<b>Section 4 - Requirements for an Interchanged Tape</b>		<b>40</b>
11	Track Format	40
11.1	General	40
11.2	Physical block format	41
11.2.1	Logical Transfer Segment (LTS)	41
11.2.2	Compression Unit	42
11.2.3	Physical block	43
11.2.4	Information Matrix	50
11.2.5	Recorded patterns	51
11.3	Search field format	51
11.3.1	Search field data	51
11.3.2	Search field CRC and ECC	53
11.3.3	Search field recording patterns	53
11.4	Servo area	53
11.5	Track layout	53
12	Method of recording	56
12.1	Physical Recording Density	56
12.1.1	Long Term Average Bit Cell Length	56
12.1.2	Short Term Average Bit Cell Length	56
12.1.3	Rate of Change	56
12.2	Bit Shift	57
12.3	Amplitude of Data Signals	57
13	Track geometry	57
13.1	General	57
13.2	Track pitch	57
13.3	Average track pitch	57
13.4	Track width	57
13.5	Track angle	58
13.6	Track length	58
13.7	Guard band	58
13.8	Azimuth angles	58
13.9	Track linearity	58

<b>14</b>	Layout of a tape	<b>58</b>
<b>14.1</b>	General	<b>58</b>
<b>14.2</b>	Tape History Log (THL)	<b>58</b>
<b>14.3</b>	Physical Beginning of Partition	<b>59</b>
<b>14.4</b>	Logical Beginning of Partition	<b>59</b>
<b>14.5</b>	Data area	<b>59</b>
<b>14.5.1</b>	General	<b>59</b>
<b>14.5.2</b>	Short File Mark	<b>59</b>
<b>14.5.3</b>	Long File Mark	<b>59</b>
<b>14.5.4</b>	Set Mark	<b>59</b>
<b>14.6</b>	End of Data	<b>59</b>
<b>14.7</b>	Physical End of Partition (PEOP)	<b>59</b>
<b>Annexes</b>		
<b>A</b>	(normative) - Measurement of Light Transmittance of Tape and Leaders	<b>60</b>
<b>B</b>	(normative) - Tape abrasivity measurement procedure	<b>63</b>
<b>C</b>	(normative) - Generation of the Logical Block CRC	<b>65</b>
<b>D</b>	(normative) - ECC3 Check Bytes	<b>66</b>
<b>E</b>	(normative) - Generation of the Data Area CRC	<b>67</b>
<b>F</b>	(normative) - Generation of the ECC	<b>68</b>
<b>G</b>	(normative) - Pre-coder	<b>69</b>
<b>H</b>	(normative) - Representation of 8-bit bytes by 10-bit patterns	<b>70</b>
<b>J</b>	(normative) - Randomisation	<b>77</b>
<b>K</b>	(normative) - Generation of the Search Field CRC	<b>78</b>
<b>L</b>	(normative) - The Search Field ECC	<b>79</b>
<b>M</b>	(normative) - Measurement of bit shift	<b>80</b>
<b>N</b>	(informative) - Recommendations for transportation	<b>82</b>