

ISO/IEC 19058:2001-05 (E)

Information technology_ - Telecommunications and information exchange between systems; Broadband Private Integrated Services Network; Inter-exchange signalling protocol_ - Generic functional protocol

Contents	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions	2
4.1 Gateway PINX	2
4.2 Inter-PINX link (IPL)	2
4.3 Preceding side	2
4.4 Private Integrated services Network eXchange (PINX)	2
4.5 Succeeding side	2
5 Abbreviations	2
6 Description	2
6.1 Overview	2
6.2 Addressing mechanisms	2
6.2.1 Explicit addressing	2
6.2.2 Functional addressing	3
6.3 Protocol architecture	3
6.4 Services provided by individual protocol entities	3
6.4.1 Services provided by ROSE	3
6.4.2 Services provided by GFT-control	3
6.4.3 Services provided by bearer-related transport	3
6.4.4 Services provided by connectionless bearer-independent transport	3
6.4.5 Services provided by connection-oriented bearer-independent transport	3
7 Operational requirements	3
8 Primitive definitions and state definitions	3
8.1 Primitive definitions	3
8.2 State definitions	3
8.2.1 APDU transport mechanisms	3
8.2.2 GFT-Control	3
9 Coding requirements	3
9.1 Message functional definitions and content	3
9.1.1 Additional messages for bearer-related transactions	4
9.1.2 Messages for connectionless bearer-independent transport	4
9.1.3 Messages for connection-oriented bearer-independent transport	4
9.2 General message format and information element coding	4
9.2.1 Message type	4

9.2.2	Other information elements	4
9.2.3	Encoding of information described using ASN.1	5
10	Signalling procedures	5
10.1	APDU transport mechanisms	5
10.1.1	Bearer-related transport	5
10.1.2	Bearer-independent transport mechanisms	6
10.1.3	Connection-oriented bearer-independent transport mechanism	6
10.1.4	Connectionless bearer-independent transport mechanism	7
10.2	GFT-Control procedures for APDUs	7
10.2.1	GFT-control procedures for transport of APDUs	7
10.2.2	GFT-Control procedures for CO-BI connection control	7
10.2.3	GFT-Control procedures for CL-BI mode	8
10.3	Remote operations procedures	8
10.3.1	Introduction	8
10.3.2	Procedures for operations	8
10.4	Notification transport mechanisms	8
10.4.1	Sending notification information	8
10.4.2	Receiving notification information	8
10.5	GFT-Control procedures for notifications	9
10.5.1	Actions at a PINX which generates notifications	9
10.5.2	Actions at a receiving PINX	9
11	Interworking with (narrowband) QSIG	9
11.1	Full termination of generic functional protocol	9
11.2	Generic interworking function	9
11.2.1	Architecture	9
11.2.2	Bearer-related transport mechanism	9
11.2.3	Connection-oriented bearer independent transport mechanism	9
11.2.4	Connectionless bearer independent transport mechanism	9
12	Parameter values	9
12.1	Connection-oriented bearer-independent transport	9
13	Dynamic description (SDLs)	9
13.1	Block overview diagram	9
13.2	Component transport mechanisms	9
13.2.1	Bearer-related transport mechanism	9
13.2.2	Connection-oriented bearer-independent transport mechanism	9
13.2.3	Connectionless bearer-independent transport mechanism	10
13.3	GFT-Control	10
14	Manufacturer Specific Information (MSI)	16
14.1	Manufacturer specific operations and errors	16
14.2	Manufacturer specific additions to standardised operations and error	16
14.3	Manufacturer specific notifications	16
Annexes		
A	Protocol Implementation Conformance Statement (PICS) proforma	17
B	Formal definition of data types using ITU-T Rec. X.208	18
C	Formal definition of data types using ITU-T Rec. X.680	20
D	Information flows	22

E - Instruction indicators	23
F - Formal definitions of remote operations notation using ITU-T Rec. X.208	24
G - Formal definitions of remote operations notation using ITU-T Rec. X.680	25
H - Examples of the use of Manufacturer Specific Information	26
I - Remote operations protocol	27
J - Problem code definitions	28