

# ISO/IEC 14443-2:2001-07 (E)

## Identification cards - Contactless integrated circuit(s) cards; Proximity cards - Part 2: Radio frequency power and signal interface

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols and abbreviated terms .....	2
5	Initial dialogue for proximity cards .....	3
6	Power transfer .....	3
6.1	Frequency .....	3
6.2	Operating field .....	3
7	Signal interface .....	3
8	Communication signal interface Type A .....	4
8.1	Communication PCD to PICC .....	4
8.1.1	Bit rate .....	4
8.1.2	Modulation .....	4
8.1.3	Bit representation and coding .....	6
8.2	Communication PICC to PCD .....	7
8.2.1	Bit rate .....	7
8.2.2	Load modulation .....	7
8.2.3	Subcarrier .....	7
8.2.4	Subcarrier modulation .....	7
8.2.5	Bit representation and coding .....	7
9	Communication signal interface Type B .....	8
9.1	Communication PCD to PICC .....	8
9.1.1	Bit rate .....	8
9.1.2	Modulation .....	8
9.1.3	Bit representation and coding .....	8
9.2	Communication PICC to PCD .....	9
9.2.1	Bit rate .....	9
9.2.2	Load modulation .....	9
9.2.3	Subcarrier .....	9
9.2.4	Subcarrier modulation .....	9
9.2.5	Bit representation and coding .....	9
10	PICC minimal coupling zone .....	10
Annex A (informative)	Compatibility with other card standards .....	11