

# ISO/IEC 21889:2001-09 (E)

## Information technology\_ - Telecommunications and information exchange between systems\_ - Private Integrated Services Network; Inter-exchange signalling protocol; Call Identification and Call Linkage Additional Network Feature

---

<b>Contents</b>		<b>Page</b>
Foreword		v
Introduction		vi
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Conformance</b>	<b>1</b>
<b>3</b>	<b>Normative references</b>	<b>1</b>
<b>4</b>	<b>Definitions</b>	<b>3</b>
<b>4.1</b>	External definitions	<b>3</b>
<b>4.2</b>	Other definitions	<b>3</b>
<b>4.2.1</b>	CIDL PINX	<b>3</b>
<b>4.2.2</b>	CIDL Transit PINX	<b>4</b>
<b>5</b>	<b>Acronyms</b>	<b>4</b>
<b>6</b>	<b>Signalling protocol for the support of ANF-CIDL</b>	<b>4</b>
<b>6.1</b>	ANF-CIDL description	<b>4</b>
<b>6.2</b>	ANF-CIDL operational requirements	<b>4</b>
<b>6.2.1</b>	Provision/Withdrawal	<b>4</b>
<b>6.2.2</b>	Requirements on an Originating PINX	<b>4</b>
<b>6.2.3</b>	Requirements on a CIDL PINX	<b>4</b>
<b>6.2.4</b>	Requirements on a CIDL Transit PINX	<b>4</b>
<b>6.3</b>	ANF-CIDL coding requirements	<b>5</b>
<b>6.3.1</b>	Operations	<b>5</b>
<b>6.3.2</b>	Information elements	<b>6</b>
<b>6.3.3</b>	Messages	<b>6</b>
<b>6.4</b>	ANF-CIDL state definitions	<b>6</b>
<b>6.4.1</b>	States at a Originating PINX	<b>6</b>
<b>6.4.2</b>	States at a CIDL PINX	<b>7</b>
<b>6.4.3</b>	States at a CIDL Transit PINX	<b>7</b>
<b>6.5</b>	ANF-CIDL signalling procedures	<b>7</b>
<b>6.5.1</b>	Actions at a Originating PINX	<b>7</b>
<b>6.5.2</b>	Procedures at the CIDL PINX	<b>7</b>
<b>6.5.3</b>	Actions at a CIDL Transit PINX	<b>9</b>
<b>6.6</b>	ANF-CIDL impact of interworking with public ISDNs	<b>10</b>
<b>6.7</b>	ANF-CIDL impact of interworking with non-ISDNs	<b>10</b>
<b>6.8</b>	Protocol Interactions between ANF-CIDL and other supplementary services and ANFs	<b>10</b>
<b>6.8.1</b>	Calling Name Identification Presentation (SS-CNIP)	<b>10</b>
<b>6.8.2</b>	Connected Name Identification Presentation (SS-CONP)	<b>10</b>
<b>6.8.3</b>	Completion of Calls to Busy Subscribers (SS-CCBS)	<b>10</b>
<b>6.8.4</b>	Completion of Calls on No Reply (SS-CCNR)	<b>10</b>
<b>6.8.5</b>	Call Forwarding Unconditional (SS-CFU)	<b>10</b>
<b>6.8.6</b>	Call Forwarding Busy (SS-CFB)	<b>11</b>
<b>6.8.7</b>	Call Forwarding No Reply (SS-CFNR)	<b>11</b>
<b>6.8.8</b>	Call Deflection (SS-CD)	<b>11</b>
<b>6.8.9</b>	Call Transfer (SS-CT)	<b>11</b>

<b>6.8.10</b>	Path Replacement (ANF-PR)	<b>12</b>
<b>6.8.11</b>	Advice Of Charge (SS-AOC)	<b>12</b>
<b>6.8.12</b>	Call Offer (SS-CO)	<b>12</b>
<b>6.8.13</b>	Do Not Disturb (SS-DND)	<b>12</b>
<b>6.8.14</b>	Do Not Disturb Override (SS-DNDO)	<b>12</b>
<b>6.8.15</b>	Recall (SS-RE)	<b>12</b>
<b>6.8.16</b>	Call Intrusion (SS-CI)	<b>12</b>
<b>6.8.17</b>	Call Interception (ANF-CINT)	<b>12</b>
<b>6.8.18</b>	Transit Counter (SS-TC)	<b>12</b>
<b>6.8.19</b>	Route Restriction Class (ANF-RRC)	<b>12</b>
<b>6.8.20</b>	Authentication of the PISN (SS-WTAN)	<b>13</b>
<b>6.8.21</b>	Authentication of a WTM user (SS-WTAT)	<b>13</b>
<b>6.8.22</b>	Wireless Terminal Location Registration (SS-WTLR)	<b>13</b>
<b>6.8.23</b>	Wireless Terminal Mobility Incoming Call (ANF-WTMI)	<b>13</b>
<b>6.8.24</b>	Wireless Terminal Mobility Outgoing Call (ANF-WTMO)	<b>13</b>
<b>6.8.25</b>	Message Waiting Indication (SS-MWI)	<b>13</b>
<b>6.8.26</b>	Private User Mobility Incoming Call (ANF-PUMI)	<b>13</b>
<b>6.8.27</b>	Private User Mobility Outgoing Call (ANF-PUMO)	<b>13</b>
<b>6.8.28</b>	Common Information (ANF-CMN)	<b>14</b>
<b>6.8.29</b>	Call Priority Interruption (Protection) (SS-CPI(P))	<b>14</b>
<b>6.8.30</b>	Private User Mobility - Registration (SS-PUMR)	<b>14</b>
<b>6.8.31</b>	Single Step Call Transfer (SSCT)	<b>14</b>
<b>6.8.32</b>	Simple Dialog (SD)	<b>14</b>
<b>6.9</b>	ANF-CIDL parameter values (timers)	<b>14</b>
<b>6.9.1</b>	Timer T1	<b>14</b>
<b>Annexes</b>		
<b>A</b>	Protocol Implementation Conformance Statement (PICS) proforma	<b>15</b>
<b>B</b>	Examples of message sequences	<b>24</b>
<b>C</b>	Specification and Description Language (SDL) representation of procedures	<b>28</b>
<b>D</b>	Imported definitions	<b>34</b>
<b>E</b>	ASN.1 definitions according to ITU-T Recs. X.208 / X.209	<b>38</b>