ISO/IEC 20061:2001-12 (E)

Information technology_- 12,65_mm wide magnetic tape cassette for information interchange_- Helical scan recording; DTF-2

Contents

Page

Section 1 - General **1**

1 Scope **1**

2 Conformance **1**

2.1 Magnetic tape cassette **1**
2.2 Generating system **1**
2.3 Receiving system **1**

3 Normative references **1**

4 Terms and definitions **2**

4.1 Absolute block number **2**
4.2 a.c. erase **2**
4.3 algorithm **2**
4.4 Append file **2**
4.5 Append volume **2**
4.6 Average Signal Amplitude (ASA) **2**
4.7 azimuth **2**
4.8 back surface **2**
4.9 bit cell **2**
4.10 block **2**
4.11 Block Management Table (BMT) **2**
4.12 byte **2**
4.13 cassette **2**
4.14 compressed data **2**
4.15 Control Track **2**
4.16 flux transition position **2**
4.17 flux transition spacing **2**
4.18 Logical track set ID **2**
4.19 Logical volume **2**
4.20 magnetic tape **2**
4.21 Master Standard Reference Tape (MSRT) **2**
4.22 physical recording density **2**
4.23 Reference Field (RF) **2**
4.24 Secondary Standard Reference Tape (SSRT) **2**
4.25 Standard Reference Amplitude (SRA) **3**
4.26 Standard Reference Current (Ir) **3**
4.27 Tape Reference Edge **3**
4.28 Test Recording Current (TRC) **3**
4.29 track **3**
4.30 track angle **3**
4.31 Track Set **3**
4.32 Typical Field (TF) **3**
4.33 word **3**

5 Conventions and notations **3**

5.1 Representation of numbers **3**
5.2 Names **3**

6 Acronyms **4**

7 Environment and safety **4**

7.1 Testing environment **4**
7.2 Operating environment **4**
7.3 Storage environment **5**
7.4 Transportation **5**
7.5 Safety **5**
7.6 Flammability **5**

Section 2 - Requirements for the case **5**

8 Dimensional and mechanical characteristics of the case **5**

8.1 General **5**
8.2 Type S cassette **5**
8.2.1 Overall dimensions (Figure 3) **6**
8.2.2 Holding areas (Figure 4) **6**
8.2.3 Window **6**
8.2.4 Label areas (Figure 4) **7**
8.2.5 Datum areas and datum holes (Figures 5 and 6) **7**
8.2.6 Support areas (Figure 5) **7**
8.2.7 Guiding grooves (Figures 3 and 6) **8**
8.2.8 Recognition holes (Figures 6 and 7) **9**
8.2.9 Write-inhibit plug (Figure 8) **10**
8.2.10 Pre-positioning surface (Figures 3 and 5) **11**
8.2.11 Cassette lid (Figures 9, 10, 11, 12 and 13) **11**
8.2.12 Cassette reel lock (Figure 13) **12**
8.2.13 Reel access holes (Figure 6) **13**
8.2.14 Reels (Figure 14) **13**
8.2.15 Position of the tape in the case (Figure 16) **14**
8.2.16 Tape path zone (Figures 16 to 18) **14**
8.2.17 Tape access cavity (Figure 19) **15**
8.3 Type L cassette **30**
8.3.1 Overall dimensions (Figure 22) **30**
8.3.2 Holding areas (Figure 23) **30**
8.3.3 Window **31**
8.3.4 Label areas (Figure 23) **31**
8.3.5 Datum areas and datum holes (Figures 24 and 25) **31**
8.3.6 Support areas (Figure 24) **32**
8.3.7 Guiding grooves (Figure 25) **32**
8.3.8 Recognition holes (Figure 26) **33**
8.3.9 Write-inhibit plug (Figure 27) **34**
8.3.10 Pre-positioning surface (Figures 24 and 25) **35**
8.3.11 Cassette lid (Figures 28, 29, 30, 31 and 32) **35**
8.3.12 Cassette reel lock (Figure 32) **36**
8.3.13 Reel access holes (Figure 25) **36**
8.3.14 Reels (Figure 33) **37**
8.3.15 Position of the tape in the case (Figure 35) **38**
8.3.16 Tape path zone (Figures 35 to 37) **38**
8.3.17 Tape access cavity (Figure 38) **39**
8.3.18 Cavity for compatibility with Type S cassette (Figure 39) **40**

Section 3 - Requirements for the unrecorded tape **55**

9 Mechanical, physical and dimensional characteristics of the tape **55**

9.1 Materials **55**
9.2 Tape length **55**
9.3 Tape width **55**
9.4 Width and position of splicing tape **55**
9.5 Discontinuity **55**
9.6 Tape thickness **55**
9.7 Longitudinal curvature **55**
9.8 Out-of-plane distortions **56**

9.9 Coating adhesion **56**
9.10 Layer-to-layer adhesion **57**
9.11 Tensile strength **57**
9.11.1 Breaking strength **57**
9.11.2 Yield strength **57**
9.11.3 Strength of splice **57**
9.12 Residual elongation **57**
9.13 Electrical resistance of the coated surfaces **57**
9.14 Tape wind **58**

10 Magnetic recording characteristics **58**

10.1 Typical Field (TF1) **58**
10.2 Average Signal Amplitude(ASA) **59**
10.3 Resolution **59**
10.4 Signal-to-noise ratio (S/N) **59**
10.5 Ease of erasure **59**
10.6 Tape quality **59**
10.6.1 Missing pulses **59**
10.6.2 Missing pulse zone **59**
10.7 Inhibitor tape **59**

11 Format for helical tracks **60**

11.1 General description of the write data path (see Figure 42) **60**
11.2 Formation of a Logical Track Set **60**

11.2.1 Types of information track sets **60**
11.2.2 Generation of a Logical Track Set **62**
11.2.3 Subcode data field **62**
11.2.4 Block Management Table (BMT) **66**
11.2.5 Data and information field definitions **66**

11.3 Track Set information **70**

11.3.1 Loading the Product Code Arrays **70**

11.4 Product code array processing **72**

11.4.1 Error correction method **72**
11.4.2 Error correction coding for C1 Parity **72**

11.5 Track assignments **73**

11.5.1 Segments/Sectors (Figure 46) **73**
11.5.2 Sync Blocks (Figure 47) **74**
11.5.3 Track interleave (Figure 48) **74**
11.5.4 Byte interleave across Sync Blocks (Figure 49) **77**
11.5.5 Randomization **77**

11.6 Formation of the contents of a helical track (Figure 50) **78**

11.6.1 Segment/Sector details (Figure 47) **78**
11.6.2 Channel bit coding **79**
11.6.3 Interleaved-NRZ1 (Figure 51) **79**
11.6.4 Tracking Pilot Signals (TPS) **79**

12 Track geometry **79**

12.1 General **79**
12.2 Helically recorded tracks **80**

12.2.1 Location of the tracks **80**
12.2.2 Track width **81**
12.2.3 Track angle **81**
12.2.4 Track pitch **81**
12.2.5 Location of elements in the helical track **82**

12.2.6 Location of the Data Area Reference Point **82**
12.2.7 Straightness of tracks **82**
12.2.8 Azimuth angles **82**
12.2.9 Tracking Pilot Signals (TPS) **82**
12.2.10 Amplitude of servo signals **82**

12.3 Longitudinal tracks geometry **82**

12.3.1 Control Track **82**
12.3.2 Time Code Track signals recording position **83**

13 Method of recording helical tracks **83**

13.1 Physical recording density **83**
13.2 Record current optimization **83**
13.3 Efficiency of erasure **83**

14 Method of recording longitudinal tracks **83**

14.1 Overview **83**
14.2 Control Track **83**

14.2.1 Signal **83**
14.2.2 Polarity of magnetisation (Figure 54) **83**
14.2.3 Alignment **83**
14.2.4 Read signal amplitude **84**
14.2.5 Quality of the Control Track **84**

14.3 Time Code Track **84**

14.3.1 Method of recording the Time Code Track **84**
14.3.2 Physical recording density **84**
14.3.3 Bit shift **84**
14.3.4 Read signal amplitude **84**
14.3.5 Quality of the Time Code Track **85**

14.4 Format for the Time Code Track **85**

14.4.1 Count bits **85**
14.4.2 Phase bit **85**
14.4.3 Synchronizing pattern **85**
14.4.4 Supplemental Data **85**
14.4.5 Extent of Time Code **85**

Section 5 - Requirements for recorded information **85**

15 Recorded information **85**

15.1 Recording area (Figure 55) **85**
15.2 Magnetic tape layout (Figure 56) **85**

15.2.1 Valid data areas **85**
15.2.2 Invalid data areas **86**

15.3 Physical TSID **86**

15.3.1 Structure surrounding the VSIT area **88**
15.3.2 Structure of the DIT area **88**
15.3.3 Structure of the User Data Area **89**

Section 6 - Write operations **89**

16 Write retry sequence (Figure 58) **89**

17 Append file operation (Figure 59) **90**

17.1 Append volume **90**
17.2 Append write (Figure 60) **90**
17.3 Overwrite (Figure 61) **91**

17.4 File extension (Figure 62) **92**

Annexes

A - Measurement of Signal-to-Noise Ratio **94**

B - Representation 8/9 coding patterns **95**

C - Recommendations for transportation **99**

D - Inhibitor tape **100**