

# ISO/IEC 16448 :2002-04 (E)

Information technology\_ - 120\_mm DVD\_ - Read-only disk

---

## Contents

<b>Section 1 - General</b>	<b>1</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Conformance</b>	<b>1</b>
<b>2.1 Optical Disk</b>	<b>1</b>
<b>2.2 Generating system</b>	<b>1</b>
<b>2.3 Receiving system</b>	<b>1</b>
<b>3 Normative reference</b>	<b>1</b>
<b>4 Terms and definitions</b>	<b>1</b>
<b>4.1 Adhesive layer</b>	<b>2</b>
<b>4.2 Channel bit</b>	<b>2</b>
<b>4.3 Clamping Zone</b>	<b>2</b>
<b>4.4 Digital Sum Value (DSV)</b>	<b>2</b>
<b>4.5 Disk Reference Plane</b>	<b>2</b>
<b>4.6 Dual Layer disk</b>	<b>2</b>
<b>4.7 Dummy substrate</b>	<b>2</b>
<b>4.8 Entrance surface</b>	<b>2</b>
<b>4.9 Optical disk</b>	<b>2</b>
<b>4.10 Physical sector number</b>	<b>2</b>
<b>4.11 Read-only disk</b>	<b>2</b>
<b>4.12 Recorded layer</b>	<b>2</b>
<b>4.13 Reed-Solomon code</b>	<b>2</b>
<b>4.14 Reserved field</b>	<b>2</b>
<b>4.15 Sector</b>	<b>2</b>
<b>4.16 Single Layer disk</b>	<b>2</b>
<b>4.17 Spacer</b>	<b>2</b>
<b>4.18 Substrate</b>	<b>2</b>
<b>4.19 Track</b>	<b>3</b>
<b>4.20 Track pitch</b>	<b>3</b>
<b>4.21 Zone</b>	<b>3</b>
<b>5 Conventions and notations</b>	<b>3</b>
<b>5.1 Representation of numbers</b>	<b>3</b>
<b>5.2 Names</b>	<b>3</b>
<b>6 List of acronyms</b>	<b>3</b>
<b>7 General description of the disk</b>	<b>4</b>
<b>8 General requirements</b>	<b>5</b>
<b>8.1 Environments</b>	<b>5</b>
<b>8.1.1 Test environment</b>	<b>5</b>
<b>8.1.2 Operating environment</b>	<b>6</b>
<b>8.1.3 Storage environment</b>	<b>6</b>
<b>8.1.4 Transportation</b>	<b>6</b>
<b>8.2 Safety requirements</b>	<b>6</b>
<b>8.3 Flammability</b>	<b>6</b>

<b>9</b>	<b>Reference measurement devices</b>	<b>6</b>
9.1	Pick Up Head (PUH)	6
9.2	Measurement conditions	7
9.3	Normalized servo transfer function	8
9.4	Reference Servo for axial tracking	8
9.5	Reference Servo for radial tracking	9
<b>Section 2 - Dimensional, mechanical and physical characteristics of the disk</b>		<b>10</b>
<b>10</b>	<b>Dimensional characteristics</b>	<b>10</b>
10.1	Overall dimensions	10
10.2	First transition area	10
10.3	Second transition area	10
10.4	Clamping Zone	10
10.5	Third transition area	11
10.6	Information Zone	11
10.6.1	Sub-divisions of the Information Zone	11
10.6.2	Track geometry	12
10.6.3	Track modes	12
10.6.4	Channel bit length	12
10.7	Rim area	12
10.8	Remark on tolerances	13
10.9	Runout	13
10.9.1	Axial runout	13
10.9.2	Radial runout	13
10.10	Label	13
<b>11</b>	<b>Mechanical parameters</b>	<b>14</b>
11.1	Mass	14
11.2	Moment of inertia	14
11.3	Dynamic imbalance	14
11.4	Sense of rotation	14
<b>12</b>	<b>Optical parameters</b>	<b>14</b>
12.1	Index of refraction	14
12.2	Thickness of the transparent substrate	14
12.3	Thickness of the spacer of Types C and D	14
12.4	Angular deviation	14
12.5	Birefringence of the transparent substrate	14
12.6	Reflectivity	14
<b>Section 3 - Operational Signals</b>		<b>18</b>
<b>13</b>	<b>High frequency signals (HF)</b>	<b>18</b>
13.1	Modulated amplitude	18
13.2	Signal asymmetry	19
13.3	Cross-track signal	19
13.4	Quality of signals	19
13.4.1	Jitter	19
13.4.2	Random errors	19
13.4.3	Defects	19
<b>14</b>	<b>Servo signals</b>	<b>19</b>
14.1	Differential phase tracking error signal	19
14.2	Tangential push-pull signal	20

<b>Section 4 - Data Format</b>	<b>22</b>
15 <b>General</b>	<b>22</b>
16 <b>Data Frames</b>	<b>22</b>
16.1 <b>Identification Data (ID)</b>	<b>22</b>
16.2 <b>ID Error Detection Code (IED)</b>	<b>23</b>
16.3 <b>Copyright Management Information (CPR_MAI)</b>	<b>24</b>
16.4 <b>Error Detection Code (EDC)</b>	<b>24</b>
17 <b>Scrambled Frames</b>	<b>24</b>
18 <b>ECC Blocks</b>	<b>25</b>
19 <b>Recording Frames</b>	<b>26</b>
20 <b>Modulation</b>	<b>27</b>
21 <b>Physical Sectors</b>	<b>27</b>
22 <b>Suppress control of the d.c. component</b>	<b>29</b>
<b>Section 5 - Format of the Information Zone(s)</b>	<b>30</b>
23 <b>General description of an Information Zone</b>	<b>30</b>
24 <b>Layout of the Information Zone</b>	<b>30</b>
25 <b>Physical Sector numbering</b>	<b>30</b>
26 <b>Lead-in Zone</b>	<b>32</b>
26.1 <b>Initial Zone</b>	<b>33</b>
26.2 <b>Reference Code Zone</b>	<b>33</b>
26.3 <b>Buffer Zone 1</b>	<b>33</b>
26.4 <b>Buffer Zone 2</b>	<b>33</b>
26.5 <b>Control Data Zone</b>	<b>33</b>
26.5.1 <b>Physical format information</b>	<b>34</b>
26.5.2 <b>Disk manufacturing information</b>	<b>35</b>
26.5.3 <b>Content provider information</b>	<b>36</b>
27 <b>Middle Zone</b>	<b>36</b>
28 <b>Lead-out Zone</b>	<b>36</b>
<b>Annexes</b>	
<b>A (normative) - Measurement of the angular deviation <math>\alpha</math></b>	<b>37</b>
<b>B (normative) - Measurement of birefringence</b>	<b>39</b>
<b>C (normative) - Measurement of the differential phase tracking error</b>	<b>41</b>
<b>D (normative) - Measurement of light reflectance</b>	<b>45</b>
<b>E (normative) - Tapered cone for disk clamping</b>	<b>47</b>
<b>F (normative) - Measurement of jitter</b>	<b>48</b>
<b>G (normative) - 8-to-16 Modulation with RLL (2,10) requirements</b>	<b>51</b>
<b>H (normative) - Burst Cutting Area (BCA)</b>	<b>61</b>
<b>J (normative) - Source Identification Code (SID)</b>	<b>66</b>
<b>K (informative) - Measurement of the thickness of the spacer of Dual Layer disks</b>	<b>69</b>
<b>L (informative) - Note on the Reference Code</b>	<b>71</b>
<b>M (informative) - Maximum transfer rate</b>	<b>72</b>
<b>N (informative) - Disk bonding</b>	<b>73</b>
<b>P (informative) - Transportation</b>	<b>75</b>