

# ISO 1831:1980-10 (E)

## Printing specifications for optical character recognition

---

| <b>Contents</b> |   | <b>Page</b> |
|-----------------|---|-------------|
| <b>0</b>        | <b>Introduction</b> .....   | <b>1</b>    |
| <b>0.1</b>      | <b>Interpretation of the International Standard</b> .....             | <b>1</b>    |
| <b>0.2</b>      | <b>Use of the International Standard</b> .....                        | <b>1</b>    |
| <b>0.3</b>      | <b>Annexes</b> .....  | <b>2</b>    |
| <b>1</b>        | <b>Scope and field of application</b> .....                           | <b>2</b>    |
| <b>2</b>        | <b>References</b> .....   | <b>2</b>    |
| <b>3</b>        | <b>Spectral requirements</b> .....                                    | <b>2</b>    |
| <b>3.1</b>      | <b>General</b> .....  | <b>2</b>    |
| <b>3.2</b>      | <b>Spectral bands</b> .....   | <b>2</b>    |
| <b>4</b>        | <b>Paper specifications for OCR</b> .....                             | <b>2</b>    |
| <b>4.1</b>      | <b>General</b> .....  | <b>2</b>    |
| <b>4.2</b>      | <b>Luminous reflectance factor <math>R_o</math> of paper</b> .....    | <b>2</b>    |
| <b>4.3</b>      | <b>Dirt in paper</b> .....  | <b>3</b>    |
| <b>4.4</b>      | <b>Paper opacity</b> .....  | <b>4</b>    |
| <b>4.5</b>      | <b>Variation in reflectance of paper</b> .....                        | <b>4</b>    |
| <b>5</b>        | <b>Characteristics of the printed image</b> .....                     | <b>4</b>    |
| <b>5.1</b>      | <b>General</b> .....  | <b>4</b>    |
| <b>5.2</b>      | <b>Print quality tolerance ranges</b> .....                           | <b>5</b>    |
| <b>5.3</b>      | <b>Definition of character outline limits</b> .....                   | <b>5</b>    |
| <b>5.4</b>      | <b>Measurements of Parameters</b> .....                               | <b>10</b>   |
| <b>6</b>        | <b>Character positioning</b> .....                                    | <b>19</b>   |
| <b>6.1</b>      | <b>General</b> .....  | <b>19</b>   |
| <b>6.2</b>      | <b>Document reference edges</b> .....                                 | <b>19</b>   |
| <b>6.3</b>      | <b>Character boundary</b> .....                                       | <b>19</b>   |
| <b>6.4</b>      | <b>Character skew</b> .....   | <b>20</b>   |
| <b>6.5</b>      | <b>Line boundary</b> .....  | <b>20</b>   |
| <b>6.6</b>      | <b>Field</b> .....  | <b>20</b>   |
| <b>6.7</b>      | <b>Horizontal positioning of characters within a line</b> .....       | <b>20</b>   |
| <b>6.8</b>      | <b>Character alignment within a line</b> .....                        | <b>21</b>   |
| <b>6.9</b>      | <b>Printing area</b> .....  | <b>21</b>   |
| <b>6.10</b>     | <b>Clear area</b> .....   | <b>21</b>   |
| <b>6.11</b>     | <b>Margin</b> .....   | <b>22</b>   |
| <b>6.12</b>     | <b>Line separation</b> .....  | <b>22</b>   |
| <b>6.13</b>     | <b>Line spacing</b> .....   | <b>22</b>   |
| <b>Annexes</b>  |   |             |
| <b>A</b>        | <b>Paper characteristics and measurements</b> .....                   | <b>24</b>   |
| <b>B</b>        | <b>Characteristics of the printed image</b> .....                     | <b>28</b>   |
| <b>C</b>        | <b>Computer-aided method (CAM) of print quality measurement</b> ..... | <b>31</b>   |
| <b>D</b>        | <b>Character positioning</b> .....                                    | <b>40</b>   |