

# ISO/IEC 11582 :2002-07 (E)

Information technology\_- Telecommunications and information exchange between systems\_- Private Integrated Services Network; Generic functional protocol for the support of supplementary services; Inter-exchange signalling procedures and protocol

---

## Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
4.1 External definitions	2
4.2 ACSE APDU	2
4.3 Additional Network Feature (ANF)	2
4.4 Adjacent PINX	2
4.5 Application Protocol Data Unit (APDU)	2
4.6 Call, Basic call	2
4.7 Call independent signalling connection	2
4.8 Call independent	3
4.9 Call related	3
4.10 Connection oriented	3
4.11 Connectionless	3
4.12 Coordination Function	3
4.13 Destination PINX	3
4.14 DSE APDU	3
4.15 Dialogue Service Element (DSE)	3
4.16 End PINX	3
4.17 Gateway PINX	3
4.18 Generic Functional Transport Control (GFT-Control) entity	3
4.19 Incoming side	3
4.20 Interpretation APDU	3
4.21 Inter-PINX link	3
4.22 Invocation	3
4.23 Link significance	4
4.24 Mistyped	4
4.25 Network significance	4
4.26 Next PINX	4
4.27 Notification	4
4.28 Originating PINX	4
4.29 Outgoing side	4
4.30 PINX address	4
4.31 Preceding PINX	4
4.32 Private Signalling System No.1	4
4.33 Protocol Control	4
4.34 ROSE APDU	4
4.35 Side	4
4.36 Signalling Carriage Mechanism (SCM)	4
4.37 Source PINX	4
4.38 Subsequent PINX	5
4.39 Supplementary service	5
4.40 Supplementary Services Control (SS-Control) entity	5
4.41 Terminating PINX	5
4.42 Terminal, Terminal Equipment	5
4.43 Transit PINX	5
4.44 Unrecognised	5

5	List of acronyms	5
6	General principles	6
6.1	Application Association	6
6.2	Protocol Model	6
6.3	Application of the protocol model to communication between SS-Control entities in non-Adjacent PINXs	8
6.4	Services provided by ROSE	9
6.5	Services provided by ACSE	9
6.6	Services provided by DSE	9
6.7	Services provided by GFT-Control	10
6.7.1	Connection oriented services	10
6.7.2	Connectionless transport services	11
6.7.3	Notification services	11
6.8	Services provided by Protocol Control to GFT-Control	11
6.8.1	Connection oriented transport services	11
6.8.2	Connectionless transport service	12
6.8.3	Notification services	12
6.9	Services required of the Signalling Carriage Mechanism	12
7	Protocol Control and GFT-Control Requirements	12
7.1	Call related Procedures for the transport of APDUs	12
7.1.1	Protocol Control requirements	12
7.1.2	GFT-Control requirements	13
7.2	Connectionless APDU Transport Mechanism	20
7.2.1	Protocol Control requirements	20
7.2.2	Control requirements	20
7.3	Connection oriented call independent APDU transport mechanism	21
7.3.1	Protocol Control requirements	21
7.3.2	Dynamic Description (SDL) of Connection oriented Protocol Control procedures	25
7.3.3	Generic Functional Transport Control requirements	31
7.4	Call related procedures for the transport of Notifications	34
7.4.1	Categories of notifications	34
7.4.2	Protocol Control requirements	34
7.4.3	GFT-Control requirements	34
8	Application layer requirements	35
8.1	Coordination Function requirements	35
8.1.1	Inclusion of an Interpretation APDU at a Source PINX	35
8.1.2	Handling of APDUs at a Destination PINX	35
8.2	ROSE requirements	35
8.3	ACSE requirements	36
8.4	DSE requirements	36
8.4.1	Actions at the PINX which initiates the dialogue (PINX A)	36
8.4.2	Actions at the PINX which terminates the dialogue (PINX B)	37
8.4.3	Dialogue Continuation in the Active State	37
8.4.4	Dialogue Protocol Timers	37
8.4.5	Error procedures relating to dialogue control	38
8.4.6	Example of a dialogue	38
8.4.7	Dynamic Description (SDL) of Dialogue Identification Protocol Procedures	38
8.5	SS-Control requirements	43

<b>9</b>	<b>Manufacturer Specific Information</b>	<b>43</b>
<b>9.1</b>	<b>Manufacturer specific operations</b>	<b>43</b>
<b>9.2</b>	<b>Manufacturer specific additions to standardised operations</b>	<b>43</b>
<b>9.3</b>	<b>Manufacturer specific notifications</b>	<b>44</b>
<b>10</b>	<b>Message functional definitions and contents</b>	<b>45</b>
<b>10.1</b>	<b>ALERTING</b>	<b>45</b>
<b>10.2</b>	<b>CALL PROCEEDING</b>	<b>45</b>
<b>10.3</b>	<b>CONNECT</b>	<b>46</b>
<b>10.4</b>	<b>SETUP</b>	<b>46</b>
<b>10.5</b>	<b>DISCONNECT</b>	<b>46</b>
<b>10.6</b>	<b>RELEASE</b>	<b>46</b>
<b>10.7</b>	<b>RELEASE COMPLETE</b>	<b>47</b>
<b>10.8</b>	<b>FACILITY</b>	<b>47</b>
<b>10.9</b>	<b>NOTIFY</b>	<b>48</b>
<b>10.10</b>	<b>PROGRESS</b>	<b>48</b>
<b>11</b>	<b>General message format and information element coding</b>	<b>48</b>
<b>11.1</b>	<b>Message Type</b>	<b>48</b>
<b>11.2</b>	<b>Call reference</b>	<b>49</b>
<b>11.3</b>	<b>Other information elements</b>	<b>49</b>
<b>11.3.1</b>	<b>Bearer capability</b>	<b>49</b>
<b>11.3.2</b>	<b>Channel identification</b>	<b>50</b>
<b>11.3.3</b>	<b>Facility</b>	<b>50</b>
<b>11.3.4</b>	<b>Notification indicator</b>	<b>58</b>
<b>11.4</b>	<b>Encoding of information described using ASN.1</b>	<b>60</b>
<b>Annexes</b>		
<b>A</b>	<b>Protocol Implementation Conformance Statement (PICS) for ISO/IEC 11582</b>	<b>61</b>
<b>B</b>	<b>ASN.1 definitions of generic parameters</b>	<b>70</b>
<b>C</b>	<b>Application of the functional protocol</b>	<b>75</b>
<b>D</b>	<b>Remote operations protocol and application association control</b>	<b>82</b>
<b>E</b>	<b>Formal ROSE Definitions</b>	<b>83</b>
<b>F</b>	<b>Examples of the use of Manufacturer specific information</b>	<b>84</b>
<b>G</b>	<b>Problem code definitions</b>	<b>91</b>
<b>H</b>	<b>Bibliography</b>	<b>92</b>
<b>I</b>	<b>Object identifiers defined in ISO/IEC 11582</b>	<b>93</b>
<b>J</b>	<b>“Recipe” for migration of X.208 / X.209 based QSIG ASN.1 modules to X.680 / X.690 ASN.1</b>	<b>95</b>
<b>K</b>	<b>ASN.1 definitions according to ITU-T Recs. X.208 / X.209</b>	<b>100</b>
<b>L</b>	<b>Technical changes since third edition of ECMA-165</b>	<b>112</b>