

# ISO/IEC 11582 :2002-07 (E)

Information technology\_- Telecommunications and information exchange between systems\_- Private Integrated Services Network; Generic functional protocol for the support of supplementary services; Inter-exchange signalling procedures and protocol

---

## Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
4.1 External definitions	2
4.2 ACSE APDU	2
4.3 Additional Network Feature (ANF)	2
4.4 Adjacent PINX	2
4.5 Application Protocol Data Unit (APDU)	2
4.6 Call, Basic call	2
4.7 Call independent signalling connection	2
4.8 Call independent	3
4.9 Call related	3
4.10 Connection oriented	3
4.11 Connectionless	3
4.12 Coordination Function	3
4.13 Destination PINX	3
4.14 DSE APDU	3
4.15 Dialogue Service Element (DSE)	3
4.16 End PINX	3
4.17 Gateway PINX	3
4.18 Generic Functional Transport Control (GFT-Control) entity	3
4.19 Incoming side	3
4.20 Interpretation APDU	3
4.21 Inter-PINX link	3
4.22 Invocation	3
4.23 Link significance	4
4.24 Mistyped	4
4.25 Network significance	4
4.26 Next PINX	4
4.27 Notification	4
4.28 Originating PINX	4
4.29 Outgoing side	4
4.30 PINX address	4
4.31 Preceding PINX	4
4.32 Private Signalling System No.1	4
4.33 Protocol Control	4
4.34 ROSE APDU	4
4.35 Side	4
4.36 Signalling Carriage Mechanism (SCM)	4
4.37 Source PINX	4
4.38 Subsequent PINX	5
4.39 Supplementary service	5
4.40 Supplementary Services Control (SS-Control) entity	5
4.41 Terminating PINX	5
4.42 Terminal, Terminal Equipment	5
4.43 Transit PINX	5
4.44 Unrecognised	5

<b>5</b>	List of acronyms	<b>5</b>
<b>6</b>	General principles	<b>6</b>
<b>6.1</b>	Application Association	<b>6</b>
<b>6.2</b>	Protocol Model	<b>6</b>
<b>6.3</b>	Application of the protocol model to communication between SS-Control entities in non-Adjacent PINXs	<b>8</b>
<b>6.4</b>	Services provided by ROSE	<b>9</b>
<b>6.5</b>	Services provided by ACSE	<b>9</b>
<b>6.6</b>	Services provided by DSE	<b>9</b>
<b>6.7</b>	Services provided by GFT-Control	<b>10</b>
<b>6.7.1</b>	Connection oriented services	<b>10</b>
<b>6.7.2</b>	Connectionless transport services	<b>11</b>
<b>6.7.3</b>	Notification services	<b>11</b>
<b>6.8</b>	Services provided by Protocol Control to GFT-Control	<b>11</b>
<b>6.8.1</b>	Connection oriented transport services	<b>11</b>
<b>6.8.2</b>	Connectionless transport service	<b>12</b>
<b>6.8.3</b>	Notification services	<b>12</b>
<b>6.9</b>	Services required of the Signalling Carriage Mechanism	<b>12</b>
<b>7</b>	Protocol Control and GFT-Control Requirements	<b>12</b>
<b>7.1</b>	Call related Procedures for the transport of APDUs	<b>12</b>
<b>7.1.1</b>	Protocol Control requirements	<b>12</b>
<b>7.1.2</b>	GFT-Control requirements	<b>13</b>
<b>7.2</b>	Connectionless APDU Transport Mechanism	<b>20</b>
<b>7.2.1</b>	Protocol Control requirements	<b>20</b>
<b>7.2.2</b>	Control requirements	<b>20</b>
<b>7.3</b>	Connection oriented call independent APDU transport mechanism	<b>21</b>
<b>7.3.1</b>	Protocol Control requirements	<b>21</b>
<b>7.3.2</b>	Dynamic Description (SDL) of Connection oriented Protocol Control procedures	<b>25</b>
<b>7.3.3</b>	Generic Functional Transport Control requirements	<b>31</b>
<b>7.4</b>	Call related procedures for the transport of Notifications	<b>34</b>
<b>7.4.1</b>	Categories of notifications	<b>34</b>
<b>7.4.2</b>	Protocol Control requirements	<b>34</b>
<b>7.4.3</b>	GFT-Control requirements	<b>34</b>
<b>8</b>	Application layer requirements	<b>35</b>
<b>8.1</b>	Coordination Function requirements	<b>35</b>
<b>8.1.1</b>	Inclusion of an Interpretation APDU at a Source PINX	<b>35</b>
<b>8.1.2</b>	Handling of APDUs at a Destination PINX	<b>35</b>
<b>8.2</b>	ROSE requirements	<b>35</b>
<b>8.3</b>	ACSE requirements	<b>36</b>
<b>8.4</b>	DSE requirements	<b>36</b>
<b>8.4.1</b>	Actions at the PINX which initiates the dialogue (PINX A)	<b>36</b>
<b>8.4.2</b>	Actions at the PINX which terminates the dialogue (PINX B)	<b>37</b>
<b>8.4.3</b>	Dialogue Continuation in the Active State	<b>37</b>
<b>8.4.4</b>	Dialogue Protocol Timers	<b>37</b>
<b>8.4.5</b>	Error procedures relating to dialogue control	<b>38</b>
<b>8.4.6</b>	Example of a dialogue	<b>38</b>
<b>8.4.7</b>	Dynamic Description (SDL) of Dialogue Identification Protocol Procedures	<b>38</b>
<b>8.5</b>	SS-Control requirements	<b>43</b>

<b>9</b>	<b>Manufacturer Specific Information</b>	<b>43</b>
<b>9.1</b>	<b>Manufacturer specific operations</b>	<b>43</b>
<b>9.2</b>	<b>Manufacturer specific additions to standardised operations</b>	<b>43</b>
<b>9.3</b>	<b>Manufacturer specific notifications</b>	<b>44</b>
<b>10</b>	<b>Message functional definitions and contents</b>	<b>45</b>
<b>10.1</b>	<b>ALERTING</b>	<b>45</b>
<b>10.2</b>	<b>CALL PROCEEDING</b>	<b>45</b>
<b>10.3</b>	<b>CONNECT</b>	<b>46</b>
<b>10.4</b>	<b>SETUP</b>	<b>46</b>
<b>10.5</b>	<b>DISCONNECT</b>	<b>46</b>
<b>10.6</b>	<b>RELEASE</b>	<b>46</b>
<b>10.7</b>	<b>RELEASE COMPLETE</b>	<b>47</b>
<b>10.8</b>	<b>FACILITY</b>	<b>47</b>
<b>10.9</b>	<b>NOTIFY</b>	<b>48</b>
<b>10.10</b>	<b>PROGRESS</b>	<b>48</b>
<b>11</b>	<b>General message format and information element coding</b>	<b>48</b>
<b>11.1</b>	<b>Message Type</b>	<b>48</b>
<b>11.2</b>	<b>Call reference</b>	<b>49</b>
<b>11.3</b>	<b>Other information elements</b>	<b>49</b>
<b>11.3.1</b>	<b>Bearer capability</b>	<b>49</b>
<b>11.3.2</b>	<b>Channel identification</b>	<b>50</b>
<b>11.3.3</b>	<b>Facility</b>	<b>50</b>
<b>11.3.4</b>	<b>Notification indicator</b>	<b>58</b>
<b>11.4</b>	<b>Encoding of information described using ASN.1</b>	<b>60</b>
<b>Annexes</b>		
<b>A</b>	<b>Protocol Implementation Conformance Statement (PICS) for ISO/IEC 11582</b>	<b>61</b>
<b>B</b>	<b>ASN.1 definitions of generic parameters</b>	<b>70</b>
<b>C</b>	<b>Application of the functional protocol</b>	<b>75</b>
<b>D</b>	<b>Remote operations protocol and application association control</b>	<b>82</b>
<b>E</b>	<b>Formal ROSE Definitions</b>	<b>83</b>
<b>F</b>	<b>Examples of the use of Manufacturer specific information</b>	<b>84</b>
<b>G</b>	<b>Problem code definitions</b>	<b>91</b>
<b>H</b>	<b>Bibliography</b>	<b>92</b>
<b>I</b>	<b>Object identifiers defined in ISO/IEC 11582</b>	<b>93</b>
<b>J</b>	<b>“Recipe” for migration of X.208 / X.209 based QSIG ASN.1 modules to X.680 / X.690 ASN.1</b>	<b>95</b>
<b>K</b>	<b>ASN.1 definitions according to ITU-T Recs. X.208 / X.209</b>	<b>100</b>
<b>L</b>	<b>Technical changes since third edition of ECMA-165</b>	<b>112</b>