ISO/IEC 22051:2002-10 (E)

Information technology_- Data interchange on 12,7_mm, 448-track magnetic tape cartridges_- SDLT1_format

Contents

1	**Scope**	**1**
2	**Conformance**	**1**
2.1	Magnetic tape cartridges	**1**
2.2	Generating systems	**1**
2.3	Receiving systems	**1**
3	Normative references	**1**
4	Terms and definitions	**1**
4.1	back surface	**1**
4.2	Beginning-Of-Tape marker (BOT)	**1**
4.3	block	**2**
4.4	byte	**2**
4.5	cartridge	**2**
4.6	Cyclic Redundancy Check (CRC) character	**2**
4.7	Error-Detecting Code (EDC)	**2**
4.8	End-Of-Tape marker (EOT)	**2**
4.9	Entity	**2**
4.10	Error-Correcting Code (ECC)	**2**
4.11	Envelope	**2**
4.12	Envelope size	**2**
4.13	flux transition position	**2**
4.14	flux transition spacing	**2**
4.15	logical track	**2**
4.16	magnetic tape	**2**
4.17	Master Standard Reference Tape	**2**
4.18	object	**2**
4.19	page	**2**
4.20	recording density	**2**
4.21	physical track	**2**
4.22	Record	**3**
4.23	Reference Edge	**3**
4.24	Reference Field	**3**
4.25	Secondary Standard Reference Tape	**3**
4.26	Standard Reference Amplitude (SRA)	**3**
4.27	Standard Reference Current	**3**
4.28	Test Recording Current	**3**
4.29	Typical Field	**3**
5	Conventions and notations	**3**
5.1	Representation of numbers	**3**
5.2	Dimensions	**3**
5.3	Names	**3**
5.4	Acronyms	**3**
6	Environment and safety	**4**
6.1	Cartridge and tape testing environment	**4**
6.2	Cartridge operating environment	**4**
6.3	Cartridge storage environment	**4**
6.4	Safety	**4**
6.5	Flammability	**4**
6.6	Transportation	**4**

Section 2 - Requirements for the unrecorded tape **5**

7 Mechanical and electrical requirements **5**

7.1 Material **5**
7.2 Tape length **5**
7.3 Tape width **5**
7.4 Tape thickness **5**
7.5 Discontinuity **5**
7.6 Longitudinal curvature **5**

7.6.1 Requirements **5**
7.6.2 Procedure **5**

7.7 Out-of-Plane distortions **5**
7.8 Cupping **5**
7.9 Roughness of the coating surfaces **6**

7.9.1 Roughness of the back coating surface **6**
7.9.2 Roughness of the magnetic coating surface **6**

7.10 Coating adhesion **6**
7.11 Layer-to-layer adhesion **6**

7.11.1 Requirements **6**
7.11.2 Procedure **6**

7.12 Modulus of elasticity **7**

7.12.1 Requirement **7**
7.12.2 Procedure **7**

7.13 Flexural rigidity **8**

7.13.1 Requirement **8**
7.13.2 Procedure **8**

7.14 Tensile yield force **8**

7.14.1 Procedure **8**

7.15 Electrical resistance **8**

7.15.1 Requirement **8**
7.15.2 Procedure **8**

7.16 Inhibitor tape **9**
7.17 Light transmittance of the tape and the leader **9**
7.18 Abrasivity **9**
7.19 Coefficient of dynamic friction **9**

7.19.1 Requirements **9**
7.19.2 Procedure for the measurement of the friction between the magnetic surface and the back surface **9**
7.19.3 Procedure for the measurement of the friction between the magnetic surface or the back surface and calcium titanate ceramic **10**

7.20 Servo **10**

7.20.1 Servo Bands **10**
7.20.2 Servo Tracks **11**
7.20.3 Signal **11**
7.20.4 Signal-to Noise Ratio **11**
7.20.5 Missing servo mark **11**

8 Magnetic recording characteristics **12**

8.1 Typical Field **13**
8.2 Signal amplitude **13**
8.3 Resolution **13**
8.4 Overwrite **13**
8.4.1 Requirement **13**
9 Tape quality **13**
9.1 Missing pulses **13**
9.1.1 Requirement **13**
9.2 Missing pulse zone **13**
9.2.1 Requirement **13**
9.3 Tape durability **13**
Section 3 - Mechanical specifications of the tape cartridge **14**
10 General **14**
10.1 Bottom side and right side **14**
10.2 Back side and left side **15**
10.3 Tape reel **16**
10.4 Tape leader **17**
10.5 Front side **18**
10.6 Operation of the cartridge **18**
10.7 Tape winding **19**
10.8 Moment of inertia **19**
10.9 Material **19**
Section 4 - Requirements for an interchanged tape **29**
11 Tape format **29**
11.1 Reference Edge **29**
11.2 Direction of recording **29**
11.3 Tape layout **29**
11.3.1 Data Area **29**
11.3.2 Forward Alignment and Directory Area **31**
11.3.3 Reverse Alignment Area at EOT **32**
12 Data format **33**
12.1 Record **33**
12.2 Data Bytes **33**
12.3 Data Field **33**
12.3.1 Pages **34**
12.3.2 Pad Bytes **34**
12.3.3 Page layout **34**
12.3.4 MAP entries **34**
12.3.5 EDC **35**
12.4 Data Blocks **35**
12.4.1 Control Field 1 (CF1) **36**
12.4.2 Control Field 2 (CF2) **37**
12.4.3 CRC **39**
13 Method of recording **39**
13.1 Physical recording density **40**
13.2 Channel bit cell length **40**

13.2.1 Average Channel bit cell length **40**
13.2.2 Long-term average Channel bit cell length **40**
13.2.3 Short-term average Channel bit cell length **40**

13.3 Read signal amplitude **40**
13.4 Channel skew **40**

14 Block Recording Format **41**

14.1 Scrambler **41**
14.2 Modulation **41**

14.2.1 Modulation process **41**
14.2.2 Modulated Data Group **42**

14.3 Precoder **42**
14.4 Recording Data Block **43**

14.4.1 Preamble **43**
14.4.2 Sync **43**

15 Types and Use of Blocks **43**

15.1 Types of Blocks **43**
15.2 Use of blocks **43**

15.2.1 Track ID Start Blocks **43**
15.2.2 End of Track Blocks (EOTR) **44**
15.2.3 End of Data of Data Blocks (EOD) **44**
15.2.4 ECC Blocks **44**
15.2.5 Track ID End Blocks **44**

16 Format of Entities **44**

17 Format of Envelopes **44**

18 Error handling **44**

Annexes

A - Measurement of light transmittance **45**

B - Procedure for the measurement of abrasivity **48**

C - Generation of the Data Block CRCs **50**

D - Generation of page CRCs **51**

E - ECC generation **52**

F - Allocation of Physical Tracks to Logical Tracks **55**

G - Recommendations for transportation **56**

H - Inhibitor tape **57**

J - Recommendations on tape durability **58**

K - Handling guidelines **59**