

ISO/IEC 11801:2002-09 (E)

Information technology_ - Generic cabling for customer premises

CONTENTS

- FOREWORD 10
- INTRODUCTION 11
- 1 Scope 13
- 2 Normative references..... 13
- 3 Definitions, abbreviations and symbols 17
 - 3.1 Definitions 17
 - 3.2 Abbreviations..... 23
 - 3.3 Symbols 24
 - 3.3.1 Variables 24
 - 3.3.2 Indices 25
- 4 Conformance 25
- 5 Structure of the generic cabling system 26
 - 5.1 General 26
 - 5.2 Functional elements..... 26
 - 5.3 Cabling subsystems..... 27
 - 5.3.1 General..... 27
 - 5.3.2 Campus backbone cabling subsystem..... 27
 - 5.3.3 Building backbone cabling subsystem 28
 - 5.3.4 Horizontal cabling subsystem..... 28
 - 5.3.5 Design objectives..... 28
 - 5.4 Interconnection of subsystems..... 29
 - 5.4.1 General..... 29
 - 5.4.2 Centralised cabling architecture 30
 - 5.5 Accommodation of functional elements 30
 - 5.6 Interfaces 30
 - 5.6.1 Equipment interfaces and test interfaces..... 30
 - 5.6.2 Channel and permanent link 32
 - 5.6.3 External network interface..... 32
 - 5.7 Dimensioning and configuring..... 32
 - 5.7.1 Distributors 32
 - 5.7.2 Cables 34
 - 5.7.3 Work area cords and equipment cords 34
 - 5.7.4 Patch cords and jumpers 34
 - 5.7.5 Telecommunications outlet (TO) 35
 - 5.7.6 Consolidation point 36
 - 5.7.7 Telecommunications rooms and equipment rooms 36
 - 5.7.8 Building entrance facilities 36
 - 5.7.9 External services cabling 36
- 6 Performance of balanced cabling 37
 - 6.1 General 37
 - 6.2 Layout 38
 - 6.3 Classification of balanced cabling 39
 - 6.4 Balanced cabling performance..... 39
 - 6.4.1 General..... 39

6.4.2	Return loss	39
6.4.3	Insertion loss/attenuation	40
6.4.4	NEXT	41
6.4.5	Attenuation to crosstalk ratio (ACR)	44
6.4.6	ELFEXT	45
6.4.7	Direct current (d.c.) loop resistance	47
6.4.8	Direct current (d.c.) resistance unbalance	48
6.4.9	Current carrying capacity	48
6.4.10	Operating voltage	48
6.4.11	Power capacity	48
6.4.12	Propagation delay	48
6.4.13	Delay skew	49
6.4.14	Unbalance attenuation	49
6.4.15	Coupling attenuation	50
7	Reference implementations for balanced cabling	50
7.1	General	50
7.2	Balanced cabling	50
7.2.1	General.....	50
7.2.2	Horizontal cabling	50
7.2.3	Backbone cabling.....	54
8	Performance of optical fibre cabling	55
8.1	General	55
8.2	Component choice	55
8.3	Channel attenuation.....	56
8.4	Channel topology.....	56
8.5	Propagation delay.....	58
9	Cable requirements.....	58
9.1	General	58
9.2	Balanced cables	58
9.2.1	Basic performance requirements.....	58
9.2.2	Additional requirements	59
9.2.3	Additional performance requirements for flexible cables.....	60
9.3	Additional crosstalk considerations for cable sharing in balanced cables	60
9.3.1	General.....	60
9.3.2	Power summation in backbone cables.....	60
9.3.3	Hybrid, multi-unit and cables connected to more than one TO.....	60
9.4	Optical fibre cables	61
9.4.1	Optical fibre types	61
9.4.2	Generic performance requirements	61
9.4.3	Multimode optical fibre cable.....	61
9.4.4	Single-mode optical fibre cables	62
10	Connecting hardware requirements.....	62
10.1	General requirements	62
10.1.1	Applicability	62
10.1.2	Location.....	63
10.1.3	Design	63
10.1.4	Operating environment.....	63
10.1.5	Mounting.....	63

10.1.6	Installation practices	63
10.1.7	Marking and colour coding	64
10.2	Connecting hardware for balanced cabling	64
10.2.1	General requirements	64
10.2.2	Performance marking	64
10.2.3	Mechanical characteristics	64
10.2.4	Electrical characteristics	66
10.2.5	Telecommunications outlet requirements	72
10.2.6	Design considerations for installation	73
10.3	Optical fibre connecting hardware	74
10.3.1	General requirements	74
10.3.2	Marking and colour coding	74
10.3.3	Mechanical and optical characteristics	74
10.3.4	Telecommunications outlet requirements	75
10.3.5	Connection schemes for optical fibre cabling	75
11	Screening practices	77
11.1	General	77
11.2	Electromagnetic performance	77
11.3	Earthing	78
12	Administration	78
13	Balanced cords	78
13.1	Introduction	78
13.2	Insertion loss	78
13.3	Return loss	79
13.4	NEXT	79
Annex A (normative)	Balanced permanent link and CP link performance	82
A.1	General	82
A.2	Performance	82
A.2.1	General	82
A.2.2	Return loss	83
A.2.3	Insertion loss/attenuation	84
A.2.4	NEXT	85
A.2.5	Attenuation to crosstalk ratio (ACR)	88
A.2.6	ELFEXT	89
A.2.7	Direct current (d.c.) loop resistance	92
A.2.8	Direct current (d.c.) resistance unbalance	93
A.2.9	Propagation delay	93
A.2.10	Delay skew	94
Annex B (normative)	Test procedures	96
B.1	General	96
B.2	Channel and link performance testing	96
B.2.1	Testing balanced cabling channels, permanent links and CP links	96
B.2.2	Testing optical fibre cabling channels	96
B.2.3	Channel and link test schedules	96
B.3	Transmission testing of cords for balanced cabling	97
B.4	Transmission testing of components for cabling	98
B.4.1	Transmission testing of copper cables for balanced cabling	98

B.4.2	Transmission testing of connecting hardware for balanced cabling	98
B.4.3	Transmission testing of cables for optical cabling.....	98
B.4.4	Transmission testing of connectors for optical cabling.....	98
Annex C (normative)	Mechanical and environmental performance testing of connecting hardware for balanced cabling	99
C.1	Introduction.....	99
C.2	Test requirements.....	99
C.2.1	General.....	99
C.2.2	Initial test measurements	99
C.2.3	Environmental and mechanical performance	100
Annex D (informative)	Electromagnetic characteristics	104
Annex E (informative)	Acronyms for balanced cables	105
Annex F (informative)	Supported applications	107
F.1	Supported applications for balanced cabling	107
F.2	Supported applications for optical fibre cabling	109
Annex G (informative)	Channel and permanent link models for balanced cabling	113
G.1	General	113
G.2	Insertion loss	113
G.2.1	Insertion loss of the channel configuration	113
G.2.2	Insertion loss of the permanent link configurations.....	114
G.2.3	Assumptions for insertion loss	114
G.3	NEXT.....	115
G.3.1	NEXT of the channel configuration.....	115
G.3.2	NEXT of the permanent link configurations	115
G.3.3	Assumptions for NEXT	116
G.4	ELFEXT.....	119
G.4.1	ELFEXT of the channel configuration.....	119
G.4.2	ELFEXT for the permanent link configurations	119
G.4.3	Assumptions for ELFEXT	120
G.5	Return loss	120
G.5.1	Return loss of the channel and permanent link configurations	120
G.5.2	Assumptions for the return loss circuit analysis method	121
Annex H (informative)	Class F channel and permanent link with two connections.....	124
Annex I (informative)	Significant changes to balanced cabling requirements with respect to earlier editions of this International Standard.....	125
I.1	General	125
I.2	References	125
I.3	Structural elements.....	125
I.4	Product designation	125
I.5	Component requirements.....	125
I.6	Installed cabling requirements	126
Bibliography	132

Figure 1 – Structure of generic cabling.....	27
Figure 2 – Hierarchical structure of generic cabling.....	29
Figure 3 – Structures for centralised generic cabling.....	29
Figure 4 – Accommodation of functional elements.....	30
Figure 5 – Interconnect models.....	31
Figure 6 – Cross-connect models.....	31
Figure 7 – Equipment and test interfaces.....	31
Figure 8 – Example of a generic cabling system with combined BD and FD.....	33
Figure 9 – Inter-relationship of functional elements in an installation with redundancy.....	34
Figure 10 – Channel, permanent link and CP link of a balanced cabling.....	37
Figure 11 – Example of a system showing the location of cabling interfaces and extent of associated channels.....	38
Figure 12 – Horizontal cabling models.....	52
Figure 13 – Backbone cabling model.....	54
Figure 14 – Combined backbone/horizontal channels.....	57
Figure 15 – Eight-position outlet pin and pair grouping assignments (front view of connector).....	73
Figure 16 – Duplex SC connectivity configuration.....	76
Figure 17 – Optical fibre patch cord.....	77
Figure A.1 – Link options.....	82
Figure E.1 – Cable naming schema.....	105
Figure E.2 – Cable types.....	106
Figure G.1 – Example of computation of NEXT with higher precision.....	116
Figure H.1 – Two connection channel and permanent link.....	124
Figure I.1 – Horizontal cabling model.....	127
Figure I.2 – Backbone cabling model.....	127

Table 1 – Maximum channel lengths	32
Table 2 – Return loss for channel.....	40
Table 3 – Informative return loss values for channel at key frequencies	40
Table 4 – Insertion loss for channel.....	41
Table 5 – Informative insertion loss values for channel at key frequencies	41
Table 6 – NEXT for channel	42
Table 7 – Informative NEXT values for channel at key frequencies.....	42
Table 8 – PS NEXT for channel.....	43
Table 9 – Informative PS NEXT values for channel at key frequencies	43
Table 10 – Informative ACR values for channel at key frequencies.....	44
Table 11 – Informative PS ACR values for channel at key frequencies	45
Table 12 – ELFEXT for channel.....	46
Table 13 – Informative ELFEXT values for channel at key frequencies	46
Table 14 – PS ELFEXT for channel	47
Table 15 – Informative PS ELFEXT values for channel at key frequencies	47
Table 16 – Direct current (d.c.) loop resistance for channel.....	47
Table 17 – Propagation delay for channel	48
Table 18 – Informative propagation delay values for channel at key frequencies	49
Table 19 – Delay skew for channel.....	49
Table 20 – Unbalance attenuation for channel.....	50
Table 21 – Horizontal link length equations	53
Table 22 – Backbone link length equations	55
Table 23 – Channel attenuation.....	56
Table 24 – Basic requirements of balanced cables	58
Table 25 – Mechanical characteristics of balanced cables.....	59
Table 26 – Optical fibre cable attenuation	61
Table 27 – Multimode optical fibre modal bandwidth.....	62
Table 28 – Mechanical characteristics of connecting hardware for use with balanced cabling	65
Table 29 – Electrical characteristics of telecommunications outlets intended for use with balanced cabling	67
Table 30 – Return loss	68
Table 31 – Insertion loss	68
Table 32 – Near end crosstalk (NEXT)	68
Table 33 – Power sum near end crosstalk (PS NEXT).....	69
Table 34 – Far end crosstalk (FEXT).....	69
Table 35 – Power sum far end crosstalk (PS FEXT	70
Table 36 – Input to output resistance	70
Table 37 – Input to output resistance unbalance	70
Table 38 – Current carrying capacity.....	71
Table 39 – Propagation delay.....	71
Table 40 – Delay skew	71

Table 41 – Transverse conversion loss (TCL) f.f.s.....	71
Table 42 – Transfer impedance (screened connectors only).....	72
Table 43 – Insulation resistance.....	72
Table 44 – Voltage proof.....	72
Table 45 – Matrix of backward compatible mated modular connector performance.....	73
Table 46 – Mechanical and optical characteristics of optical fibre connecting hardware.....	75
Table 47 – Minimum return loss for balanced cords.....	79
Table 48 – Informative values of return loss at key frequencies for Category 5, 6 and 7 cords.....	79
Table 49 – Informative values of NEXT at key frequencies for Category 5, 6 and 7 cords.....	81
Table A.1 – Return loss for permanent link or CP link.....	83
Table A.2 – Informative return loss values for permanent link with maximum implementation at key frequencies.....	83
Table A.3 – Insertion loss for permanent link or CP link.....	84
Table A.4 – Informative insertion loss values for permanent link with maximum implementation at key frequencies.....	85
Table A.5 – NEXT for permanent link or CP link.....	86
Table A.6 – Informative NEXT values for permanent link with maximum implementation at key frequencies.....	86
Table A.7 – PS NEXT for permanent link or CP link.....	87
Table A.8 – Informative PS NEXT values for permanent link with maximum implementation at key frequencies.....	88
Table A.9 – Informative ACR values for permanent link with maximum implementation at key frequencies.....	89
Table A.10 – Informative PS ACR values for permanent link with maximum implementation at key frequencies.....	89
Table A.11 – ELFEXT for permanent link or CP link.....	90
Table A.12 – Informative ELFEXT values for permanent link with maximum implementation at key frequencies.....	91
Table A.13 – PS ELFEXT for permanent link or CP link.....	92
Table A.14 – Informative PS ELFEXT values for permanent link with maximum implementation at key frequencies.....	92
Table A.15 – Direct current (d.c.) loop resistance for permanent link or CP link.....	93
Table A.16 – Informative d.c. loop resistance for permanent link with maximum implementation.....	93
Table A.17 – Propagation delay for permanent link or CP link.....	94
Table A.18 – Informative propagation delay values for permanent link with maximum implementation at key frequencies.....	94
Table A.19 – Delay skew for permanent link or CP link.....	95
Table A.20 – Informative delay skew for permanent link with maximum implementation.....	95
Table B.1 – Cabling characteristics of copper and optical fibre cabling for acceptance, compliance and reference testing.....	97
Table C.1 – Group P.....	100
Table C.2 – Group A.....	101
Table C.3 – Group B.....	102
Table C.4 – Group C.....	103

Table C.5 – Group D	103
Table F.1 – Applications using balanced cabling	108
Table F.2 – Modular connector pin assignment for applications.....	109
Table F.3 – Supported applications using optical fibre cabling.....	110
Table F.4 – Maximum channel lengths supported by optical fibre applications for multimode fibre	111
Table F.5 – Maximum channel length supported by optical fibre applications for single-mode fibres	112
Table G.1 – Insertion loss deviation.	114
Table H.1 – ACR and PS ACR values for 2 connection class F channels and permanent links at key frequencies	124
Table I.1 – Principal transmission performance requirements of 150 Ω connecting hardware.....	126
Table I.2 – Minimum return loss limits for links, permanent links and channels for the different cabling classes.....	128
Table I.3 – Maximum attenuation limits for links, permanent links and channels for the different cabling classes.....	128
Table I.4 – Minimum NEXT limits for links, permanent links and channels for the different cabling classes.....	129
Table I.5 – Minimum ACR limits for links, permanent links and channels for the different cabling classes.....	129
Table I.6 – Maximum propagation delay limits for links, permanent links and channels for the different cabling classes.....	130
Table I.7 – Maximum d.c. loop resistance limits for links, permanent links and channels for the different cabling classes.....	130
Table I.8 – Minimum unbalance attenuation (LCL/LCTL) limits for links, permanent links and channels for the different cabling classes	130
Table I.9 – Minimum PS NEXT, PS ACR, ELFEXT and PS ELFEXT limits for permanent links and channels for the different cabling classes.....	131
Table I.10 – Maximum delay skew limits for permanent links and channels for the different cabling classes.....	131