

# ISO/IEC 15431:2003-04 (E)

## Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Inter-exchange signalling protocol — Wireless terminal call handling additional network features

---

### Contents

Foreword	vi
Introduction	vii
<b>1</b> Scope	<b>1</b>
<b>2</b> Conformance	<b>1</b>
<b>3</b> Normative references	<b>1</b>
<b>4</b> Terms and definitions	<b>2</b>
<b>4.1</b> External definitions	<b>2</b>
<b>4.2</b> Other definitions	<b>3</b>
<b>4.2.1</b> Alternative identifier	<b>3</b>
<b>4.2.2</b> Home data base (HDB)	<b>3</b>
<b>4.2.3</b> Home PINX	<b>3</b>
<b>4.2.4</b> Rerouteing PINX	<b>3</b>
<b>4.2.5</b> Visitor data base (VDB)	<b>3</b>
<b>4.2.6</b> Visitor PINX	<b>3</b>
<b>4.2.7</b> WTMI-detect PINX	<b>3</b>
<b>5</b> Symbols and abbreviated terms	<b>4</b>
<b>6</b> Signalling protocol for the support of ANF-WTMI	<b>4</b>
<b>6.1</b> ANF-WTMI description	<b>4</b>
<b>6.2</b> ANF-WTMI operational requirements	<b>5</b>
<b>6.2.1</b> Requirements on the Rerouteing PINX	<b>5</b>
<b>6.2.2</b> Requirements on the WTMI-detect PINX	<b>5</b>
<b>6.2.3</b> Requirements on the Home PINX	<b>5</b>
<b>6.2.4</b> Requirements on the Visitor PINX	<b>5</b>
<b>6.2.5</b> Requirements on a Transit PINX	<b>5</b>
<b>6.3</b> ANF-WTMI coding requirements	<b>6</b>
<b>6.3.1</b> Operations	<b>6</b>
<b>6.3.2</b> Information elements	<b>8</b>
<b>6.3.3</b> Messages	<b>9</b>
<b>6.4</b> ANF-WTMI state definitions	<b>9</b>
<b>6.4.1</b> States at the Rerouteing PINX	<b>9</b>
<b>6.4.2</b> States at the WTMI-detect PINX	<b>9</b>
<b>6.4.3</b> States at the Home PINX	<b>9</b>
<b>6.4.4</b> States at the Visitor PINX	<b>9</b>
<b>6.5</b> ANF-WTMI signalling procedures for invocation and operation	<b>9</b>
<b>6.5.1</b> Actions at the Rerouteing PINX	<b>9</b>
<b>6.5.2</b> Actions at the WTMI-detect PINX	<b>10</b>
<b>6.5.3</b> Actions at the Home PINX	<b>11</b>
<b>6.5.4</b> Actions at the Visitor PINX	<b>12</b>
<b>6.5.5</b> Actions at a Transit PINX	<b>12</b>
<b>6.5.6</b> Actions at an Originating PINX	<b>12</b>
<b>6.6</b> ANF-WTMI impact of interworking with public ISDNs	<b>12</b>
<b>6.7</b> ANF-WTMI impact of interworking with non-ISDNs	<b>13</b>
<b>6.8</b> Protocol interactions between ANF-WTMI and other supplementary services and ANFs	<b>13</b>

<b>6.8.1</b>	Interaction with Calling Name Identification Presentation (SS-CNIP)	<b>13</b>
<b>6.8.2</b>	Interaction with Connected Name Identification Presentation (SS-CONP)	<b>13</b>
<b>6.8.3</b>	Interaction with Call Completion to Busy Subscriber (SS-CCBS)	<b>13</b>
<b>6.8.4</b>	Interaction with Call Completion on No Reply (SS-CCNR)	<b>13</b>
<b>6.8.5</b>	Interaction with Call Transfer (SS-CT)	<b>13</b>
<b>6.8.6</b>	Interaction with Call Forwarding Unconditional (SS-CFU)	<b>13</b>
<b>6.8.7</b>	Interaction with Call Forwarding Busy (SS-CFB)	<b>13</b>
<b>6.8.8</b>	Interaction with Call Forwarding No Reply (SS-CFNR)	<b>13</b>
<b>6.8.9</b>	Interaction with Call Deflection (SS-CD)	<b>13</b>
<b>6.8.10</b>	Interaction with Path Replacement (ANF-PR)	<b>13</b>
<b>6.8.11</b>	Interaction with Call Offer (SS-CO)	<b>13</b>
<b>6.8.12</b>	Interaction with Call Intrusion (SS-CI)	<b>14</b>
<b>6.8.13</b>	Interaction with Do Not Disturb (SS-DND)	<b>14</b>
<b>6.8.14</b>	Interaction with Do Not Disturb Override (SS-DNDO)	<b>14</b>
<b>6.8.15</b>	Interaction with Advice Of Charge (SS-AOC)	<b>14</b>
<b>6.8.16</b>	Interaction with Recall (SS-RE)	<b>14</b>
<b>6.8.17</b>	Interaction with Call Interception (ANF-CINT)	<b>14</b>
<b>6.8.18</b>	Interaction with Transit Counter (ANF-TC)	<b>14</b>
<b>6.8.19</b>	Interaction with Route Restriction Class (ANF-RRC)	<b>14</b>
<b>6.8.20</b>	Interaction with Message Waiting Indication (SS-MWI)	<b>15</b>
<b>6.8.21</b>	Interaction with Wireless Terminal Location Registration (SS-WTLR)	<b>15</b>
<b>6.8.22</b>	Interaction with Wireless Terminal Information (ANF-WTINFO)	<b>15</b>
<b>6.8.23</b>	Interaction with Wireless Terminal Outgoing Call (ANF-WTMO)	<b>15</b>
<b>6.8.24</b>	Interaction with Wireless Terminal Authentication of the Terminal (SS-WTAT)	<b>15</b>
<b>6.8.25</b>	Interaction with Wireless Terminal Authentication of the Network (SS-WTAN)	<b>15</b>
<b>6.9</b>	ANF-WTMI parameter values (timers)	<b>16</b>
<b>6.9.1</b>	Timer T1	<b>16</b>
<b>6.9.2</b>	Timer T2	<b>16</b>
<b>7</b>	Signalling protocol for the support of ANF-WTMO	<b>16</b>
<b>7.1</b>	ANF-WTMO description	<b>16</b>
<b>7.2</b>	ANF-WTMO operational requirements	<b>16</b>
<b>7.2.1</b>	Requirements on the Originating PINX	<b>16</b>
<b>7.2.2</b>	Requirements on the Home PINX	<b>16</b>
<b>7.2.3</b>	Requirements on a Transit PINX	<b>16</b>
<b>7.3</b>	ANF-WTMO coding requirements	<b>16</b>
<b>7.3.1</b>	Operations	<b>16</b>
<b>7.3.2</b>	Information elements	<b>16</b>
<b>7.3.3</b>	Messages	<b>16</b>
<b>7.4</b>	ANF-WTMO state definitions	<b>17</b>
<b>7.4.1</b>	States at the Originating PINX	<b>17</b>
<b>7.4.2</b>	States at the Home PINX	<b>17</b>
<b>7.5</b>	ANF-WTMO signalling procedures	<b>17</b>
<b>7.5.1</b>	Actions at the Originating PINX	<b>17</b>
<b>7.5.2</b>	Actions at the Home PINX	<b>17</b>
<b>7.5.3</b>	Actions at the Transit PINX	<b>18</b>
<b>7.6</b>	ANF-WTMO impact of interworking with public ISDNs	<b>18</b>
<b>7.7</b>	ANF-WTMO impact of interworking with non-ISDNs	<b>18</b>
<b>7.8</b>	Protocol interactions between ANF-WTMO and other supplementary services and ANFs	<b>18</b>
<b>7.8.1</b>	Interaction with Calling Name Identification Presentation (SS-CNIP)	<b>18</b>
<b>7.8.2</b>	Interaction with Connected Name Identification Presentation (SS-CONP)	<b>18</b>

<b>7.8.3</b>	Interaction with Call Completion to Busy Subscriber (SS-CCBS)	<b>18</b>
<b>7.8.4</b>	Interaction with Call Completion on No Reply (SS-CCNR)	<b>18</b>
<b>7.8.5</b>	Interaction with Call Transfer (SS-CT)	<b>18</b>
<b>7.8.6</b>	Interaction with Call Diversion (SS-CFU, SS-CFB, SS-CFNR, SS-CD)	<b>18</b>
<b>7.8.7</b>	Interaction with Path Replacement (ANF-PR)	<b>19</b>
<b>7.8.8</b>	Interaction with Call Offer (SS-CO)	<b>19</b>
<b>7.8.9</b>	Interaction with Call Intrusion (SS-CI)	<b>19</b>
<b>7.8.10</b>	Interaction with Do Not Disturb (SS-DND)	<b>19</b>
<b>7.8.11</b>	Interaction with Do Not Disturb Override (SS-DNDO)	<b>19</b>
<b>7.8.12</b>	Interaction with Advice of Charge (SS-AOC)	<b>19</b>
<b>7.8.13</b>	Interaction with Recall (SS-RE)	<b>19</b>
<b>7.8.14</b>	Interaction with Call Interception (ANF-CINT)	<b>19</b>
<b>7.8.15</b>	Interaction with Transit Counter (ANF-TC)	<b>19</b>
<b>7.8.16</b>	Interaction with Route Restriction Class (ANF-RRC)	<b>19</b>
<b>7.8.17</b>	Interaction with Message Waiting Indication (SS-MWI)	<b>19</b>
<b>7.8.18</b>	Interaction with Wireless Terminal Location Registration (SS-WTLR)	<b>19</b>
<b>7.8.19</b>	Interaction with Wireless Terminal Information (ANF-WTINFO)	<b>19</b>
<b>7.8.20</b>	Interaction with Wireless Terminal Incoming Call (ANF-WTMI)	<b>19</b>
<b>7.8.21</b>	Interaction with Wireless Terminal Authentication of the Terminal (SS-WTAT)	<b>19</b>
<b>7.8.22</b>	Interaction with Wireless Terminal Authentication of the Network (SS-WTAN)	<b>20</b>
<b>7.9</b>	Parameter values (timers)	<b>20</b>
<b>7.9.1</b>	Timers at the Originating PINX	<b>20</b>
<b>7.9.2</b>	Timers at the Home PINX	<b>20</b>
<b>Annexes</b>		
<b>A</b>	Protocol Implementation Conformance Statement (PICS) proforma	<b>21</b>
<b>B</b>	Imported ASN.1 definitions	<b>31</b>
<b>C</b>	Examples of Message Sequences	<b>32</b>
<b>D</b>	Specification and Description Language (SDL) representation of procedures	<b>37</b>
<b>E</b>	ASN.1 definitions according to ITU-T Recs. X.208 / X.209	<b>45</b>