

ISO/IEC 23651:2003-08 (E)

Information technology — 8 mm wide magnetic tape cartridge for information interchange —
Helical scan recording — AIT-3 format

Contents

| | |
|--|----------|
| Section 1 - General | 1 |
| 1 Scope | 1 |
| 2 Conformance | 1 |
| 2.1 Magnetic tape cartridge | 1 |
| 2.2 Generating drive | 1 |
| 2.3 Receiving drive | 1 |
| 3 Normative references | 2 |
| 4 Terms and definitions | 2 |
| 4.1 Absolute Frame Number (AFN) | 2 |
| 4.2 a.c. erase | 2 |
| 4.3 Access | 2 |
| 4.4 algorithm | 2 |
| 4.5 Area ID | 2 |
| 4.6 Automatic Track Finding (ATF) | 2 |
| 4.7 Average Signal Amplitude | 2 |
| 4.8 azimuth | 2 |
| 4.9 back surface | 2 |
| 4.10 byte | 2 |
| 4.11 cartridge | 2 |
| 4.12 Channel bit | 3 |
| 4.13 Codeword | 3 |
| 4.14 Early Warning Point (EWP) | 3 |
| 4.15 End of Data (EOD) | 3 |
| 4.16 Entity | 3 |
| 4.17 Error Correcting Code (ECC) | 3 |
| 4.18 flux transition position | 3 |
| 4.19 flux transition spacing | 3 |
| 4.20 Frame | 3 |
| 4.21 Housekeeping Frame | 3 |
| 4.22 Logical Beginning of Tape (LBOT) | 3 |
| 4.23 magnetic tape | 3 |
| 4.24 Master Standard Amplitude Calibration Tape | 3 |
| 4.25 Master Standard Reference Tape | 3 |
| 4.26 Partition Boundary | 3 |
| 4.27 Physical Beginning of Tape (PBOT) | 3 |
| 4.28 Physical End of Tape (PEOT) | 4 |
| 4.29 physical recording density | 4 |
| 4.30 pre-recording condition | 4 |
| 4.31 processing | 4 |
| 4.32 processed data | 4 |
| 4.33 Processed Record | 4 |
| 4.34 record | 4 |
| 4.35 Reference Field | 4 |
| 4.36 Remote Memory In Cartridge (RMIC) | 4 |
| 4.37 Secondary Standard Amplitude Calibration Tape | 4 |
| 4.38 Secondary Standard Reference Tape | 4 |

| | | |
|---|---|-----------|
| 4.39 | Separator Mark | 4 |
| 4.40 | Standard Reference Amplitude (SRA) | 4 |
| 4.41 | Standard Reference Current | 4 |
| 4.42 | Tape Reference Edge | 4 |
| 4.43 | Test Recording Current | 4 |
| 4.44 | track | 5 |
| 4.45 | Typical Field | 5 |
| 4.46 | unprocessed data | 5 |
| 4.47 | Unprocessed Record | 5 |
| 5 | Conventions and Notations | 5 |
| 5.1 | Representation of numbers | 5 |
| 5.2 | Names | 5 |
| 6 | Acronyms | 5 |
| 7 | Environment and safety | 6 |
| 7.1 | Test environment | 6 |
| 7.2 | Operating environment | 6 |
| 7.3 | Storage environment | 6 |
| 7.4 | Transportation | 6 |
| 7.5 | Safety | 6 |
| 7.6 | Flammability | 6 |
| Section 2 - Requirements for the case | | 6 |
| 8 | Dimensional and mechanical characteristics of the case | 6 |
| 8.1 | General | 6 |
| 8.2 | Overall dimension | 7 |
| 8.3 | Holding areas | 7 |
| 8.4 | Cartridge insertion | 8 |
| 8.5 | Window | 8 |
| 8.6 | Loading grips | 9 |
| 8.7 | Label areas | 9 |
| 8.8 | Datum areas and Datum holes | 9 |
| 8.9 | Support areas | 10 |
| 8.10 | Recognition holes | 10 |
| 8.11 | Write-inhibit hole | 11 |
| 8.12 | Pre-positioning surfaces | 12 |
| 8.13 | Cartridge lid | 12 |
| 8.14 | Cartridge reel lock | 13 |
| 8.15 | Reel access holes | 14 |
| 8.16 | Interface between the reels and the drive spindles | 14 |
| 8.17 | Light path | 15 |
| 8.18 | Position of the tape in the case | 16 |
| 8.19 | Tape path zone | 16 |
| 8.20 | Tape access cavity | 16 |
| 8.21 | Tape access cavity clearance | 17 |
| 8.22 | Requirements for the RMIC | 17 |
| 8.23 | Recognition recesses | 18 |
| Section 3 - Requirements for the unrecorded tape | | 38 |
| 9 | Mechanical, physical and dimensional characteristics of the tape | 38 |
| 9.1 | Materials | 38 |
| 9.2 | Tape length | 38 |

| | | |
|------------------|---|-----------|
| 9.2.1 | Length of magnetic tape | 38 |
| 9.2.2 | Length of leader and trailer tapes | 38 |
| 9.2.3 | Length of the splicing tapes | 38 |
| 9.3 | Tape width | 38 |
| 9.3.1 | Width of magnetic, leader and trailer tapes | 38 |
| 9.3.2 | Width and position of the splicing tape | 38 |
| 9.4 | Discontinuities | 39 |
| 9.5 | Tape thickness | 39 |
| 9.5.1 | Thickness of the magnetic tape | 39 |
| 9.5.2 | Thickness of the leader and trailer tape | 39 |
| 9.5.3 | Thickness of the splicing tape | 39 |
| 9.6 | Longitudinal curvature | 39 |
| 9.7 | Cupping | 39 |
| 9.8 | Coating adhesion | 39 |
| 9.9 | Layer-to-layer adhesion | 40 |
| 9.10 | Tensile strength | 40 |
| 9.10.1 | Breaking strength | 40 |
| 9.10.2 | Yield strength | 40 |
| 9.11 | Residual elongation | 40 |
| 9.12 | Electrical resistance of the recording surface | 40 |
| 9.13 | Tape winding | 41 |
| 9.14 | Light transmittance of the tape | 41 |
| 9.15 | Recognition stripe | 41 |
| 10 | Magnetic recording characteristics | 42 |
| 10.1 | Typical Field | 42 |
| 10.2 | Signal Amplitude | 42 |
| 10.3 | Resolution | 43 |
| 10.4 | Overwrite | 43 |
| 10.5 | Ease of erasure | 43 |
| 10.6 | Tape quality | 43 |
| 10.6.1 | Missing pulses | 43 |
| 10.6.2 | Missing pulse zone | 43 |
| 10.7 | Signal-to-Noise Ratio (SNR) characteristic | 43 |
| Section 4 | Requirements for an interchanged tape | 44 |
| 11 | Format | 44 |
| 11.1 | General | 44 |
| 11.2 | Basic Groups | 44 |
| 11.2.1 | Entity | 45 |
| 11.2.2 | Group Information Table | 45 |
| 11.2.3 | Block Access Table (BAT) | 48 |
| 11.3 | Sub-Groups | 50 |
| 11.3.1 | G1 Sub-Group | 50 |
| 11.3.2 | G2 Sub-Group - Randomizing | 51 |
| 11.3.3 | G3 Sub-Group | 52 |
| 11.4 | Data Block | 53 |
| 11.4.1 | ID information | 53 |
| 11.4.2 | Recording of the ID Information in the Data Block Headers | 56 |
| 12 | Method of recording | 61 |
| 12.1 | Physical recording density | 62 |
| 12.2 | Long-term average bit cell length | 62 |
| 12.3 | Short-term average bit cell length | 62 |
| 12.4 | Rate of change | 62 |

| | | |
|-----------|--|-----------|
| 12.5 | Bit shift | 62 |
| 12.6 | Read signal amplitude | 62 |
| 12.7 | Maximum recorded levels | 62 |
| 13 | Track geometry | 62 |
| 13.1 | Track configuration | 62 |
| 13.2 | Average track pitch | 63 |
| 13.3 | Variations of the track pitch | 63 |
| 13.4 | Track width | 63 |
| 13.5 | Track angle | 63 |
| 13.6 | Track edge straightness | 63 |
| 13.7 | Track length | 63 |
| 13.8 | Azimuth angles | 63 |
| 14 | Recorded patterns | 64 |
| 14.1 | Recorded Data Block | 64 |
| 15 | Format of tracks | 64 |
| 15.1 | Track structure | 64 |
| 15.2 | Positioning accuracy | 64 |
| 15.3 | Tracking scheme | 64 |
| 15.4 | Generation of Margin Blocks | 65 |
| 16 | Layout of the tape | 66 |
| 16.1 | Device Area | 66 |
| 16.2 | Reference Area | 67 |
| 16.3 | Position Tolerance Band No. 1 | 67 |
| 16.4 | System Area | 67 |
| 16.4.1 | System Preamble | 67 |
| 16.4.2 | System Log | 67 |
| 16.4.3 | System Postamble | 72 |
| 16.4.4 | Position Tolerance Band No. 2 | 72 |
| 16.4.5 | Vendor Group Preamble | 72 |
| 16.5 | Data Area | 72 |
| 16.5.1 | Vendor Group | 72 |
| 16.5.2 | Recorded Data Group | 72 |
| 16.5.3 | ECC3 | 73 |
| 16.5.4 | Multiple Recorded Instances | 74 |
| 16.5.5 | Repeated Frames | 74 |
| 16.5.6 | Appending and overwriting | 75 |
| 16.6 | EOD Area | 76 |
| 16.7 | Optional Device Area | 76 |
| 16.8 | Logical End Of Tape (LEOT) | 77 |
| 16.9 | Logical Beginning of Tape (LBOT) | 77 |
| 16.10 | Early Warning Point - EWP | 77 |
| 16.11 | Empty Partition | 77 |
| 16.12 | Initialization | 77 |
| 17 | Housekeeping Frames | 78 |
| 17.1 | Amble Frames | 78 |
| 17.2 | System Amble Frames | 78 |
| 18 | AIT Remote Memory In Cartridge (AIT RMIC) | 78 |
| 18.1 | General | 78 |
| 18.2 | Content of the AIT RMIC | 78 |
| 18.2.1 | Manufacturer's Information Section | 79 |

| | | |
|------------------------|---|------------|
| 18.2.2 | Communication Information Section | 82 |
| 18.2.3 | Mechanism Error Log Information Section | 82 |
| 18.2.4 | Memory Management Information Section | 83 |
| 18.2.5 | Volume Information Section | 84 |
| 18.2.6 | Volume Use History Information Section | 85 |
| 18.3 | Memory Heap Management | 85 |
| 18.3.1 | Cell | 85 |
| 18.3.2 | Cell Header | 85 |
| 18.3.3 | Partition Information Cell | 87 |
| 18.3.4 | Physical Tape Directory Information Cell | 87 |
| 18.3.5 | User Volume Information Cell | 88 |
| 18.3.6 | User Partition Information Cell | 88 |
| 18.3.7 | Application Information Cell | 89 |
| 18.3.8 | Date and Time Stamp Information Cell | 90 |
| 18.3.9 | Media Identification Information Cell | 91 |
| 18.3.10 | Tape Alert Information Cell | 91 |
| 18.4 | Electrical interface | 92 |
| 18.5 | Environment | 92 |
| 18.5.1 | Electromagnetic Compatibility | 92 |
| 18.5.2 | Magnetic fields | 92 |
| 18.5.3 | X-rays | 92 |
| 18.6 | Operating Field | 92 |
| 18.7 | Message from AIT RMIC reader-writer to AIT RMIC | 92 |
| 18.8 | Message from AIT RMIC to AIT RMIC reader-writer | 93 |
| 18.8.1 | Load modulation | 94 |
| 18.9 | EDC | 95 |
| 18.10 | AIT RMIC states | 95 |
| 18.11 | Command and Response | 96 |
| 18.11.1 | Attention Command and Response | 97 |
| 18.11.2 | Attention Command and Response Type 1 | 97 |
| 18.11.3 | Attention Command and Response Type 2 | 97 |
| 18.11.4 | Read Command and Response | 98 |
| 18.11.5 | Write Command and Response | 98 |
| 18.11.6 | Status Command and Response | 98 |
| 18.11.7 | Reset Command and Response | 99 |
| 18.12 | Dialogue | 99 |
| 18.12.1 | Read data from AIT RMIC | 99 |
| 18.12.2 | Write data to AIT RMIC | 100 |
| 18.12.3 | Read and Write with Session ID | 101 |
| Annexes | | |
| A (normative) | - Measurement of light transmittance | 105 |
| B (normative) | - Measurement of Signal-to-Noise Ratio | 108 |
| C (normative) | - Method for determining the nominal and the maximum allowable recorded levels (pre-recording condition) | 109 |
| D (normative) | - Representation of 16-bit words by 18-Channel bits patterns | 110 |
| E (normative) | - Measurement of bit shift | 111 |
| F (normative) | - Method of measuring the straightness of track edges | 113 |
| G (normative) | - ECC calculation | 114 |
| H (informative) | - Recommendations for transportation | 117 |
| J (informative) | - Read-After-Write | 118 |
| K (informative) | - Basic Group No. 0 | 119 |
| L (informative) | - Chip for the AIT-3 format | 120 |
| M (informative) | - Generation of EDC bytes for the Error Detecting Code for G2 Sub-Groups | 121 |