ISO/IEC 23290:2004-10 (E)

Information technology - Telecommunications and information exchange betwe en systems - Private Integrated Services Network (PISN) - Mapping functions for the tunnelling of QSIG through H.323 networks

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Terms and definitions 2
4.1 External definitions 2
4.2 Other definitions 2
4.2.1 Call 2
4.2.2 Channel 3
4.2.3 Inter-PINX Connection (IPC) 3
4.2.4 Inter-PINX Link (IPL) 3
4.2.5 PINX roles 3

5 List of acronyms 3

6 Introduction 4
6.1 Reference configuration 4
6.2 Specific scenarios 4
6.3 Relationship with H.323 gateways 5

7 Capabilities at the Q reference point 6

8 Capabilities at the C reference point 6

9 Mapping functions 7
9.1 General requirements 7
9.2 Mapping of the DQ-channel 7
9.3 Mapping of the UQ-channel(s) 7
9.3.1 On-demand scenario 7
9.3.2 Semi-permanent scenario 7

10 IPC control procedures 8
10.1 Protocol identification 8
10.2 Registration with gatekeeper 8
10.3 Systems without gatekeeper 8
10.4 H.323 call establishment 8
10.4.1 Call admission 8
10.4.2 Outgoing call establishment 9
10.4.3 Incoming call establishment 9
10.5 Transfer of inter-PINX signalling information 10
10.6 H.323 call clearing 10

11 Scenario specific procedures 10

11.1 On-demand scenario 10
11.2 Semi-permanent scenario 11

Annex A (normative) Implementation Conformance Statement (ICS) Proforma 13

Annex B (informative) Examples of message sequences 20