

# ISO/IEC 8802-2:1998-06 (E)

## Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 2: Logical link control

---

<b>Contents</b>	<b>Page</b>
1. Overview.....	1
1.1 Scope and purpose .....	1
1.2 Standards compatibility.....	3
1.3 Normative references.....	3
1.4 Acronyms and definitions .....	5
1.5 Conformance .....	11
2. LLC sublayer Service specifications.....	12
2.1 General .....	12
2.2 Network layer/LLC sublayer interface Service specification .....	14
2.3 LLC sublayer/MAC sublayer interface Service specification .....	35
2.4 LLC sublayer/LLC sublayer management function interface service specification .....	38
3. LLC PDU structure .....	39
3.1 General .....	39
3.2 LLC PDU format.....	39
3.3 Elements of the LLC PDU .....	39
4. LLC types and classes of procedures.....	42
4.1 General .....	42
4.2 Classes of LLC (conformance clause) .....	43
4.3 Support of route determination entity (RDE) (conformance clause) .....	45
5. LLC Elements of procedure .....	46
5.1 General .....	46
5.2 Control field formats .....	46
5.3 Control field parameters.....	47
5.4 Commands and responses .....	50
6. LLC description of the Type 1 procedures .....	62
6.1 Mode of Operation.....	62
6.2 Procedure for addressing.....	62
6.3 Procedure for the use of the P/F bit .....	62
6.4 Procedures for logical data link setup and disconnection .....	62
6.5 Procedures for information transfer.....	62
6.6 Uses of the XID command PDU and response PDU .....	63
6.7 Uses of the TEST command PDU and response PDU .....	63
6.8 List of logical data link parameters .....	64
6.9 Precise description of the Type 1 procedures .....	64
7. LLC description of the Type 2 procedures .....	73
7.1 Modes .....	73
7.2 Procedure for addressing.....	74
7.3 Procedures for the use of the P/F bit .....	74
7.4 Procedures for data link setup and disconnection.....	74
7.5 Procedures for information transfer.....	76
7.6 Procedures for resetting.....	80
7.7 FRMR exception conditions .....	81
7.8 List of data link connection parameters .....	82
7.9 Precise description the Type 2 procedures.....	83

8.	LLC description of the Type 3 procedures .....	115
8.1	Modes of operation.....	115
8.2	Procedure for addressing .....	115
8.3	Procedure for the use of the P/F bit1 .....	115
8.4	Procedures for link setup and disconnection .....	115
8.5	Procedures for information transfer .....	116
8.6	List of logical link parameters.....	119
8.7	Precise description of Type 3 procedures .....	121
9.	LLC RDE procedures.....	130
9.1	Overview of RDE.....	130
9.2	Support of the LLC service.....	130
9.3	Principles of operation.....	135
9.4	Encoding of RDE PDUs .....	139
9.5	Encoding of the routing Information field (RIF).....	140
9.6	RDE route control process .....	140
9.7	The route determination component (RDC).....	147
10.	LLC sublayer managed objects .....	154
10.1	LLCStation managed object .....	155
10.2	ILCSAP managed object .....	162
10.3	LLCConnectionless managed object .....	163
10.4	LLCConnection2 managed object.....	167
10.5	LLCConnection2IVMO managed object .....	180
10.6	LLCConnectionlessAck managed object.....	181
10.7	LLCConnectionlessAckIVMO managed object.....	188
10.8	RDE Setup managed object .....	189
10.9	1 RDE pair managed object .....	191
10.10	Resource Type ID managed object.....	193
10.11	Conformance .....	194
10.12	ASN.I LLCDefinitions.....	194

## ANNEX

Annex A (normative) Protocol Implementation Conformance Statement (PICS) proforma.....	199
Annex B (informative) Relationship between LLC Type 3 and PROWAY (IEC 60955 : 1989) .....	223
Annex C (informative) LLC flow control techniques for bridged LANs .....	228
Annex D (informative) Subnetwork access protocol.....	230
Annex E (normative) Allocation of object identifier values.....	231