

ISO/IEC 22533 :2005-07 (E)

Information technology_ - Data interchange on 90_mm optical disk cartridges_ - Capacity: 2,3_Gbytes per cartridge

Contents

Page

- Foreword..... vii
- Section 1 - General 1
 - 1 Scope 1
 - 2 Conformance..... 1
 - 2.1 Optical disk Cartridge (ODC) 1
 - 2.2 Generating system..... 1
 - 2.3 Receiving system..... 2
 - 2.4 Compatibility statement 2
 - 3 Normative references 2
 - 4 Terms and definitions..... 2
 - 5 Conventions and notations 5
 - 5.1 Representation of numbers 5
 - 5.2 Names 5
 - 6 Abbreviations and acronyms 5
 - 7 General description of the optical disk cartridge..... 6
 - 8 General requirements..... 6
 - 8.1 Environments 6
 - 8.2 Temperature shock..... 8
 - 8.3 Safety requirements 8
 - 8.4 Flammability 8
 - 9 Reference Drive..... 8
 - 9.1 Optical system 8
 - 9.2 Optical beam 9
 - 9.3 Read channels..... 10
 - 9.4 Tracking 10
 - 9.5 Rotation of the disk 10
- Section 2 - Mechanical and physical characteristics 11
 - 10 Dimensional and physical characteristics of the case 11
 - 10.1 General description of the case (see Figure 2)..... 11
 - 10.2 Reference planes of the case 11
 - 10.3 Dimensions of the case..... 11
 - 10.4 Mechanical characteristics 18
 - 11 Dimensional, mechanical and physical characteristics of the disk 31
 - 11.1 General description of the disk 31
 - 11.2 Reference axis and plane of the disk..... 31
 - 11.3 Dimensions of the disk (see Figure 13)..... 31
 - 11.4 Mechanical characteristics 32
 - 11.5 Optical Characteristics..... 34
 - 12 Interface between cartridge and drive 36
 - 12.1 Clamping method..... 36
 - 12.2 Clamping force..... 36
 - 12.3 Capture cylinder (see Figure 14) 36
 - 12.4 Disk position in operating condition (see Figure 14)..... 36

Section 3 - Format of information.....	38
13 Geometry of physical tracks	38
13.1 Physical track shape.....	38
13.2 Direction of track spiral	39
13.3 Physical track pitch	39
14 Track format.....	39
14.1 Logical Track number	39
14.2 Logical Track layout	39
14.3 Clock frequencies and periods.....	40
14.4 Radial alignment	40
14.5 Sector number	41
15 Sector format	41
15.1 Sector layout.....	41
15.2 Sector Mark (SM).....	42
15.3 VFO fields.....	42
15.4 Address Mark (AM)	43
15.5 ID fields	43
15.6 Postambles (PA).....	44
15.7 Gap	45
15.8 Sync	45
15.9 Data field	45
15.10 VCO lock pattern field (VLP)	46
15.11 Buffer field	46
16 Recording code	46
17 Format of the Information Zone.....	47
17.1 General description of the Information Zone	47
17.2 Division of the Information Zone	47
18 Format of the Data Zone	51
18.1 Buffer tracks and Test tracks in the Data Zone	51
18.2 Defect Management Areas (DMAs)	51
18.3 Disk Definition Structure (DDS)	55
18.4 Partitioning	55
18.5 Logical block address	55
19 Defect management	57
19.1 Initialization of the disk	57
19.2 Certification	57
19.3 Disks not certified	58
19.4 Write procedure.....	58
19.5 Primary Defect List (PDL).....	58
19.6 Secondary Defect List (SDL).....	59
Section 4 - Characteristics of embossed information.....	60
20 Method of testing	60
20.1 Environment	60
20.2 Use of the Reference Drive	60
20.3 Definition of signals	61
21 Signals from grooves	62
21.1 Divided push-pull signal.....	62
21.2 Phase depth	63
21.3 Track location	63
22 Signals from Headers	63
22.1 Sector Mark.....	64
22.2 VFO1 and VFO2	64
22.3 Address Mark, ID field and Postamble.....	64
22.4 Timing jitter.....	64

22.5	Asymmetry	65
23	Signals from embossed Recording fields	65
23.1	Signal amplitude	65
23.2	Timing jitter	65
Section 5 - Characteristics of the recording layer and user data		66
24	Method of testing	66
24.1	Environment	66
24.2	Reference Drive	66
24.3	Write conditions	67
24.4	Erase conditions	69
24.5	Definition of signals	70
25	Magneto-optical characteristics	70
25.1	Figure of merit	70
25.2	Imbalance of the magneto-optical signal	70
26	Write characteristics	71
26.1	Resolution	71
26.2	Narrow-band signal-to-noise ratio (NBSNR)	72
26.3	Cross-talk ratio	73
26.4	Timing jitter	73
26.5	Media thermal interaction	73
27	Erase power determination	74
Section 6 - Characteristics of user data		75
28	Method of testing	75
28.1	Environment	75
28.2	Reference Drive	75
29	Minimum quality of a sector	76
29.1	Headers	76
29.2	User-written data	77
30	Data interchange requirements	77
30.1	Tracking	77
30.2	User-written data	77
30.3	Quality of disk	77
Annex A (normative) Edge distortion test		78
Annex B (normative) Compliance test		79
Annex C (normative) CRC for ID fields		81
Annex D (normative) Interleave, CRC, ECC, Resync for the data field		82
Annex E (normative) Contents of the Control Zone		87
Annex F (normative) Determination of the Resync patterns		94
Annex G (normative) Measurement of the figure of merit		99
Annex H (normative) Read Channel for measuring NBSNR and jitter		100
Annex I (normative) Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media		103
Annex J (normative) Air cleanliness class 100 000		104
Annex K (normative) Position of the cartridge relative to the reference planes		105
Annex L (normative) Relaxation by zones of the requirements for signals		106
Annex M (normative) Test method for measuring the adsorbent force of the hub		107
Annex N (informative) Track deviation measurement		109

Annex O (informative) Derivation of the operating climatic environment 113
Annex P (informative) Transportation 118
Annex Q (informative) Office environment 119
Annex R (informative) Values to be implemented in existing and future standards 120
Annex S (informative) Measurement of the vertical birefringence of the substrate 121
Annex T (informative) Sector retirement guidelines 123
Annex U (informative) Laser power calibration for evaluation of media power sensitivity 124