

ISO/IEC 23915:2005-11 (E)

Information technology - Telecommunications and information exchange between systems - Corporate Telecommunication Networks - Signalling Interworking between QSIG and SIP - Call Diversion

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	External definitions	2
3.2	Other definitions	3
3.2.1	Call diversion	3
3.2.2	Call forwarding busy (CFB)	3
3.2.3	Call forwarding no reply (CFNR)	3
3.2.4	Call forwarding unconditional (CFU)	3
3.2.5	Corporate telecommunication Network (CN)	3
3.2.6	Entity A	3
3.2.7	Entity B	3
3.2.8	Entity C	3
3.2.9	Gateway	3
3.2.10	IP network	3
3.2.11	Leg A	3
3.2.12	Leg B	3
3.2.13	Leg C	4
3.2.14	Private Integrated Services Network (PISN)	4
3.2.15	Private Integrated services Network eXchange (PINX)	4
3.2.16	Rerouting entity	4
3.2.17	User A	4
3.2.18	User B	4
3.2.19	User C	4
4	Abbreviations and acronyms	4
5	Background and architecture for SIP-QSIG interworking	5
6	Call diversion	5
7	Call diversion in QSIG	6
8	Call diversion in SIP	7
9	Diversion interworking	7
9.1	Scenarios for diversion interworking	7
9.2	Mapping of numbers, names and URIs	8
9.3	Derivation of QSIG diversion reasons	8
9.3.1	Scenario A1	9
9.3.2	Scenario B1	9
9.3.3	Scenario C2	9
9.4	Derivation of SIP response codes (scenarios A2 and C1)	9

9.5	Mapping the QSIG diversion counter	10
9.6	Privacy considerations	10
9.7	Interworking for scenario A1	10
9.7.1	Transmitting a SIP INVITE request	10
9.7.2	Receipt of a SIP 1xx or 2xx response	11
9.7.3	Receipt of a SIP 4xx, 5xx or 6xx response	11
9.8	Interworking for scenario A2	11
9.8.1	Receipt of a SIP INVITE request	12
9.8.2	Receipt of a QSIG divertingLegInformation1 invoke APDU	12
9.8.3	Receipt of a QSIG divertingLegInformation3 invoke APDU	12
9.8.4	Transmitting a SIP response in which History-Info is allowed	12
9.9	Interworking for scenario B1	13
9.9.1	Receipt of a SIP 3xx response	13
9.9.2	Receipt of a QSIG DISCONNECT or FACILITY message containing a callRerouteing return result APDU	14
9.9.3	Receipt of a QSIG FACILITY message containing a callRerouteing return error APDU	14
9.9.4	Receipt of a QSIG FACILITY message containing a cfnrDivertedLegFailed invoke APDU	14
9.10	Interworking for scenario B2	15
9.10.1	Receipt of a QSIG FACILITY message containing a CallRerouteing invoke APDU	15
9.11	Interworking for scenario C1	15
9.11.1	Receipt of a QSIG SETUP message containing a divertingLegInformation2 invoke APDU	15
9.11.2	Transmitting a QSIG CONNECT message	16
9.12	Interworking for scenario C2	16
9.12.1	Transmitting a QSIG SETUP message	16
9.12.2	Receipt of a QSIG message containing a divertingLegInformation3 invoke APDU	17
9.12.3	Sending History-Info in a response	17
10	Example message sequences	17
10.1	Scenario A1	18
10.1.1	Successful call - history information in 200 response	18
10.1.2	Successful call - history information in provisional response	19
10.1.3	Failed call	20
10.2	Scenario A2	21
10.2.1	Successful call - CFU or CFB	21
10.2.2	Successful call - CFNR	22
10.3	Scenario B1	23
10.3.1	Successful diversion - CFU or CFB	23
10.3.2	Successful diversion - CFNR	24
10.3.3	Failure - callRerouting.err received	25
10.3.4	Failure - No answer following CFNR	26
10.4	Scenario B2	27
10.5	Scenario C1	28
10.6	Scenario C2	29
10.7	Scenario A1 followed by B1	30
10.8	Scenario A2 followed by scenario B2	31
10.9	Scenario C1 followed by scenario A1	32
10.10	Scenario C2 followed by scenario A2	33
10.11	Scenario C1 followed by scenario B1	34
10.12	Scenario C2 followed by scenario B2	35
11	Security considerations	35