ISO/IEC 23917:2005-11 (E)

Information technology - Telecommunications and information exchange between systems - NFCIP-1 - Protocol Test Methods

Contents

Page

1 Scope 1

2 Conformance 1

3 Normative references 1

4 Notational conventions 1
4.1 Representation of numbers 1
4.2 Names 1
4.3 Test report 2

5 Terms and definitions 2
5.1 Activation in Active communication Mode 2
5.2 Activation in Passive communication Mode 2
5.3 Active communication Mode 2
5.4 Operating volume 2
5.5 Passive communication Mode 2
5.6 Single Device Detection (SDD) 2
5.7 Scenario 2
5.8 Test commands 2

6 Acronyms and abbreviations 3

7 General description 5
7.1 Apparatus for Testing 5
7.1.1 Generating the I/O character timing in reception mode 5
7.1.2 Measuring and monitoring the RF I/O protocol 5
7.1.3 Test scenario and report 5
7.1.4 RFU bits 5
7.1.5 General rules 5

8 Target test methods 5
8.1 Apparatus for testing the Target (Target-test-apparatus) 5
8.3 Activation in Passive communication Mode at 212 and 424 kbps 7
8.3.1 Activation time 7
8.3.2 Frame format 8
8.3.3 SDD at 212 and 424 kbps 8
8.4 Activation in Active communication Mode 9
8.4.1 RF Collision Avoidance 9
8.5 Logical operation of the Target Transport Protocol 10
8.5.1 Handling of ATR_REQ 10
8.5.2 Handling of PSL_REQ 11
8.5.3 Handling of DEP_REQ Information PDUs 13
8.5.4 Handling of DEP_REQ Information PDUs with the "more information" bit set to ONE 14
8.5.5 Handling of DEP_REQ supervisory PDU's with timeout bit set to ONE 19
8.5.6 Handling of DEP_REQ supervisory PDUs with timeout bit set to ZERO 20
8.5.7 Handling of DSL_REQ 21
8.5.8 Handling of RLS_REQ 22
8.5.9 Handling of WUP_REQ (Active communication Mode Only) 24

9 Initiator test methods 26

9.1 Apparatus for testing the Initiator (Initiator-test-apparatus) 26
9.1.1 Initiator test apparatus concept 26

Foreword v

Introduction vi
9.1.4 Protocol activation procedures for Active communication Mode 27
9.2 List of protocol test methods for Initiators 27
9.3 Activation in Passive communication Mode at 212 and 424 kbps 28
9.3.1 Frame format 28
9.3.2 SDD at 212 and 424 kbps 28
9.4 Activation in Active communication Mode 29
9.4.1 Initial RF Collision Avoidance 29
9.4.2 Response RF Collision Avoidance with time jitter n=0 29
9.5 Logical operation of the Transport Protocol 30
9.5.1 Handling of ATR_RES 30
9.5.2 Handling of PSL_RES 31
9.5.3 Handling of DEP_RES Information PDUs 32
9.5.4 Handling of DEP_RES Information PDU's with more information bit set to ONE 34
9.5.5 Handling of DEP_RES supervisory PDU's with timeout bit set to ONE 37
9.5.6 Handling of DEP_RES supervisory PDUs with timeout bit set to ZERO 39
9.5.7 Handling of DSL_RES 40
9.5.8 Handling of RLS_RES 41

Annex A (normative) Test report template for Target tests 43

Annex B (normative) Test report template for Initiator tests 48
9.1.2 Protocol activation procedure for Passive communication Mode at 106 kbps 26
9.1.3 Protocol activation procedures for Passive communication Mode at 212 and 424 kbps 27