

ISO/IEC 23917:2005-11 (E)

Information technology - Telecommunications and information exchange between systems - NFCIP-1 - Protocol Test Methods

Contents		Page
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Notational conventions	1
4.1	Representation of numbers	1
4.2	Names	1
4.3	Test report	2
5	Terms and definitions	2
5.1	Activation in Active communication Mode	2
5.2	Activation in Passive communication Mode	2
5.3	Active communication Mode	2
5.4	Operating volume	2
5.5	Passive communication Mode	2
5.6	Single Device Detection (SDD)	2
5.7	Scenario	2
5.8	Test commands	2
6	Acronyms and abbreviations	3
7	General description	5
7.1	Apparatus for Testing	5
7.1.1	Generating the I/O character timing in reception mode	5
7.1.2	Measuring and monitoring the RF I/O protocol	5
7.1.3	Test scenario and report	5
7.1.4	RFU bits	5
7.1.5	General rules	5
8	Target test methods	5
8.1	Apparatus for testing the Target (Target-test-apparatus)	5
8.3	Activation in Passive communication Mode at 212 and 424 kbps	7
8.3.1	Activation time	7
8.3.2	Frame format	8
8.3.3	SDD at 212 and 424 kbps	8
8.4	Activation in Active communication Mode	9
8.4.1	RF Collision Avoidance	9
8.5	Logical operation of the Target Transport Protocol	10
8.5.1	Handling of ATR_REQ	10
8.5.2	Handling of PSL_REQ	11
8.5.3	Handling of DEP_REQ Information PDUs	13
8.5.4	Handling of DEP_REQ Information PDUs with the "more information" bit set to ONE	14
8.5.5	Handling of DEP_REQ supervisory PDU's with timeout bit set to ONE	19
8.5.6	Handling of DEP_REQ supervisory PDUs with timeout bit set to ZERO	20
8.5.7	Handling of DSL_REQ	21
8.5.8	Handling of RLS_REQ	22
8.5.9	Handling of WUP_REQ (Active communication Mode Only)	24
9	Initiator test methods	26

9.1	Apparatus for testing the Initiator (Initiator-test-apparatus)	26
9.1.1	Initiator test apparatus concept	26
Foreword		v
Introduction		vi
9.1.4	Protocol activation procedures for Active communication Mode	27
9.2	List of protocol test methods for Initiators	27
9.3	Activation in Passive communication Mode at 212 and 424 kbps	28
9.3.1	Frame format	28
9.3.2	SDD at 212 and 424 kbps	28
9.4	Activation in Active communication Mode	29
9.4.1	Initial RF Collision Avoidance	29
9.4.2	Response RF Collision Avoidance with time jitter n=0	29
9.5	Logical operation of the Transport Protocol	30
9.5.1	Handling of ATR_RES	30
9.5.2	Handling of PSL_RES	31
9.5.3	Handling of DEP_RES Information PDUs	32
9.5.4	Handling of DEP_RES Information PDU's with more information bit set to ONE	34
9.5.5	Handling of DEP_RES supervisory PDU's with timeout bit set to ONE	37
9.5.6	Handling of DEP_RES supervisory PDUs with timeout bit set to ZERO	39
9.5.7	Handling of DSL_RES	40
9.5.8	Handling of RLS_RES	41
Annex A (normative) Test report template for Target tests		43
Annex B (normative) Test report template for Initiator tests		48
9.1.2	Protocol activation procedure for Passive communication Mode at 106 kbps	26
9.1.3	Protocol activation procedures for Passive communication Mode at 212 and 424 kbps	27