

# ISO/IEC 18050:2006-02 (E)

## Information technology - Office equipment - Print quality attributes for machine readable Digital Postage Marks

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| Foreword .....  |  | v           |
| Introduction .....  |  | vi          |
| 1   | Scope .....  | 1           |
| 2   | Normative references .....   | 1           |
| 3   | Terms and definitions .....  | 2           |
| 4   | Symbols and abbreviations .....                                    | 3           |
| 5   | Requirements .....   | 3           |
| 6   | Basic measurement methodology .....                                | 4           |
| 7   | Verification requirements for Digital Postage Marks .....          | 5           |
| 7.1   | Verification equipment .....                                       | 5           |
| 7.2   | Optical geometry .....   | 5           |
| 7.3   | Light source .....   | 6           |
| 7.4   | Measuring aperture .....   | 6           |
| 7.4.1   | Measuring aperture for two-dimensional multi-row symbologies ..... | 7           |
| 7.4.2   | Measuring aperture for two-dimensional matrix symbologies .....    | 7           |
| 7.5   | Mail format .....  | 7           |
| 8   | Grading implications for individual symbol attributes .....        | 8           |
| 9   | Additional grading parameters - quiet zone .....                   | 9           |
| 10  | Qualification of printing systems for Digital Postage Marks .....  | 9           |
| Annex A (normative) Test procedure for printing systems for Digital Postage Marks .....                                   |  | 11          |
| A.1   | Environmental conditions for test .....                            | 11          |
| A.2   | Test materials .....   | 11          |
| A.3   | Test procedure .....   | 12          |
| Annex B (informative) Light sources and spectral response characteristics for verification of Digital Postage Marks ..... |  | 13          |
| B.1   | Narrow-band illumination .....                                     | 13          |
| B.2   | Broad-band illumination (white light) .....                        | 13          |
| B.2.1   | Halogen lamps .....  | 14          |
| B.2.2   | Light emitting diode .....   | 14          |
| B.2.3   | Gas discharge lamp .....   | 14          |
| B.2.4   | Fluorescent lamps .....  | 15          |
| C.1   | Parameters for two-dimensional multi-row symbols .....             | 16          |
| C.2   | Parameters for two-dimensional matrix symbologies .....            | 17          |

|  |           |
|--|-----------|
| <b>Annex D (informative) Characteristics of Digital Postage Mark printing and reading environments that affect print quality .....</b> | <b>18</b> |
| <b>D.1 Printing of Digital Postage Marks .....</b>   | <b>18</b> |
| D.1.1 Ink-jet printing .....   | 18        |
| D.1.2 Laser printing .....   | 18        |
| D.1.3 Thermal transfer printing .....  | 19        |
| D.1.4 Direct thermal printing .....  | 19        |
| D.1.5 Matching X dimension to printer resolution .....   | 19        |
| D.2 Reading environment .....  | 20        |
| <b>Annex E (informative) Possible causes of low parameter grades in the Digital Postage Mark environment .....</b>                     | <b>21</b> |
| <b>E.1 Multi-row symbologies .....</b>   | <b>21</b> |
| E.1.1 Symbol Contrast .....  | 21        |
| E.1.2 Minimum reflectance .....  | 21        |
| E.1.3 Minimum edge contrast .....  | 21        |
| E.1.4 Modulation .....   | 21        |
| E.1.5 Decode .....   | 22        |
| E.1.6 Defects .....  | 22        |
| E.1.7 Decodability .....   | 22        |
| E.1.8 Codeword yield .....   | 22        |
| E.1.9 Unused error correction (UEC) .....  | 22        |
| E.1.10 Quiet zone .....  | 22        |
| E.1.11 Print growth .....  | 22        |
| E.1.12 Codeword quality .....  | 23        |
| <b>E.2 Matrix symbologies .....</b>  | <b>23</b> |
| E.2.1 Symbol Contrast .....  | 23        |
| E.2.2 Fixed pattern damage .....   | 23        |
| E.2.3 Modulation .....   | 23        |
| E.2.4 Axial non-uniformity .....   | 23        |
| E.2.5 Grid non-uniformity .....  | 24        |
| E.2.6 Unused error correction .....  | 24        |
| E.2.7 Quiet zone .....   | 24        |
| E.2.8 Print growth .....   | 24        |
| <b>Bibliography .....</b>  | <b>25</b> |