

ISO/IEC 19794-3:2006-08 (E)

Information technology - Biometric data interchange formats - Part 3: Finger pattern spectral data

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Conformance | 1 |
| 3 | Normative references | 1 |
| 4 | Terms and definitions | 1 |
| 5 | Symbols and abbreviated terms | 4 |
| 6 | Data conventions | 5 |
| 6.1 | Byte and bit ordering | 5 |
| 6.2 | Coordinate system | 5 |
| 6.3 | Greyscale precision | 6 |
| 6.4 | Image polarity | 6 |
| 6.5 | Angle direction of rotation | 6 |
| 6.6 | Phase and propagation angles | 6 |
| 7 | Determination of finger pattern spectral data | 6 |
| 7.1 | Overview | 6 |
| 7.2 | Step 0) [Optional] Image pre-processing | 6 |
| 7.3 | Step 1) Cellular partitioning | 6 |
| 7.4 | Step 2) Spectral component selection | 7 |
| 7.4.1 | Quantized co-sinusoidal triplets | 7 |
| 7.4.2 | Discrete Fourier Transform | 10 |
| 7.4.3 | Gabor filters | 12 |
| 7.5 | Quality | 13 |
| 8 | Finger pattern spectral data record | 14 |
| 8.1 | Record header | 14 |
| 8.1.1 | Format identifier | 14 |
| 8.1.2 | Version number | 15 |
| 8.1.3 | Length of record | 15 |
| 8.1.4 | Number of single finger records | 15 |
| 8.1.5 | x (horizontal) resolution | 15 |
| 8.1.6 | y (vertical) resolution | 15 |
| 8.1.7 | Number of cells in x-direction | 15 |
| 8.1.8 | Number of cells in y-direction | 15 |
| 8.1.9 | Number of pixels in cells in x-direction | 15 |
| 8.1.10 | Number of pixels in cells in y-direction | 15 |
| 8.1.11 | Number of pixels between cell centres in x-direction | 15 |
| 8.1.12 | Number of pixels between cell centres in y-direction | 16 |
| 8.1.13 | Spectral component selection method | 16 |
| 8.1.14 | Type of window | 16 |
| 8.1.15 | Standard deviation | 16 |
| 8.1.16 | Number of frequencies | 17 |
| 8.1.17 | Frequencies | 17 |

| | | |
|-----------------------|--|----|
| 8.1.18 | Number of orientations | 17 |
| 8.1.19 | Number of spectral components to be retained per cell | 17 |
| 8.1.20 | Bit-depth of propagation angle of co-sinusoidal function | 18 |
| 8.1.21 | Bit-depth of wavelength of co-sinusoidal function | 18 |
| 8.1.22 | Bit-depth of phase | 18 |
| 8.1.23 | Bit-depth of magnitude | 18 |
| 8.1.24 | Bit-depth of quality score | 18 |
| 8.1.25 | Cell quality group granularity | 19 |
| 8.1.26 | Reserved bytes | 19 |
| 8.2 | Single finger record | 19 |
| 8.2.1 | Header | 19 |
| 8.2.2 | Finger pattern spectral data block | 20 |
| 8.2.3 | Extended data block | 23 |
| 8.3 | Summary of finger pattern spectral data record | 28 |
| 9 | Finger pattern spectral data card format | 31 |
| | | |
| Annex A (informative) | Finger pattern spectral data record examples - quantized co-sinusoidal triplet spectral component selection method | 33 |
| A.1 | Example 1 | 33 |
| A.2 | Example 2 | 34 |
| A.3 | Size comparisons | 36 |
| | | |
| Annex B (informative) | Finger pattern spectral data record examples - Discrete Fourier Transform spectral component selection method | 37 |
| B.1 | Example 1 | 37 |
| B.2 | Example 2 | 38 |
| | | |
| Annex C (informative) | Finger pattern spectral data record example - Gabor filter spectral component selection method | 40 |
| | | |
| Bibliography | | 42 |