

ISO/IEC 17345:2006-12 (E)

Information technology - Data Interchange on 130 mm Rewritable and Write Once Read Many Ultra Density Optical (UDO) Disk Cartridges - Capacity: 30 Gbytes per Cartridge - First Generation

Contents		Page
Foreword		vii
Introduction		viii
Section 1 -- General		1
1 Scope		1
2 Conformance		2
2.1 Optical disk		2
2.2 Generating system		2
2.3 Receiving system		2
2.4 Compatibility statement		2
3 Normative references		2
4 Terms and definitions		2
5 Conventions and notations		6
5.1 Representation of numbers		6
5.2 Names		6
6 Acronyms		6
7 General description		7
8 General requirement		8
8.1 Environments		8
8.2 Temperature shock		9
8.3 Safety requirements		9
8.4 Flammability		9
9 Reference Drive		9
9.1 Optical system		9
9.2 Optical beam		10
9.3 Read Channel		11
9.4 Tracking		11
9.5 Rotation of the disk		11
Section 2 -- Mechanical and physical characteristics		11
10 Dimensional and physical characteristics of the case		11
10.1 General description of the case		11
10.2 Relationship of Sides A and B		11
10.3 Reference axes and case reference planes		12
10.4 Case drawings		12
10.5 Dimensions of the case		12
10.6 Mechanical characteristics		19
10.7 Drop test		20

10.8	Electro-static discharge test	20
11	Dimensional, mechanical, and physical characteristics of the disk	31
11.1	General description of the disk	31
11.2	Reference axis and plane of the disk	32
11.3	Dimensions of the disk	32
11.4	Mechanical characteristics	34
11.5	Optical characteristics	36
12	Interface between cartridge and drive	37
12.1	Clamping method	37
12.2	Clamping force	37
12.3	Capture cylinder	38
12.4	Disk position in operating condition	38
Section 3 -- Format of information		40
13	Track and Header geometry	40
13.1	Track and Header shape	40
13.2	Wobble groove	41
13.3	Mirror Area	41
13.4	Direction of spiral	41
13.5	Track pitch	41
13.6	Physical Track number	42
14	Track format	43
14.1	Physical Track layout	43
14.2	Physical Block Address (PBA)	43
14.3	Sectors with Mirror Area	46
14.4	Radial alignment	47
15	Sector format	47
15.1	Sector layout	47
15.2	IDL, IDG	49
15.3	Blank fields	50
15.4	Quadrature Wobble Marks (QWM)	50
15.5	Gap	51
15.6	Guard	51
15.7	Verify and Protect (VAP)	52
15.8	VFO1, VFO2	52
15.9	Sync	53
15.10	Data field	53
15.11	Postamble (PA)	54
15.12	Buffer	54
15.13	Transition Area (TA)	55
16	Recording codes	55
16.1	Preformatted Header	55
16.2	Data field	55
17	Formatted Zone	57
17.1	General description of the Formatted Zone	57
17.2	Division of the Formatted Zone	57
17.3	Drive test data patterns	64
17.4	SDI Zones usage	64
17.5	DDS Zones Usage	66
18	Layout of the User Zones	67
18.1	General description of the User Zones	67
18.2	Divisions of the User Zones	67
18.3	User Area	67
18.4	Defect Management Area (DMA)	69

18.5	Disk Definition Structure (DDS)	71
19	Defect Management in the Rewritable (RW) and Write Once Read Many (WORM) Zones ...	73
19.1	Initialization of the disk	73
19.2	Certification	73
19.3	Disk not certified	74
19.4	Write procedure	75
19.5	Primary Defect List (PDL) format and content	75
19.6	Secondary Defect List (SDL) format and content	76
Section 4 -- Characteristics of embossed information		77
20	Embossed information - Method of testing	77
20.1	Environment	77
20.2	Use of the Reference Drive	77
20.3	Definition of signals	78
21	Signals from grooves and lands	79
21.1	Ratio of groove to land signal	79
21.2	Ratio of groove/land to Mirror Area signal	79
21.3	Divided push-pull signal	80
21.4	Wobble signal	80
21.5	Phase depth	81
21.6	Track location	81
22	Signals from Headers	81
22.1	Reference reflectance ltop	81
22.2	Address Mark and ID signals	81
22.3	QWM signals	82
22.4	Timing mean and jitter	83
Section 5 -- Characteristics of the recording layer		83
23	Method of testing	83
23.1	Environment	83
23.2	Reference Drive	83
23.3	Write conditions	84
23.4	Erase power for Type RW media	86
23.5	Read power damage	86
24	Phase Change characteristics	86
24.1	Mark polarity	86
24.2	Rewrite cycles for Type RW media	86
25	Write characteristics	86
25.1	Resolution	86
25.2	Narrow-Band Signal-to-Noise Ratio (NBSNR)	87
25.3	Cross-talk ratio	88
25.4	Timing mean	88
25.5	Timing jitter	89
25.6	Asymmetry	89
26	Erase power determination for Type RW media	89
26.1	Cross-Erase for Type RW Media	90
Section 6 -- Characteristics of user data		91
27	User Data - Method of testing	91
27.1	Environment	91
27.2	Reference Drive	91
28	Minimum quality of a sector	92

28.1	Headers ID	92
28.2	User-written data	93
28.3	Wobble signal	93
29	Data interchange requirements	93
29.1	Tracking	93
29.2	User-written data	93
29.3	Quality of disk	93
Annex A (normative) Air cleanliness class 100 000		94
Annex B (normative) Edge distortion test		96
Annex C (normative) Compliance test		98
Annex D (normative) Cartridge electro-static discharge test		101
Annex E (normative) Test method for measuring the adsorbent force of the hub		102
Annex F (normative) CRC for ID fields		104
Annex G (normative) Data field scrambler implementation		105
Annex H (normative) Interleave, CRC, ECC, Resync, and Reference for the Data field		107
Annex I (normative) Drive Information Record (DIR) usage		112
Annex J (normative) Determination of the Resync and Reference patterns		114
Annex K (normative) Specific Disk Information		116
Annex L (normative) Read Channel for measuring analog signals and jitter		132
Annex M (normative) Timing mean and timing jitter measuring procedure		133
Annex N (normative) Implementation Independent Mark Quality Determination (IIMQD) for the interchange of recorded media		134
Annex O (normative) Definition of the write pulse shape		136
Annex P (normative) Asymmetry measuring definition		137
Annex Q (normative) Enhanced Selective Inter-Symbol Interference Cancellation (ESISIC) algorithm		138
Annex R (normative) Requirements for interchange		140
Annex S (informative) Office environment		142
Annex T (informative) Derivation of the operating climatic environment		143
Annex U (informative) Transportation		148
Annex V (informative) Track deviation measurement		149
Annex W (informative) Measurement of the vertical birefringence of the cover layer		153
Annex X (informative) Quadrature Wobble offset control		154
Annex Y (informative) Start Position Shift (SPS) implementation		157
Annex Z (informative) Sector retirement guidelines		158

Annex AA (informative) Guidelines for the use of Type WORM ODCs	159
Annex BB (informative) Media type identification in existing and future standards	160
Annex CC (informative) Laser power calibration for evaluation of media power parameters	161