

ISO/IEC 26907:2007-03 (E)

Information technology - Telecommunications and information exchange between systems - High Rate Ultra Wideband PHY and MAC Standard

Contents		Page
Foreword		x
Introduction		xi
1	Scope	1
2	Conformance	1
3	Normative references	1
4	Terms and definitions	2
5	Notational conventions	4
6	Abbreviations and acronyms	4
7	General description	7
7.1	PHY general description	7
7.2	MAC general description	8
7.2.1	General description of the architecture	8
7.2.2	Device address	8
7.2.3	Features assumed from the PHY	8
7.2.4	Overview of MAC service functionality	9
7.2.5	MUX sublayer	13
7.2.6	MAC policies	13
7.2.7	Test vectors	13
8	PHY layer partitioning	13
8.1	PHY function	14
8.2	PLCP sublayer	14
8.3	PMD sublayer	14
8.4	PHY layer management entity (PLME)	14
9	Description of signal	14
9.1	Mathematical framework	14
10	PLCP sublayer	15
10.1	PPDU	15
10.1.1	PSDU rate-dependent parameters	18
10.1.2	Timing-related parameters	18
10.1.3	Frame-related parameters	19
10.2	PLCP preamble	19
10.2.1	Standard PLCP preamble	20
10.2.2	Burst PLCP preamble	21
10.3	PLCP header	32
10.3.1	PHY header	33
10.3.2	Reed-Solomon outer code for the PLCP header	37
10.3.3	Header check sequence	39
10.4	PSDU	40
10.4.1	Pad bits	41
10.5	Data scrambler	42

10.6	Tail bits	43
10.7	Convolutional encoder	43
10.8	Bit interleaving	46
10.9	Constellation mapping	48
10.9.1	QPSK	48
10.9.2	Dual-carrier modulation (DCM)	49
10.10	OFDM modulation	51
10.10.1	Implementation considerations	55
10.10.2	Data subcarriers	55
10.10.3	Guard subcarriers	59
10.10.4	Pilot subcarriers	59
11	General requirements	61
11.1	Operating band frequencies	61
11.1.1	Operating frequency range	61
11.1.2	Band numbering	61
11.2	Channelization	62
11.3	PHY layer timing	64
11.3.1	Interframe spacing	65
11.3.2	Receive-to-transmit turnaround time	65
11.3.3	Transmit-to-receive turnaround time	65
11.3.4	Time between successive transmissions	65
11.3.5	Band frequency switch time	65
12	Transmitter specifications	66
12.1	Transmit PSD mask	66
12.2	Transmit centre frequency tolerance	66
12.3	Symbol clock frequency tolerance	66
12.4	Clock synchronization	66
12.5	Phase coherence	66
12.6	Transmit power control	66
12.7	Transmitter constellation error	67
13	Receiver specification	68
13.1	Receiver sensitivity	68
13.2	Receiver CCA performance	69
13.3	Link quality indicator	69
14	Ranging and location awareness	70
14.1	Ranging requirements	70
14.2	Ranging reference signal	70
14.3	PHY ranging resources	70
14.4	PHY ranging operation	70
14.5	Ranging calibration constants	70
14.6	Example range measurement (informative)	71
15	PHY and MAC service access points (informative)	72
15.1	Generic MIB management primitives	72
15.1.1	XX-GET.request	73
15.1.2	XX-GET.confirm	73
15.1.3	XX-SET.request	74
15.1.4	XX-SET.confirm	74
15.2	PHY SAP interface	74
15.2.1	Data transfer	75
15.2.2	PHY transmission control	76
15.2.3	PHY reception control	78
15.2.4	PHY CCA control	81
15.3	PLME SAP interface	82
15.3.1	PHY reset	84
15.3.2	PHY ranging timer control	84
15.4	MAC sublayer management primitives	85
15.5	MAC management information base (MIB)	85

15.6	MLME SAP interface	86
15.6.1	Reset	86
15.6.2	Scan	87
15.6.3	Beacon transmission and reception	89
15.6.4	IE management	93
15.6.5	PTK establishment	95
15.6.6	GTK solicitation/distribution	98
15.6.7	Temporal key update	100
15.6.8	Security violation report	102
15.6.9	Pseudo-random function (PRF)	103
15.6.10	Application-specific IE (ASIE) management	104
15.6.11	Multicast address binding	106
15.6.12	Link events	109
15.6.13	Probe	112
15.6.14	Hibernation and sleep cycle	115
15.6.15	Higher layer synchronization support	119
15.6.16	DRP reservation management	121
15.6.17	Connection configuration primitives	127
15.6.18	Range measurement	129
15.6.19	Application-specific command management	130
15.7	MAC SAP interface	132
15.7.1	MAC-DATA.request	133
15.7.2	MAC-DATA.indication	134
15.7.3	MAC-DATA.confirm	134
16	MAC frame formats	135
16.1	Frame format conventions	135
16.1.1	Figures	135
16.1.2	Octet order	135
16.1.3	Encoding	135
16.2	General MAC frame format	135
16.2.1	Frame control	136
16.2.2	DestAddr	138
16.2.3	SrcAddr	138
16.2.4	Sequence control	138
16.2.5	Access information	138
16.2.6	Frame payload	139
16.2.7	FCS	139
16.3	Beacon frames	140
16.4	Control frames	142
16.4.1	Immediate acknowledgement (Imm-ACK)	143
16.4.2	Block acknowledgement (B-ACK)	143
16.4.3	Request to send (RTS)	144
16.4.4	Clear to send (CTS)	144
16.4.5	Unused DRP reservation announcement (UDA)	144
16.4.6	Unused DRP reservation response (UDR)	144
16.4.7	Application-specific	144
16.5	Command frames	144
16.5.1	DRP reservation request	145
16.5.2	DRP reservation response	146
16.5.3	Probe	146
16.5.4	Pairwise temporal key (PTK)	146
16.5.5	Group temporal key (GTK)	147
16.5.6	Range measurement	148
16.5.7	Application-specific	150
16.6	Data frames	150
16.7	Aggregated data frames	150
16.8	Information elements	150
16.8.1	Application-specific IE (ASIE)	152
16.8.2	Application-specific probe IE	152
16.8.3	Beacon period occupancy IE (BPOIE)	153
16.8.4	BP switch IE	154

16.8.5	Channel change IE	154
16.8.6	Distributed reservation protocol (DRP) IE	154
16.8.7	DRP availability IE	156
16.8.8	Hibernation anchor IE	156
16.8.9	Hibernation mode IE	157
16.8.10	Identification IE	157
16.8.11	Link feedback IE	159
16.8.12	MAC capabilities IE	160
16.8.13	Master key identifier (MKID) IE	161
16.8.14	Multicast address binding (MAB) IE	161
16.8.15	PCA availability IE	161
16.8.16	PHY capabilities IE	162
16.8.17	Probe IE	163
16.8.18	Relinquish request IE	164
16.8.19	Traffic indication map (TIM) IE	165
17	MAC sublayer functional description	165
17.1	Frame processing	165
17.1.1	Frame addresses	166
17.1.2	Frame reception	166
17.1.3	Frame transaction	166
17.1.4	Frame transfer	167
17.1.5	Frame retry	167
17.1.6	Inter-frame space (IFS)	168
17.1.7	Duplicate detection	168
17.1.8	RTS/CTS use	169
17.1.9	MAC header fields	169
17.1.10	Information elements	172
17.2	Beacon period	174
17.2.1	Beacon slot state	174
17.2.2	BP length	175
17.2.3	Beacon transmission and reception	175
17.2.4	Beacon collision detection	176
17.2.5	BP contraction	176
17.2.6	Merger of multiple BPs	176
17.3	Prioritized contention access (PCA)	179
17.3.1	PCA medium availability	180
17.3.2	NAV	180
17.3.3	Medium status	180
17.3.4	PCA parameters	181
17.3.5	Obtaining a TXOP	181
17.3.6	Using a TXOP	182
17.3.7	Invoking a backoff procedure	183
17.3.8	Decrementing a backoff counter	184
17.4	Distributed reservation protocol (DRP)	185
17.4.1	Reservation type	185
17.4.2	DRP availability IE	186
17.4.3	DRP reservation negotiation	186
17.4.4	DRP reservation announcements	188
17.4.5	Resolution of DRP reservation conflicts	188
17.4.6	BPST realignment and existing DRP reservations	190
17.4.7	Modification and termination of existing DRP reservations	190
17.4.8	Release of hard or private DRP reservation blocks	190
17.4.9	Retransmit procedures in DRP reservations	191
17.5	Synchronization of devices	191
17.5.1	Clock accuracy	192
17.5.2	Synchronization for devices in hibernation mode	192
17.5.3	Guard times	192
17.6	Fragmentation and reassembly	193
17.7	Aggregation	194
17.8	Acknowledgement policies	194
17.8.1	No-ACK	194

17.8.2	Immediate ACK	194
17.8.3	Block ACK	194
17.9	Probe	196
17.10	Dynamic channel selection	196
17.11	Multi-rate support	197
17.12	Transmit power control	197
17.13	Power management mechanisms	197
17.13.1	Power management modes	197
17.13.2	Device power states	197
17.13.3	Power state transitions	198
17.13.4	Hibernation mode operation	199
17.13.5	Hibernation anchor operation	200
17.14	ASIE operation	201
17.15	Range measurement operation	201
17.16	MAC sublayer parameters	204
18	Security	205
18.1	Security mechanisms	206
18.1.1	Security operation	206
18.1.2	4-way handshake	206
18.1.3	Key transport	206
18.1.4	Freshness protection	206
18.1.5	Data encryption	206
18.1.6	Frame integrity protection	207
18.2	Security modes	207
18.2.1	Security mode 0	208
18.2.2	Security mode 1	209
18.2.3	Security mode 2	209
18.3	Temporal keys	209
18.3.1	Mutual authentication and PTK derivation	210
18.3.2	GTK exchange	211
18.3.3	Pseudo-random function (PRF) definition	211
18.3.4	PTK and KCK derivation	212
18.3.5	PTK MIC generation	213
18.3.6	Random number generation	213
18.4	Frame reception steps and replay prevention measures	214
18.4.1	Frame reception	214
18.4.2	Replay prevention	214
18.4.3	Implications on GTKs	214
18.5	AES-128 CCM Inputs	215
18.5.1	Overview	215
18.5.2	Nonce	215
18.5.3	CCM blocks	215
Annex A (normative) MUX sublayer		219
Annex B (normative) MAC Policies		221
Annex C (normative) Assigned number document		226
Annex D (informative) MAC test vectors		230
Annex E (informative) Example encoding of a PHY packet		241
Annex F (informative) Recommended out-of-band emission limits		286
Annex G (informative) Range measurement calculations		287
Bibliography		291