

ISO/TS 28560-4:2023-07 (E)

Information and documentation - RFID in libraries - Part 4: Encoding of data elements based on rules from ISO/IEC 15962 in an RFID tag with partitioned memory

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Applicability and relationship with other systems	4
4.1	General	4
4.2	Independent standards-based components	4
4.3	Integrated encoding/decoding software	6
4.4	Legacy-based architecture	6
5	Requirements	7
5.1	Data elements	7
5.2	RFID air interface: ISO/IEC 18000-63 for UHF	7
5.2.1	General	7
5.2.2	Air interface conformance	8
5.2.3	Tag performance	8
5.2.4	Interrogator performance	8
5.2.5	System performance	8
5.3	RFID air interface: Other air interface protocols	8
5.4	Data protocol	8
5.5	RFID interrogators (RFID readers)	9
6	Data elements	9
6.1	General	9
6.2	Unique item identifier (UII)	11
6.2.1	UII comprising of only the primary item identifier	11
6.2.2	UII comprising owner institution + primary item identifier	12
6.2.3	Encoding set information	12
6.2.4	Unambiguous UII structure	13
6.3	Primary item identifier	13
6.4	Content parameter	13
6.5	Owner institution (ISIL)	14
6.6	Set information	14
6.7	Type of usage	15
6.8	Shelf location	15
6.9	ONIX media format	15
6.10	MARC media format	15
6.11	Supplier identifier	15
6.12	Order number	15
6.13	ILL borrowing institute	15
6.14	ILL transaction number	16
6.15	GS1 product identifier	16
6.16	Alternative unique item identifier	16
6.17	Local data	16
6.18	Title	17

6.19	Product identifier (local)	17
6.20	Media format (other)	17
6.21	Supply chain stage	17
6.22	Supplier invoice number	18
6.23	Alternative item number	18
6.24	Alternative owner institution	18
6.25	Subsidiary of an owner library	18
6.26	Alternative ILL borrowing institution	18
6.27	Other reserved data elements	18
7	Data encoding	19
7.1	Data protocol overview	19
7.1.1	General	19
7.1.2	Data constructs	19
7.1.3	AFI	19
7.1.4	Data format	19
7.1.5	Object identifier for library applications	20
7.1.6	Object identifier for the Ull and its interpretation	20
7.1.7	DSFID	20
7.2	ISO/IEC 15961-1 commands and responses	20
7.3	ISO/IEC 15962 encoding rules for this document	21
7.3.1	General	21
7.3.2	Structure of MB 00	23
7.3.3	Encoding and use of MB 00	23
7.3.4	Structure of MB 01	23
7.3.5	Encoding in MB 01	24
7.3.6	Relative-OID for the Ull	26
7.3.7	Decoding and processing the Monomorphic-Ull	26
7.3.8	Use of GS1 EPC codes in MB 01	26
7.3.9	Structure and use of MB 10	27
7.3.10	Structure of MB 11	27
7.3.11	Encoding in MB 11	28
8	RFID tag requirements	32
8.1	Air interface protocol	32
8.1.1	General	32
8.1.2	Memory parameters	32
8.1.3	Declaring memory parameters	32
8.2	Required air interface commands	33
8.3	Air interface conformance	34
8.4	Performance	34
9	Data integrity, security, and privacy issues	34
9.1	Data integrity	34
9.2	Item security	34
9.2.1	General	34
9.2.2	Use of the Ull	35
9.2.3	Using passwords in MB 00	35
9.2.4	Use of the unique tag ID	37
9.2.5	Use of the AFI	37
9.2.6	Use of the EAS features	38
9.3	Privacy issues	38
10	Implementation and migration	38
11	Miscellaneous	38
	Annex A (informative) Information about ISO 28560 RFID in libraries	39
	Annex B (informative) Relevant ISO/IEC 15961-1 application commands	40

Annex C (informative) Locking procedure for MB 01 with encoding in MB 11	43
Annex D (informative) Monomorphic-UJI and URN Code 40 encoding	44
Annex E (informative) Encoding examples	48
Annex F (informative) Implementation and migration	52
Bibliography	54