

DIN EN 15431:2008-05 (E)

Winter and road service area maintenance equipments - Power system and related controls - Interchangeability and performance requirements

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Power System and related controls	5
3.1	Hydraulic system for municipal vehicles - Specifications	5
3.1.1	Drive of the oil pump	5
3.1.2	Hydraulic Circuits	5
3.1.3	Connection between the hydraulic system of the vehicle and the implements	5
3.1.4	Flow Rates	5
3.1.5	Pressure	5
3.1.6	Power	6
3.1.7	Capacity of the oil tank	6
3.1.8	Maximum oil temperature, cooling capacity test procedure	6
3.1.9	Line cross sections	8
3.1.10	Couplings and functions	9
3.1.11	Hydraulic Fluid	10
3.2	Mechanical Front-Mounted Power Take Off PTO, shaft profile and Performance	10
3.2.1	General	10
3.2.2	Profile A: $n = 540 \text{ min}^{-1}$ $P_{\text{max}} = 60 \text{ kW}$	10
3.2.3	Profile B: $n = 540 \text{ min}^{-1}$ or $n = 1\,000 \text{ min}^{-1}$ $P_{\text{max}} = 150 \text{ kW}$	10
3.2.4	Power take-off shaft profile	11
3.3	Electrical Connectors	13
3.3.1	Connector 24 V, 7 pins, at the front of the vehicle, socket design according to ISO 1185 ..	13
3.3.2	Connector 12 V, 7 pins, at the front of the vehicle, socket design based on ISO 1724	14
3.3.3	Electrical Connectors in the cabine, 24 V, 3 pin	15
3.3.4	Electrical Connectors in the cabin, 12 V, 3 pin	16
Bibliography		18