

DIN EN 13071-1:2019-09 (E)

Stationary waste containers up to 5 000 l, top lifted and bottom emptied - Part 1: General requirements

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	General requirements	8
4.1	Recommendations	8
4.2	Design	9
4.3	Filling apertures	9
4.4	Total height	10
4.5	External surfaces/edges	10
4.6	Lifting connection position	10
4.7	Total permissible mass	10
4.8	Total usable volume	10
4.9	Waste spillage	10
5	Test conditions	10
5.1	General	10
5.2	Temperature requirements	10
5.3	Waste density	10
6	Test methods	11
6.1	General	11
6.2	Test methods on empty containers	11
6.2.1	Stability test (not applicable for flexible containers)	11
6.2.2	Resistance to interior impacts (not applicable for flexible containers)	11
Figure 1 -- Description of the guiding tube and its position 1 according to the slope of the filling aperture		12
Figure 2 -- Slant of positions 2 and 5 in relation to position 1		13
6.2.3	Free fall test	13
6.2.4	Resistance of the roof	14
6.3	Tests methods on loaded containers	14
6.3.1	Resistance to exterior impacts (not applicable for flexible containers)	14
Figure 3 -- Exterior impact test using the incline plan (informative)		15
Figure 4 -- Determination of lateral impact directions according to the shapes of the containers		16
6.3.2	Emptying device/Locking system (not applicable to flexible containers)	16
6.3.3	Mechanical resistance of the lifting components	17
6.4	Measurement of the sound level emitted by falling glass inside the containers	18
6.5	Components treated against corrosion and aging	18
6.6	Weathering and aging (for thermoplastics only)	18
6.6.1	Requirement	18
6.6.2	Procedure	19

6.7	Sequence of tests	19
	Table 1 -- Sequence of the tests (when applicable)	19
7	Data sheet	20
8	Marking	20
9	Test report	20
	Annex A (normative) Weathering test	21
	Bibliography	22