

DIN EN 12574-1:2006-04 (E)

Stationary waste containers - Part 1: Containers with a capacity up to 10 000 l with flat or dome lid(s), for trunnion, double trunnion or pocket lifting device - Dimensions and design

Contents		Page
Foreword		4
Introduction		5
1 Scope		6
2 Normative references		6
3 Terms and definitions		6
4 Volumes		7
5 Dimensions and design		7
6 Nominal load		8
7 Safety and health requirements		8
8 Testing		8
9 Marking		8
10 Designation		9
Annex A (informative) A-Deviations		23
Bibliography		24
Figures Figure 1 -- Dimensions of containers with flat lid(s) for trunnion lifting device without lid opener (type 1) (see Table 1)		11
Figure 2 -- Handle protection (if above trunnion) and clearance at trunnion (see Table 1)		12
Figure 3a -- Dimensions of containers with dome lid(s) for trunnion lifting device with lid opener (type 3 and 4) (see Table 1)		13
Figure 3b -- Dimensions of the lid opening system (type 3 and 4) for containers showed in Figure 3a (see Table 1)		14
Figure 4 -- Containers with dome lid(s) for pocket lifting device with lid opener (type 3) (see Table 2)16 Table 3 -- Dimensions related to Figure 5 (containers with flat lid, up to 10 000 l)		17
Figure 5 -- Containers with flat lid(s) for lifting devices with pocket receiver without lid opener (see Table 3)		18
Figure 6 -- Dimensions of containers with flat lid(s) for pocket lifting device without lid opener (see Table 4)		20

Figure 7 -- Container with flat lid(s) for double trunnion lifting device without lid opener (type 1 and 2) (see Table 5)	22
Tables Table 1 -- Dimensions related to Figures 1, 2 and 3	10
Table 2 -- Dimensions related to Figure 4 (containers with dome lid)	15
Table 4 -- Dimension related to Figure 6	19
Table 5 -- Dimensions related to Figure 7	21