

Table of contents

European Forewod	9
Introduction.....	10
1 Scope.....	12
2 Normative references	13
3 Terms, definitions and abbreviated terms.....	14
3.1 Terms defined in other standards	14
3.2 Terms specific to the present standard	14
3.3 Abbreviated terms.....	17
3.4 Nomenclature	18
4 Overview.....	20
4.1 Plasma interaction effects.....	20
4.1.1 Presentation.....	20
4.1.2 Most common engineering concerns.....	20
4.1.3 Overview of physical mechanisms	21
4.2 Relationship with other standards	23
5 Protection programme	25
6 Surface material requirements	26
6.1 Overview	26
6.1.1 Description and applicability.....	26
6.1.2 Purpose common to all spacecraft	27
6.1.3 A special case: scientific spacecraft with plasma measurement instruments	27
6.2 General requirements	27
6.2.1 Maximum permitted voltage	27
6.2.2 Maximum resistivity.....	28
6.3 Electrical continuity, including surfaces and structural and mechanical parts	28
6.3.1 Grounding of surface metallic parts.....	28
6.3.2 Exceptions	29

6.3.3	Electrical continuity for surface materials	30
6.4	Surface charging analysis.....	34
6.5	Deliberate potentials	34
6.6	Testing of materials and assemblies	34
6.6.1	General	34
6.6.2	Material characterization tests.....	36
6.6.3	Material and assembly qualification.....	36
6.7	Scientific spacecraft with plasma measurement instruments	37
6.8	Verification.....	37
6.8.1	Grounding	37
6.8.2	Material selection	38
6.8.3	Environmental effects.....	38
6.8.4	Computer modelling	38
6.9	Triggering of ESD	39
7	Secondary arc requirements	40
7.1	Description and applicability	40
7.2	Solar arrays	41
7.2.1	Overview	41
7.2.2	General requirement	41
7.2.3	Testing of solar arrays.....	41
7.3	Other exposed parts of the power system including solar array drive mechanisms	46
8	High voltage system requirements	47
8.1	Description	47
8.2	Requirements	47
8.3	Validation.....	47
9	Internal parts and materials requirements	48
9.1	Description	48
9.2	General.....	48
9.2.1	Internal charging and discharge effects.....	48
9.2.2	Grounding and connectivity.....	48
9.2.3	Dielectric electric fields and voltages.....	49
9.3	Validation.....	50
10	Tether requirements	54
10.1	Description	54
10.2	General.....	54

10.2.1	Hazards arising on tethered spacecraft due to voltages generated by conductive tethers	54
10.2.2	Current collection and resulting problems	54
10.2.3	Hazards arising from high currents flowing through the tether and spacecraft structures.....	55
10.2.4	Continuity of insulation.	55
10.2.5	Hazards from undesired conductive paths	55
10.2.6	Hazards from electro-dynamic tether oscillations	55
10.2.7	Other effects	55
10.3	Validation.....	56
11	Electric propulsion requirements	57
11.1	Overview	57
11.1.1	Description	57
11.1.2	Coverage of the requirements	57
11.2	General.....	59
11.2.1	Spacecraft neutralization.....	59
11.2.2	Beam neutralization	60
11.2.3	Contamination.....	60
11.2.4	Sputtering	61
11.2.5	Neutral gas effects	61
11.3	Validation.....	61
11.3.1	Ground testing	61
11.3.2	Computer modelling characteristics	62
11.3.3	In-flight monitoring.....	62
11.3.4	Sputtering	62
11.3.5	Neutral gas effects	62
Annex A	(normative) Electrical hazard mitigation plan - DRD	64
A.1	DRD identification	64
A.1.1	Requirement identification and source document.....	64
A.1.2	Purpose and objective.....	64
A.2	Expected response	64
A.2.1	Scope and content	64
A.2.2	Special remarks	65
Annex B	(informative) Tailoring guidelines.....	66
B.1	Overview	66
B.2	LEO	66
B.2.1	General	66

B.2.2	LEO orbits with high inclination	67
B.3	MEO and GEO orbits.....	67
B.4	Spacecraft with onboard plasma detectors	67
B.5	Tethered spacecraft.....	68
B.6	Active spacecraft	68
B.7	Solar Wind	68
B.8	Other planetary magnetospheres.....	68
Annex C (informative)	Physical background to the requirements	69
C.1	Introduction.....	69
C.2	Definition of symbols.....	69
C.3	Electrostatic sheaths.....	69
C.3.1	Introduction	69
C.3.2	The electrostatic potential	70
C.3.3	The Debye length.....	70
C.3.4	Presheath	71
C.3.5	Models of current through the sheath.....	72
C.3.6	Thin sheath – space-charge-limited model.....	72
C.3.7	Thick sheath – orbit motion limited (OML) model	73
C.3.8	General case.....	74
C.3.9	Magnetic field modification of charging currents.....	74
C.4	Current collection and grounding to the plasma	74
C.5	External surface charging	75
C.5.1	Definition.....	75
C.5.2	Processes	75
C.5.3	Effects.....	76
C.5.4	Surface emission processes	76
C.5.5	Floating potential.....	77
C.5.6	Conductivity and resistivity	78
C.5.7	Time scales.....	80
C.6	Spacecraft motion effects	80
C.6.1	Wakes.....	80
C.6.2	Motion across the magnetic field	83
C.7	Induced plasmas	84
C.7.1	Definition.....	84
C.7.2	Electric propulsion thrusters.....	85
C.7.3	Induced plasma characteristics	85
C.7.4	Charge-exchange effects	86

C.7.5	Neutral particle effects	87
C.7.6	Effect on floating potential	87
C.8	Internal and deep-dielectric charging	87
C.8.1	Definition	87
C.8.2	Relationship to surface charging	88
C.8.3	Charge deposition	89
C.8.4	Material conductivity	89
C.8.5	Time dependence	92
C.8.6	Geometric considerations	92
C.8.7	Isolated internal conductors	93
C.8.8	Electric field sensitive systems	93
C.9	Discharges and transients	94
C.9.1	General definition	94
C.9.2	Review of the process	94
C.9.3	Dielectric material discharge.	95
C.9.4	Metallic discharge	97
C.9.5	Internal dielectric discharge	98
C.9.6	Secondary powered discharge	99
C.9.7	Discharge thresholds	99
Annex D (informative)	Charging simulation	101
D.1	Surface charging codes	101
D.1.1	Introduction	101
D.2	Internal charging codes	103
D.2.1	DICTAT	103
D.2.2	ESADDC	103
D.2.3	GEANT-4	104
D.2.4	NOVICE	104
D.3	Environment model for internal charging	104
D.3.1	FLUMIC	104
D.3.2	Worst case GEO spectrum	104
Annex E (informative)	Testing and measurement.	105
E.1	Definition of symbols	105
E.2	Solar array testing	105
E.2.1	Solar cell sample	105
E.2.2	Pre-testing of the solar array simulator (SAS)	106
E.2.3	Solar array test procedure	108
E.2.4	Other elements	112

E.2.5	The solar panel simulation device	113
E.3	Measurement of conductivity and resistivity	115
E.3.1	Determination of intrinsic bulk conductivity by direct measurement	115
E.3.2	Determination of radiation-induced conductivity coefficients by direct measurement	116
E.3.3	Determination of conductivity and radiation-induced conductivity by electron irradiation.....	117
E.3.4	The ASTM method for measurement of surface resistivity and its adaptation for space used materials.....	117
References		120
Bibliography		124
 Figures		
	Figure 6-1: Applicability of electrical continuity requirements.....	31
	Figure 7-1: Solar array test set-up	44
 Figure C-1 : Schematic diagram of potential variation through sheath and pre-sheath.		
		71
 Figure C-2 : Example secondary yield curve		
		77
 Figure C-3 : Schematic diagram of wake structure around an object at relative motion with respect to a plasma		
		81
 Figure C-4 : Schematic diagram of void region		
		82
 Figure C-5 : Schematic diagram of internal charging in a planar dielectric		
		88
 Figure C-6 : Dielectric discharge mechanism.....		
		96
 Figure C-7 :Shape of the current in relation to discharge starting point.....		
		96
 Figure C-8 : Example of discharge on pierced aluminized Teflon® irradiated by electrons with energies ranging from 0 to 220 keV.		
		97
 Figure C-9 : Schematic diagram of discharge at a triple point in the inverted voltage gradient configuration with potential contours indicated by colour scale.....		
		98
 Figure E-1 : Photograph of solar cells sample – Front face & Rear face (Stentor Sample. Picture from Denis Payan - CNES®).....		
		106
 Figure E-2 : Schematic diagram of power supply test circuit.....		
		107
 Figure E-3 : Example of a measured power source switch response.....		
		107

Figure E-4 : Example solar array simulator	108
Figure E-5 : Absolute capacitance of the satellite	109
Figure E-6 : Junction capacitance of a cell versus to voltage.....	111
Figure E-7 : The shortened solar array sample and the missing capacitances	112
Figure E-8 : Discharging circuit oscillations.....	113
Figure E-9 : Effect of an added resistance in the discharging circuit (SAS + resistance)	113
Figure E-10 : Setup simulating the satellite including flashover current	114
Figure E-11 : Basic arrangement of apparatus for measuring dielectric conductivity in planar samples	115
Figure E-12 : Arrangement for measuring cable dielectric conductivity and cross-section through co-axial cable	115
Figure E-13 : Arrangement for carrying out conductivity tests on planar samples under irradiation.....	117
Figure E-14 : Basic experimental set up for surface conductivity	119

Tables

Table 4-1: List of electrostatic and other plasma interaction effects on space systems.....	22
Table 7-1: Tested voltage-current combinations	41
Table 7-2: Typical inductance values for cables	45
Table C-1 : Parameters in different regions in space	71
Table C-2 : Typical plasma parameters for LEO and GEO	82
Table C-3 : Plasma conditions on exit plane of several electric propulsion thrusters.....	86
Table C-4 : Emission versus backflow current magnitudes for several electric propulsion thrusters.....	86
Table C-5 : Value of E_a for several materials	90