DIN EN 4075:2009-04 (D/E)

Luft- und Raumfahrt - Flachkopfschrauben, mit Flügelkreuzschlitz, Gewinde annähernd bis Kopf, aus korrosionsbeständigem Stahl, verkadmet - Klasse: 490 MPa (bei Raumtemperatur) / 425 °C; Deutsche und Englische Fassung EN 4075:2008

Aerospace series - Screws, pan head, offset cruciform recess, threaded to head, in corrosion resisting steel, passivated - Classification: 490 MPa (at ambient temperature) / 425 °C; German and English version EN 4075:2008

Inhalt

Seite

Vorwort 3

1 Anwendungsbereich 4

2 Normative Verweisungen 4

3 Anforderungen 5
3.1 Ausführung — Maße — Massen 5
3.2 Form- und Lagetoleranzen 5
3.3 Werkstoffe 5
3.4 Oberflächenbehandlung 5

4 Bezeichnung 6

5 Kennzeichnung 7

6 Technische Lieferbedingungen 7
6.1 Allgemeines 7
6.2 Anerkennung der Hersteller 7
6.3 Weitere veränderte Anforderungen 7
6.4 Gestrichene Anforderungen 7

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Required characteristics 5
3.1 Configuration — Dimensions — Masses 5
3.2 Tolerances of form and position 5
3.3 Materials 5
3.4 Surface treatment 5

4 Designation 6

5 Marking 7

6 Technical specification 7
6.1 General 7
6.2 Approval of manufacturers 7
6.3 Other modified requirements 7
6.4 Requirements deleted 7