

ISO 10830:2011-07 (E)

Space systems - Non-destructive testing - Automatic ultrasonic inspection method of graphite ingot for solid rocket motors

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | General | 4 |
| 4.1 | Requirements | 4 |
| 4.2 | Test conductor | 5 |
| 5 | Composition of ultrasonic test equipment | 5 |
| 5.1 | Basic composition of equipment | 5 |
| 5.2 | Ultrasonic test instrument | 5 |
| 5.3 | Probe | 6 |
| 5.4 | Scanning equipment | 6 |
| 5.5 | Display and recording equipment | 6 |
| 6 | Preparation of automatic ultrasonic inspection | 7 |
| 6.1 | Reference blocks | 7 |
| 6.2 | Water path | 8 |
| 6.3 | Setting for angle-beam incidence | 8 |
| 6.4 | Scanning zone and gate range | 8 |
| 6.5 | Distance-amplitude correction | 9 |
| 6.6 | Determination of apparent widths of beam spread | 9 |
| 6.7 | Selection of scanning pitch in beam-index scanning | 10 |
| 6.8 | Selection of data collection interval in incident-angle scanning | 10 |
| 6.9 | Required compensation of detection sensitivity | 10 |
| 7 | Procedure for automatic ultrasonic inspection | 11 |
| 7.1 | Test blocks | 11 |
| 7.2 | Test sequence | 12 |
| 8 | Automatic ultrasonic inspection | 13 |
| 8.1 | Preparation for testing | 13 |
| 8.2 | Primary inspection | 13 |
| 8.3 | Secondary inspection | 14 |
| 9 | Acceptance criteria | 14 |
| 10 | Reporting and recording | 14 |
| 10.1 | General | 14 |
| 10.2 | Report of test result | 14 |
| 10.3 | Scanning details and corresponding gate range | 14 |
| 10.4 | Inspection condition data | 15 |
| 10.5 | Secondary inspection details | 15 |

| | |
|---|-----------|
| Annex A (normative) Reference blocks and test method for ultrasonic characteristic determination of graphite ingot | 16 |
| Annex B (normative) Propagation-characteristic test of graphite ingot | 22 |
| Bibliography | 25 |