

# ISO 10502:2012-02 (E)

## Aerospace - Hose assemblies in polytetrafluoroethylene (PTFE) for use up to 232 °C and 10 500 kPa - Technical specifications and requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Requirements .....</b>	<b>2</b>
<b>3.1</b>	<b>Qualification .....</b>	<b>2</b>
<b>3.2</b>	<b>Materials .....</b>	<b>2</b>
<b>3.3</b>	<b>Construction .....</b>	<b>2</b>
<b>3.4</b>	<b>Inner tube requirements .....</b>	<b>3</b>
<b>3.5</b>	<b>Hose .....</b>	<b>4</b>
<b>3.6</b>	<b>Screw threads .....</b>	<b>6</b>
<b>3.7</b>	<b>Length tolerances .....</b>	<b>6</b>
<b>3.8</b>	<b>Part numbering of interchangeable parts .....</b>	<b>6</b>
<b>3.9</b>	<b>Identification of products .....</b>	<b>7</b>
<b>3.10</b>	<b>Workmanship .....</b>	<b>7</b>
<b>3.11</b>	<b>Hose assembly -- Test and performance requirements .....</b>	<b>8</b>
<b>4</b>	<b>Responsibility for inspection .....</b>	<b>10</b>
<b>4.1</b>	<b>General .....</b>	<b>10</b>
<b>4.2</b>	<b>Classification of inspections .....</b>	<b>10</b>
<b>4.3</b>	<b>Qualification inspections .....</b>	<b>10</b>
<b>4.4</b>	<b>Quality conformance inspections .....</b>	<b>13</b>
<b>4.5</b>	<b>Test conditions .....</b>	<b>14</b>
<b>4.6</b>	<b>Inspection methods .....</b>	<b>15</b>
<b>5</b>	<b>Preparation for delivery .....</b>	<b>15</b>
<b>5.1</b>	<b>Preservation and packaging .....</b>	<b>15</b>
<b>5.2</b>	<b>Marking .....</b>	<b>16</b>
<b>6</b>	<b>Ordering data .....</b>	<b>16</b>
<b>Annex A (informative) Equivalent materials and components .....</b>		<b>17</b>