ISO 26869:2012-04 (E)

Space systems - Small-auxiliary-spacecraft (SASC)-to- launch- vehicle interface control document

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative reference 1

3 Terms,definitionsandabbreviatedterms 1
3.1 Termsanddefinitions 1
3.2 Abbreviatedterms 1

4 Applicableandreferencedocumentation 2
4.1 Applicabledocuments 2
4.2 Reference documents 2
4.3 Waivers 2

5 SASC mission characteristics 2
5.1 SASC mission description 2
5.2 SASC additional constraints 2
5.3 SASC simulator 2

6 Mechanical interface 2
6.1 General 2
6.2 Mechanicalconfiguration 3
6.3 SASC fundamental frequencies 3
6.4 Usablevolume 3
6.5 LVSASC adapter interface 3
6.6 Connectorandmicroswitchdefinition 3
6.7 Purgesandfluidconnectioninterface 3

7 Electrical interfaces 4
7.1 General 4
7.2 Umbilicalwiringdiagram 4
7.3 Umbilicalconnectors 4
7.4 Umbilicalwiringlinks 4
7.5 Electrical commands dedication to SASC 5
7.6 Separation status transmission 6
7.7 Power supply 6
7.8 Earth potential continuity 6

8 Radiofrequencyandelectromagneticinterface 6

9 LV and SASC mission characteristics 6
9.1 SASC input data for mission analysis 6
9.2 Trajectory and performance analysis 7
9.3 Launch windows 7
9.4 SASCpointingandseparation 7

10 Induced environment 7
10.1 General 7

10.2 Mechanical environment 7
10.3 Thermal environment 8
10.4 Static pressure 9
10.5 Contamination and cleanliness 9
10.6 Radioandelectromagneticenvironment 9
10.7 Overallcompatibility 9

11 Verificationtests 9
11.1 General 9
11.2 SASCmechanicalenvironmentqualificationandacceptancetests 9
11.3 LV/SASC 10
11.4 Primary payload/SASC 10

12 Launch-rangeoperation 10
12.1 General 10
12.2 Rangecapabilities 10
12.3 Rangecommunicationfacility 13
12.4 Umbilicallinesandgroundlines 14
12.5 Overall data transmission 14
12.6 Operational constraints 15
12.7 Rangeservices 15