

ISO 22641:2012-07 (E)

Space data and information transfer systems - TM (telemetry) synchronization and channel coding

CONTENTS

| <u>Section</u> | <u>Page</u> |
|---|-------------|
| 1 INTRODUCTION | 1-1 |
| 1.1 PURPOSE..... | 1-1 |
| 1.2 SCOPE..... | 1-1 |
| 1.3 APPLICABILITY..... | 1-1 |
| 1.4 RATIONALE..... | 1-2 |
| 1.5 DOCUMENT STRUCTURE..... | 1-2 |
| 1.6 CONVENTIONS AND DEFINITIONS..... | 1-3 |
| 1.7 PATENTED TECHNOLOGIES..... | 1-5 |
| 1.8 REFERENCES..... | 1-5 |
| 2 OVERVIEW | 2-1 |
| 2.1 ARCHITECTURE..... | 2-1 |
| 2.2 SUMMARY OF FUNCTIONS..... | 2-1 |
| 2.3 INTERNAL ORGANIZATION OF SUBLAYER..... | 2-3 |
| 3 CONVOLUTIONAL CODING | 3-1 |
| 3.1 OVERVIEW..... | 3-1 |
| 3.2 GENERAL..... | 3-1 |
| 3.3 BASIC CONVOLUTIONAL CODE SPECIFICATION..... | 3-2 |
| 3.4 PUNCTURED CONVOLUTIONAL CODES..... | 3-4 |
| 4 REED-SOLOMON CODING | 4-1 |
| 4.1 OVERVIEW..... | 4-1 |
| 4.2 GENERAL..... | 4-1 |
| 4.3 SPECIFICATION..... | 4-1 |
| 4.4 DISCUSSION..... | 4-6 |
| 5 CONCATENATED CODING | 5-1 |
| 6 TURBO CODING | 6-1 |
| 6.1 OVERVIEW..... | 6-1 |
| 6.2 GENERAL..... | 6-1 |
| 6.3 SPECIFICATION..... | 6-1 |

CONTENTS (continued)

| <u>Section</u> | <u>Page</u> |
|--|-------------|
| 7 LOW-DENSITY PARITY-CHECK CODING | 7-1 |
| 7.1 OVERVIEW | 7-1 |
| 7.2 GENERAL | 7-1 |
| 7.3 LOW-DENSITY PARITY-CHECK CODE WITH RATE 223/255 | 7-2 |
| 7.4 LOW-DENSITY PARITY-CHECK CODE FAMILY WITH RATES 1/2, 2/3, AND 4/5 | 7-7 |
| 8 FRAME SYNCHRONIZATION | 8-1 |
| 8.1 OVERVIEW | 8-1 |
| 8.2 THE ATTACHED SYNC MARKER (ASM) | 8-2 |
| 8.3 ASM BIT PATTERNS | 8-2 |
| 8.4 LOCATION OF ASM | 8-4 |
| 8.5 RELATIONSHIP OF ASM TO REED-SOLOMON, TURBO, AND LDPC CODEBLOCKS AND CODEWORDS | 8-4 |
| 8.6 ASM FOR EMBEDDED DATA STREAM | 8-5 |
| 9 PSEUDO-RANDOMIZER | 9-1 |
| 9.1 OVERVIEW | 9-1 |
| 9.2 PSEUDO-RANDOMIZER DESCRIPTION | 9-1 |
| 9.3 SYNCHRONIZATION AND APPLICATION OF PSEUDO-RANDOMIZER ... | 9-2 |
| 9.4 SEQUENCE SPECIFICATION | 9-2 |
| 9.5 LOGIC DIAGRAM | 9-3 |
| 10 TRANSFER FRAME LENGTHS | 10-1 |
| 10.1 OVERVIEW | 10-1 |
| 10.2 GENERAL | 10-1 |
| 10.3 CASE 1: UNCODED | 10-1 |
| 10.4 CASE 2: CONVOLUTIONAL ONLY | 10-1 |
| 10.5 CASE 3: REED-SOLOMON ONLY | 10-1 |
| 10.6 CASE 4: CONCATENATED | 10-2 |
| 10.7 CASE 5: TURBO | 10-2 |
| 10.8 CASE 6: LDPC | 10-3 |
| 11 MANAGED PARAMETERS | 11-1 |
| 11.1 OVERVIEW | 11-1 |
| 11.2 GENERAL | 11-1 |

CONTENTS (continued)

| <u>Section</u> | <u>Page</u> |
|---|-------------|
| 11.3 MANAGED PARAMETERS FOR SELECTED OPTIONS | 11-1 |
| 11.4 MANAGED PARAMETERS FOR CONVOLUTIONAL CODE | 11-2 |
| 11.5 MANAGED PARAMETERS FOR REED-SOLOMON CODE | 11-2 |
| 11.6 MANAGED PARAMETERS FOR TURBO CODE | 11-3 |
| 11.7 MANAGED PARAMETERS FOR LOW-DENSITY PARITY-CHECK CODE | 11-3 |
| 11.8 MANAGED PARAMETERS FOR FRAME SYNCHRONIZATION | 11-3 |
| ANNEX A SERVICE (NORMATIVE)..... | A-1 |
| ANNEX B SECURITY, SANA, AND PATENT CONSIDERATIONS (INFORMATIVE) | B-1 |
| ANNEX C ANNEX TO SUBSECTION 7.3, LOW-DENSITY PARITY- CHECK CODE WITH RATE 223/255 (INFORMATIVE)..... | C-1 |
| ANNEX D ACRONYMS AND TERMS (INFORMATIVE)..... | D-1 |
| ANNEX E INFORMATIVE REFERENCES (INFORMATIVE) | E-1 |
| ANNEX F TRANSFORMATION BETWEEN BERLEKAMP AND CONVENTIONAL REPRESENTATIONS (INFORMATIVE)..... | F-1 |
| ANNEX G EXPANSION OF REED-SOLOMON COEFFICIENTS (INFORMATIVE) | G-1 |
| ANNEX H CHANGES FROM REFERENCES [E2] AND [E3] (INFORMATIVE) | H-1 |
| | |
| <u>Figure</u> | |
| 1-1 Bit Numbering Convention..... | 1-4 |
| 2-1 Relationship with OSI Layers | 2-1 |
| 2-2 Internal Organization of the Sublayer at the Sending End..... | 2-4 |
| 2-3 Internal Organization of the Sublayer at the Receiving End..... | 2-5 |
| 3-1 Basic Convolutional Encoder Block Diagram | 3-3 |
| 3-2 Punctured Encoder Block Diagram | 3-4 |
| 4-1 Reed-Solomon Codeblock Partitioning | 4-5 |
| 4-2 Functional Representation of R-S Interleaving..... | 4-7 |
| 6-1 Interpretation of Permutation..... | 6-5 |
| 6-2 Turbo Encoder Block Diagram | 6-5 |
| 6-3 Turbo Codewords for Different Code Rates..... | 6-8 |
| 6-4 Turbo Codeword with Attached Sync Marker..... | 6-9 |
| 7-1 Base Parity Check Matrix of the Basic (8176, 7156) LDPC Code..... | 7-3 |
| 7-2 Systematic Circulant Generator Matrix | 7-6 |
| 7-3 Shortened Codeword..... | 7-7 |
| 8-1 ASM Bit Pattern for Uncoded, Convolutional, Reed-Solomon, Concatenated, and Rate 7/8 LDPC Coded Data | 8-3 |

CONTENTS (continued)

| <u>Figure</u> | <u>Page</u> |
|--|-------------|
| 8-2 ASM Bit Pattern for Rate 1/2 Turbo and Rates 1/2, 2/3, and 4/5 LDPC Coded Data | 8-3 |
| 8-3 ASM Bit Pattern for Rate 1/3 Turbo Coded Data | 8-3 |
| 8-4 ASM Bit Pattern for Rate 1/4 Turbo Coded Data | 8-3 |
| 8-5 ASM Bit Pattern for Rate 1/6 Turbo Coded Data | 8-4 |
| 8-6 Embedded ASM Bit Pattern | 8-5 |
| 9-1 Pseudo-Randomizer Configuration | 9-2 |
| 9-2 Pseudo-Randomizer Logic Diagram | 9-3 |
| F-1 Transformational Equivalence | F-2 |

Table

| | |
|--|------|
| 3-1 Puncture Code Patterns for Convolutional Code Rates | 3-4 |
| 6-1 Specified Information Block Lengths | 6-3 |
| 6-2 Codeword Lengths for Supported Code Rates (Measured in Bits) | 6-3 |
| 6-3 Parameters k_1 and k_2 for Specified Information Block Lengths | 6-4 |
| 7-1 Specification of Circulants | 7-4 |
| 7-2 Values of Submatrix Size M for Supported Codes | 7-7 |
| 7-3 Description of $\phi_k(0, M)$ and $\phi_k(1, M)$ | 7-9 |
| 7-4 Description of $\phi_k(2, M)$ and $\phi_k(3, M)$ | 7-10 |
| 7-5 Codeword Lengths for Supported Code Rates (Measured in Bits) | 7-11 |
| 11-1 Managed Parameters for Selected Options | 11-2 |
| 11-2 Managed Parameters for Convolutional Code | 11-2 |
| 11-3 Managed Parameters for Reed-Solomon Code | 11-2 |
| 11-4 Managed Parameters for Turbo Code | 11-3 |
| 11-5 Managed Parameters for Low Density Parity Check Code | 11-3 |
| 11-6 Managed Parameters for Frame Synchronization | 11-3 |
| C-1 Table of Circulants for the Generator Matrix | C-1 |
| F-1 Equivalence of Representations | F-5 |
| H-1 Terms That Have Been Changed from Reference [E2] | H-2 |
| H-2 Terms That Have Been Changed from Reference [E3] | H-2 |