

DIN EN 16603-50-01:2014-12 (E)

Space engineering - Space data links - Telemetry synchronization and channel coding; English version EN 16603-50-01:2014

Contents	Page
Foreword	6
1 Scope.....	7
2 Normative references.....	8
3 Terms, definitions and abbreviated terms.....	9
3.1 Terms from other standards.....	9
3.2 Terms specific to the present standard	9
3.3 Abbreviations.....	9
3.4 Conventions.....	10
4 Overview.....	11
4.1 Introduction.....	11
4.2 Coding	11
4.2.1 Channel codes	11
4.2.2 Connection vectors	12
4.3 Convolutional codes	12
4.4 Reed-Solomon codes	12
4.5 Concatenated codes	13
4.6 Turbo codes.....	13
4.7 Synchronization and pseudo-randomization	13
5 Convolutional coding	16
5.1 Properties	16
5.2 General.....	16
5.3 Basic convolutional code	17
5.4 Punctured convolutional code	18
6 Reed-Solomon coding.....	20
6.1 Properties	20
6.2 General.....	20
6.3 Specification	21
6.3.1 Parameters and general characteristics	21
6.3.2 Generator polynomials	21

6.3.3	Symbol interleaving depth	22
6.3.4	Symbol interleaving mechanism.....	22
6.3.5	Reed-Solomon codeblock partitioning	23
6.3.6	Shortened codeblock length.....	24
6.3.7	Dual basis symbol representation and ordering.....	25
6.3.8	Synchronization	26
6.3.9	Ambiguity resolution.....	26
6.4	Reed-Solomon with $E=8$	26
6.4.1	Introduction	26
6.4.2	General.....	27
7	Turbo coding.....	28
7.1	Properties	28
7.2	General.....	28
7.3	Specification	29
7.3.1	General	29
7.3.2	Parameters and general characteristics	29
7.3.3	Turbo code permutation	30
7.3.4	Backward and forward connection vectors	32
7.3.5	Turbo encoder block	33
7.3.6	Turbo codeblock specification	33
7.3.7	Turbo codeblock synchronization	34
8	Frame synchronization	35
8.1	Introduction.....	35
8.2	The attached sync marker (ASM)	35
8.2.1	Overview.....	35
8.2.2	Encoder side	36
8.2.3	Decoder side.....	36
8.3	ASM bit patterns	36
8.4	Location of ASM	37
8.5	Relationship of ASM to Reed-Solomon and turbo codeblocks	37
8.6	ASM for embedded data stream	38
8.6.1	Overview.....	38
8.6.2	Embedded ASM.....	38
9	Pseudo-randomizer	39
9.1	General.....	39
9.1.1	Overview.....	39

9.1.2	Application	39
9.2	Pseudo-randomizer description	39
9.3	Synchronization and application of pseudo-randomizer	40
9.3.1	Overview	40
9.3.2	Application	40
9.4	Sequence specification	41
Annex A (informative)	Transformation between Berlekamp and conventional representations	43
Annex B (informative)	Expansion of Reed-Solomon coefficients	50
Annex C (informative)	Compatible frame lengths	52
Annex D (informative)	Application profiles	54
Annex E (informative)	Changes from ESA-PSS-04-103.....	60
Annex F (informative)	Differences from CCSDS recommendations	61
Annex G (informative)	Mission configuration parameters.....	62
Annex H (informative)	Turbo code patent rights	66
Bibliography.....		67

Figures

Figure 3-1:	Bit numbering convention	10
Figure 4-1:	Coding, randomization and synchronization (1).....	14
Figure 4-2:	Coding, randomization and synchronization (2).....	15
Figure 5-1:	Convolutional encoder block diagram.....	18
Figure 5-2:	Punctured encoder block diagram	19
Figure 6-1:	Functional representation of R-S interleaving	23
Figure 6-2:	Reed-Solomon codeblock partitioning	24
Figure 7-1:	Interpretation of permutation	31
Figure 7-2:	Turbo encoder block diagram.....	32
Figure 7-3:	Turbo codeblocks for code rates 1/2 and 1/4.....	34
Figure 7-4:	Turbo codeblock with attached sync marker.....	34
Figure 8-1:	Format of channel access data unit (CADU).....	35
Figure 8-2	ASM bit pattern for non-turbo-coded data.....	36
Figure 8-3:	ASM bit pattern for rate 1/2 turbo-coded data.....	36
Figure 8-4:	ASM bit pattern for rate 1/4 turbo-coded data.....	37
Figure 8-5:	Embedded ASM bit pattern	38

Figure 9-1: Pseudo-randomizer configuration	40
Figure 9-2: Pseudo-randomizer logic diagram	42
Figure A-1 : Transformational equivalence	44

Tables

Table 5-1: Basic convolutional code characteristics.....	17
Table 5-2: Punctured convolutional code characteristics	19
Table 5-3: Puncture code patterns for convolutional codes	19
Table 7-1: Specified information block lengths	30
Table 7-2: Codeblock lengths (measured in bits).....	30
Table 7-3: Parameters k_1 and k_2 for specified information block lengths.....	31
Table 7-4: Forward connection vectors.....	32
Table 8-1: ASM bit patterns in hexadecimal notation.....	37
Table A-1 : Equivalence of representations (Part 1 of 4).....	46
Table B-1 : Expansion for $E=16$	50
Table B-2 : Expansion for $E=8$	51
Table C-1 : Maximum frame lengths for $E=16$	53
Table C-2 : Maximum frame lengths for $E=8$	53
Table D-1 : Preferred coding schemes	56
Table D-2 : Coding gains and bandwidth expansions	58
Table D-3 : Coding gains for R-S(255, 239) and 4D-8PSK-TCM	59