

DIN EN 16603-50-04:2014-12 (E)

Space engineering - Space data links - Telecommand protocols, synchronization and channel coding; English version EN 16603-50-04:2014

Contents	Page
Foreword	10
1 Scope	11
2 Normative references	12
3 Terms, definitions and abbreviated terms	13
3.1 Terms from other standards.....	13
3.2 Terms specific to the present standard	13
3.3 Abbreviated terms.....	14
3.4 Conventions.....	15
3.4.1 Bit 0, bit 1, bit N-1.....	15
3.4.2 Most significant bit.....	15
3.4.3 Use of capitals for the names of data structures and fields.....	15
4 Overview	16
4.1 Presentation	16
4.2 Protocol profiles	16
4.3 Segmentation sublayer	17
4.4 Transfer sublayer.....	18
4.5 Synchronization and channel coding sublayer	18
4.6 Physical layer	18
4.7 Virtual channels	19
5 Segmentation sublayer	20
5.1 Overview	20
5.2 TC Segment	21
5.2.1 General.....	21
5.2.2 Segment Header	22
5.2.3 Segment Data Field	23
5.3 Transfer notification	23
5.3.1 Overview.....	23
5.3.2 Requirements.....	24
5.4 Blocking of packets.....	25

5.4.1	Overview	25
5.4.2	Virtual channels where TC Segments are used.....	25
5.4.3	Virtual channels where TC Segments are not used.....	26
5.4.4	Packet properties	26
5.4.5	Blocking function.....	27
5.4.6	Deblocking function.....	27
5.5	Segmentation	27
5.5.1	Overview	27
5.5.2	Segmenting function	28
5.5.3	Reassembly function.....	28
5.5.4	Packet assembly controller	29
5.6	MAP multiplexing.....	32
6	Transfer sublayer	33
6.1	Overview	33
6.1.1	Data structures in the transfer sublayer.....	33
6.1.2	Procedures in the transfer sublayer.....	33
6.2	TC Transfer Frame definition	35
6.2.1	General	35
6.2.2	Transfer Frame Primary Header.....	36
6.2.3	Transfer Frame Data Field	40
6.2.4	Frame Error Control Field.....	41
6.3	CLCW definition.....	43
6.3.1	General	43
6.3.2	Control Word Type	45
6.3.3	CLCW Version Number.....	45
6.3.4	Status Field	45
6.3.5	COP in Effect	45
6.3.6	Virtual Channel Identification.....	45
6.3.7	Reserved Spare	46
6.3.8	No RF Available Flag	46
6.3.9	No Bit Lock Flag.....	47
6.3.10	Lockout Flag	47
6.3.11	Wait Flag.....	48
6.3.12	Retransmit Flag.....	48
6.3.13	FARM-B Counter	48
6.3.14	Reserved Spare	48
6.3.15	Report Value	49

6.4	Frame header procedure	49
6.5	Frame error control procedure at the sending end	49
6.6	Frame delimiting and fill removal procedure.....	49
6.6.1	Overview	49
6.6.2	Actions	50
6.7	Frame error control procedure at the receiving end	50
6.8	Frame header validation procedure	50
6.8.1	Overview.....	50
6.8.2	Actions	51
6.9	Virtual channel multiplexing	51
6.9.1	Overview.....	51
6.9.2	Multiplexing mechanism.....	52
6.9.3	Demultiplexing	52
7	COP-1.....	53
7.1	Overview	53
7.1.1	Scope.....	53
7.1.2	Interfaces	53
7.1.3	Retransmission protocol.....	53
7.1.4	Frames.....	54
7.1.5	Services	54
7.1.6	Protocol machine	56
7.2	Internal variables	56
7.2.1	Overview.....	56
7.2.2	FOP-1 Variables	57
7.2.3	FARM-1 variables	64
7.3	Features of COP-1 interfaces	69
7.3.1	Overview.....	69
7.3.2	Parameters	70
7.4	Upper interface of COP-1 at the sending end	70
7.4.1	Overview.....	70
7.4.2	Sequence-controlled service management interface	71
7.4.3	Sequence-controlled service data transfer interface.....	77
7.4.4	Expedited service data transfer interface	80
7.5	Upper interface of COP-1 at the receiving end.....	82
7.5.1	Overview.....	82
7.5.2	Buffer management mechanism.....	82
7.5.3	The wait system	82

7.5.4	Single back-end buffer	83
7.5.5	FDU Arrived Indication	84
7.6	Lower interface of COP-1 at the sending end	84
7.6.1	Overview	84
7.6.2	Transmit Request for Frame signal	85
7.6.3	Abort request signal	85
7.6.4	Response signal	86
7.7	Lower interface of COP-1 at the receiving end.....	86
7.7.1	Overview	86
7.7.2	Valid Frame Arrived Indication	87
7.8	Format of COP-1 control commands	87
7.8.1	Overview	87
7.8.2	General	87
7.8.3	Unlock	87
7.8.4	Set V(R)	88
7.9	Actions.....	88
7.9.1	Format of the state tables.....	88
7.9.2	FOP-1	89
7.9.3	FARM-1	96

8 Synchronization and channel coding sublayer111

8.1	Overview	111
8.2	BCH codeblock.....	111
8.2.1	General	111
8.2.2	Information	112
8.2.3	Error Control	112
8.3	Communications link transmission unit (CLTU).....	113
8.3.1	General	113
8.3.2	Start Sequence	113
8.3.3	Encoded Data	114
8.3.4	Tail Sequence	114
8.4	Randomization procedure.....	115
8.4.1	Overview	115
8.4.2	General	115
8.4.3	Random sequence	115
8.4.4	Application of the randomizer	116
8.5	BCH codeblock encoding procedure.....	116
8.6	Fill bits	117

8.6.1	Overview.....	117
8.6.2	General.....	117
8.7	Channel logic at the receiving end.....	118
8.8	BCH codeblock decoding procedures.....	119
8.8.1	Overview.....	119
8.8.2	General.....	120
9	Physical layer.....	121
9.1	Overview.....	121
9.2	Physical layer data structures.....	121
9.2.1	Acquisition sequence.....	121
9.2.2	CLTU.....	122
9.2.3	Idle sequence.....	122
9.3	Physical layer procedures.....	122
9.3.1	Overview.....	122
9.3.2	Carrier modulation modes.....	122
9.3.3	Telecommand session.....	124
9.3.4	Physical layer operation procedure (PLOP).....	124
Annex A (informative)	Frame error control.....	127
A.1	Overview.....	127
A.2	Encoding.....	127
A.3	Decoding.....	128
Annex B (informative)	Changes from ESA-PSS-04-107.....	129
B.1	Overview.....	129
B.2	Technical changes.....	129
Annex C (informative)	Differences from CCSDS recommendations.....	132
C.1	Overview.....	132
C.2	Differences.....	132
Annex D (informative)	Performance issues.....	135
D.1	Introduction.....	135
D.2	Performance components.....	136
D.3	Factors affecting frame rejection rate.....	136
D.3.1	Bit synchronization factor.....	136
D.3.2	CLTU Start Sequence factors.....	137
D.3.3	BCH Codeblock Factor.....	138
D.3.4	Tail Sequence factor.....	140

D.3.5	Frames and CLTUs.....	141
D.4	Factors affecting frame undetected error rate	143
Annex E (informative)	Mission configuration parameters	147
E.1	Introduction.....	147
E.2	Parameters of a physical channel	147
E.2.1	Overview.....	147
E.2.2	Fixed parameters	147
E.2.3	Length of the acquisition sequence	147
E.2.4	Physical layer operation procedure	148
E.2.5	Transfer Frame Version Number.....	148
E.2.6	Maximum length of a TC Transfer Frame.....	148
E.2.7	Virtual channels	148
E.2.8	Use of the expedited service	148
E.2.9	Multiplexing parameters	148
E.3	Parameters of a virtual channel	149
E.3.1	Overview.....	149
E.3.2	Spacecraft Identifier and Virtual Channel Identifier.....	149
E.3.3	Maximum length of a TC Transfer Frame.....	149
E.3.4	FOP-1 parameters	149
E.3.5	CLCW reporting rate	149
E.3.6	Status Field of CLCW.....	149
E.3.7	Fixed parameters	149
E.3.8	FARM-1 sliding window parameters.....	150
E.3.9	Use of TC Segments.....	150
E.3.10	Parameters of a virtual channel with TC Segments.....	150
E.3.11	Parameters of a virtual channel without TC Segments.....	150
E.4	Parameters of a MAP	151
E.4.1	Overview.....	151
E.4.2	MAP Identifier	151
E.4.3	Use of the blocking function	151
E.4.4	Segmentation function	151
E.5	Parameters for packet types	152
E.5.1	Overview.....	152
E.5.2	Valid packet version numbers	152
Bibliography.....		153

Figures

Figure 3-1: numbering convention	15
Figure 4-1: Layers and sublayers specified in this Standard	17
Figure 5-1: TC Segment	21
Figure 5-2: Example of blocking of packets	25
Figure 5-3: Example of segmentation of a user data unit	28
Figure 6-1: TC Transfer Frame format	36
Figure 6-2: Format of a CLCW	44
Figure 7-1: COP-1 sequence variables	55
Figure 7-2: FARM sliding window concept	67
Figure 7-3: State table format	89
Figure 7-4: Actions for look for directive	94
Figure 7-5: Actions for look for FDU	95
Figure 7-6: FOP-1 state transitions for main protocol	105
Figure 7-7: FOP-1 state transitions for initialisation protocol	106
Figure 7-8: FOP-1 state transitions	107
Figure 7-9: FARM-1 state transitions	110
Figure 8-1: BCH codeblock format	112
Figure 8-2: Format of a CLTU	113
Figure 8-3: Bit pattern of the Start Sequence	113
Figure 8-4: Bit transition generator logic diagram	116
Figure 8-5: (63,56) Modified BCH code generator	117
Figure 8-6: State diagram for the channel (receiving end)	119
Figure 9-1: Sequence of CMMs comprising PLOP-2	125
Figure 9-2: Sequence of CMMs comprising PLOP-1	126
Figure A-1 : Encoder	127
Figure A-2 : Decoder	128
Figure D-1 : Frame rejection probability, P_{FY} , in SEC mode using PLOP-2	143
Figure D-2 : Probability of undetected error in a frame in SEC mode	146

Tables

Table 6-1: Sending-end procedures in the transfer sublayer	34
Table 6-2: Receiving-end procedures in the transfer sublayer	35
Table 6-3: Combined Bypass Flag and Control Command Flag	38
Table 6-4: Fields in a CLCW	43
Table 7-1: COP-1 interfaces	70

Table 7-2: Signals for management interface	71
Table 7-3: FOP-1 directive types and qualifiers	73
Table 7-4: Reasons for an Alert notification	75
Table 7-5: Signals for sequence-controlled service data transfer interface	78
Table 7-6: Signals for expedited service data transfer interface.....	80
Table 7-7: Signals for the interface of FOP-1 to the lower procedures.....	84
Table 7-8: FOP-1 state table	98
Table 7-9: FARM-1 state table.....	108
Table 8-1: Channel states (receiving end)	118
Table 8-2: Channel events (receiving end)	119
Table 9-1: Carrier modulation modes	123
Table B-1 : Field name differences from ESA-PSS-04-107	131
Table B-2 : Names with “Communications” or “Command”	131
Table C-1 : Name differences from CCSDS recommendations	134
Table D-1 : Probability of not recognizing the Start Sequence	138
Table D-2 : Meaning of decoding values	138
Table D-3 : Decoding cases in SEC mode.....	138
Table D-4 : Probability of codeblock rejection for a CLTU during decoding in SEC mode...	140
Table D-5 : Parity and Syndrome when Tail Sequence has errors.....	141
Table D-6 : Probability of missing the Tail Sequence.....	141
Table D-7 : Frame rejection probability, P_{FY} (PLOP-2).....	142
Table D-8 : Sources of undetected errors (SEC mode).....	143
Table D-9 : Probability of n errors occurring in a codeblock.....	144
Table D-10 : Error detection performance when decoding a codeblock in SEC mode	144
Table D-11 : Probability of undetected error in a frame, SEC mode, with CRC	145