

DIN EN 16603-50-05:2017-06 (E)

Space engineering - Radio frequency and modulation; English version EN 16603-50-05:2014 + AC:2017

| Inhalt | Seite |
|---|-----------|
| Foreword | 6 |
| Introduction..... | 7 |
| 1 Scope..... | 8 |
| 2 Normative references..... | 9 |
| 3 Terms, definitions and abbreviated terms..... | 10 |
| 3.1 Terms from other standards..... | 10 |
| 3.2 Terms specific to the present standard | 10 |
| 3.3 Abbreviated terms..... | 12 |
| 4 Frequency allocations, assignment and use | 15 |
| 4.1 Frequency allocations to the Space Operation, Space Research and Earth Exploration-Satellite services | 15 |
| 4.1.1 Overview | 15 |
| 4.1.2 Frequency bands allocated to the Space Radiocommunications services..... | 15 |
| 4.2 Specific conditions for the use of certain frequency bands..... | 17 |
| 4.2.1 2 025 MHz – 2 120 MHz and 2 200 MHz – 2 300 MHz bands | 17 |
| 4.2.2 8 025 MHz – 8 400 MHz band..... | 18 |
| 4.2.3 8 400 MHz - 8 450 MHz band | 19 |
| 4.2.4 8 450 MHz – 8 500 MHz band..... | 19 |
| 4.2.5 25,5 GHz – 27,0 GHz, 37,0 GHz – 38 GHz and 40,0 GHz – 40,5 GHz bands | 19 |
| 4.3 Frequency assignment procedure..... | 20 |
| 4.3.1 Choice of frequencies | 20 |
| 4.3.2 Advance publication, coordination and notification of frequencies | 21 |
| 5 Transmitted signals..... | 22 |
| 5.1 Turnaround frequency ratio for coherent transponders | 22 |
| 5.1.1 Generation of the transmitted carrier..... | 22 |
| 5.1.2 Band pairs..... | 22 |
| 5.2 Carrier frequency stability | 24 |
| 5.2.1 Spacecraft transmitter | 24 |

| | | |
|----------|---|-----------|
| 5.2.2 | Spacecraft receiver | 25 |
| 5.2.3 | Ground station equipment..... | 25 |
| 5.3 | Polarization..... | 26 |
| 5.4 | Occupied bandwidth considerations | 26 |
| 5.5 | Emissions | 28 |
| 5.5.1 | Unwanted emission power level..... | 28 |
| 5.5.2 | Cessation of emissions | 32 |
| 5.5.3 | Power flux density limits at the Earth's surface..... | 32 |
| 5.5.4 | Power flux density limits at the GSO in the 25,5 GHz - 27,0 GHz band | 33 |
| 5.5.5 | Power limits for Earth station emissions | 34 |
| 5.5.6 | Time limitations on transmissions..... | 35 |
| 6 | Modulation | 36 |
| 6.1 | Phase modulation with residual carriers..... | 36 |
| 6.1.1 | Application | 36 |
| 6.1.2 | Modulating waveforms | 36 |
| 6.1.3 | PCM waveforms and data rates | 37 |
| 6.1.4 | Use of subcarriers | 39 |
| 6.1.5 | Data transition density..... | 41 |
| 6.1.6 | Carrier modulation index | 42 |
| 6.1.7 | Sense of modulation | 42 |
| 6.1.8 | Modulation linearity | 42 |
| 6.1.9 | Residual amplitude modulation | 42 |
| 6.1.10 | Carrier phase noise..... | 43 |
| 6.1.11 | Residual carrier, out-of-band emission and discrete spectral lines | 43 |
| 6.2 | Suppressed carrier modulation..... | 44 |
| 6.2.1 | Application and modulation schemes | 44 |
| 6.2.2 | Modulating waveforms | 45 |
| 6.2.3 | Carrier modulation..... | 45 |
| 6.2.4 | Data transition density..... | 51 |
| 6.2.5 | Symbol rate stability | 51 |
| 6.2.6 | Carrier phase noise..... | 51 |
| 6.2.7 | Carrier suppression, out-of-band emission and discrete spectral lines | 51 |
| 6.3 | Spectral roll-off | 52 |
| 7 | Link acquisition procedures | 53 |
| 7.1 | Space-Earth..... | 53 |
| 7.1.1 | Normal operation | 53 |

| | | |
|--|--|-----------|
| 7.1.2 | Alternative mode of operation | 53 |
| 7.1.3 | Coherent mode | 53 |
| 7.2 | Earth-space | 54 |
| 7.2.1 | 2 025 MHz - 2 110 MHz category A | 54 |
| 7.2.2 | 2 110 MHz - 2 120 MHz category B | 55 |
| 7.2.3 | 7 145 MHz - 7 190 MHz category B | 55 |
| 7.2.4 | 7 190 MHz – 7 235 MHz category A..... | 55 |
| 8 RF interface control..... | | 57 |
| 8.1 | RF interface control documents | 57 |
| 8.2 | Spacecraft-Earth station interface control document..... | 57 |
| 8.2.1 | Overview..... | 57 |
| 8.2.2 | Process..... | 57 |
| 8.3 | Link budget tables..... | 58 |
| 8.3.1 | General..... | 58 |
| 8.3.2 | Parameters | 58 |
| 8.4 | Spacecraft-ground network compatibility test..... | 61 |
| 9 GMSK and 8PSK TCM modulation formats | | 63 |
| 9.1 | GMSK modulation format..... | 63 |
| 9.2 | 8PSK TCM modulation format | 64 |
| 9.2.1 | General principles | 64 |
| 9.2.2 | 4 dimensional 8PSK-TCM encoder | 64 |
| 9.2.3 | Differential encoders for SEF = 2 and 2,5..... | 65 |
| 9.2.4 | Trellis encoder structure..... | 66 |
| 9.2.5 | Constellation mapper for 4 dimensional 8PSK-TCM..... | 66 |
| 9.2.6 | Channel filtering | 68 |
| Annex A (normative) Spacecraft-Earth station interface control document - DRD | | 71 |
| Annex B (informative) Cross-support from other networks | | 72 |
| Annex C (informative) Protection of Ariane-5 RF system | | 73 |
| Annex D (informative) Differences from CCSDS recommendations..... | | 76 |
| Annex E (informative) Tailoring guidelines..... | | 78 |
| Bibliography..... | | 79 |

Figures

| | |
|---|----|
| Figure 4-1: Maximum allowable bandwidth in the band 8 400 MHz - 8 450 MHz | 20 |
| Figure 6-1: PCM waveforms and symbol duration definition | 38 |
| Figure 6-2: Symbol rate reference point | 39 |
| Figure 6-3: QPSK/OQPSK constellation mapping | 46 |
| Figure 6-4: OQPSK post-amplifier filter transfer function | 49 |
| Figure 6-5: Spectral emission masks for telemetry transmission at symbol rates above 60 ksps | 52 |
| Figure 8-1: Parameter distributions and their equations..... | 60 |
| Figure 9-1: General principle of the 4D-8PSK TCM modulator | 65 |
| Figure 9-2: Codes to eliminate 22,5° phase ambiguity on carrier synchronization | 66 |
| Figure 9-3: Representation of a 64 state L=7, rate 3/4 systematic trellis encoder..... | 66 |
| Figure 9-4: Constellation mapper for SEF = 2..... | 67 |
| Figure 9-5: Constellation mapper for SEF = 2,5..... | 67 |
| Figure 9-6: Transmit structure for baseband, square root raised-cosine shaping..... | 69 |
| Figure 9-7: Transfer function for a 4 poles/2 zeros elliptic filter..... | 69 |
| Figure 9-8: Transmit structure for post-amplifier shaping..... | 70 |

Tables

| | |
|--|----|
| Table 4-1: Frequency allocations to the Space Operation, Space Research and Earth Exploration-Satellite services | 16 |
| Table 5-1: Turnaround frequency ratios for coherent transponder operation | 23 |
| Table 5-2 Alternative turnaround frequency ratios for coherent transponder operation..... | 24 |
| Table 5-3: Frequency stability for spacecraft transmitters..... | 24 |
| Table 5-4: Frequency stability for spacecraft receivers | 25 |
| Table 5-5: Occupied bandwidth | 27 |
| Table 5-6: Maximum level of spurious emissions..... | 28 |
| Table 5-7: Threshold levels of interference detrimental to radio astronomy spectral line (i.e. narrow bandwidth) observations at the surface of the Earth due to terrestrial interference sources (Recommendation ITU-R RA.769-2)..... | 30 |
| Table 5-8: Threshold levels of interference detrimental to radio astronomy continuum (i.e. wide bandwidth) observations at the surface of the Earth due to terrestrial interference sources (Recommendation ITU-R RA.769-2)..... | 31 |
| Table 5-9: Harmful interference levels at deep space antenna sites | 32 |
| Table 5-10: Power flux density limits at the Earth's surface | 33 |
| Table 6-1: PCM waveforms and rates for residual carrier modulation..... | 37 |
| Table 6-2: Subcarriers used with phase-modulated carriers | 39 |
| Table 6-3: Limits of the peak modulation index..... | 42 |
| Table 6-4: PCM waveforms | 45 |
| Table 8-1: Probability density functions for link budgets | 60 |