DIN EN 16603-50-15:2017-08 (E)

Space engineering - CANbus extention protocol; English version EN 16603-50-15:2017

Table of contents

European foreword 7

Introduction 8

1 Scope 9

2 Normative references 10

3 Terms, definitions and abbreviated terms 12

3.1 Terms from other standards 12

3.2 Terms specific to the present standard 12

3.3 Abbreviated terms 16

3.4 Bit numbering convention 17

3.5 Nomenclature 17

4 Overview of the standard and principles 19

4.1 Document organization 19

4.2 Relationship of CAN Bus Network to existing Architectures 19

4.3 CANbus network 20

4.4 Physical layer 21

4.5 Communication model 21

4.6 CANopen higher layer protocol 21

4.7 Time distribution 23

4.7.1 Overview 23

4.7.2 SYNC message and protocol 24

4.7.3 Bit timing 24

4.8 Redundancy management and monitoring 24

4.8.1 Overview 24

4.8.2 Node Monitoring via Node-Guarding or Heartbeat Messages 25

4.8.3 Bus monitoring and reconfiguration management 26

4.9 Connectors and pin assignments 27

4.10 Minimal protocol set 27

5 Physical layer 28

5.1 Topology 28

5.1.1 Physical topology 28
5.1.2 Maximum bus length and drop length 30
5.1.3 Number of network devices 30
5.2 Medium 31
5.2.1 Cable requirements 31
5.2.2 Connectors 32
5.3 Transceiver characteristics 32
5.3.1 General 32
5.3.2 ISO 11898-2:2003 transceiver electrical characteristics 33
5.3.3 Resistance to electrical CAN Network faults 33
5.3.4 Transceiver isolation 38
5.3.5 Physical layer implementation based on RS-485 transceivers 38
5.3.6 Detailed implementation for RS-485 transceiver 39
5.4 Bit timing 39
5.4.1 Bit rate 1 Mbps 39
5.4.2 Other bit rates 39
5.4.3 Bit timing 39
5.5 Electromagnetic compatibility (EMC) 40
5.6 Data link layer 40
5.6.1 ISO 11898 compliance 40
5.6.2 Fault confinement 40
6 CANopen higher layer protocol 42
6.1 Service data objects 42
6.2 Process data objects 42
6.3 Synchronisation object 42
6.4 Emergency object 43
6.5 Network management objects 43
6.5.1 Module control services 43
6.5.2 Error control services 43
6.5.3 Bootup service 43
6.5.4 Node state diagram 43
6.6 Electronic data sheets 44
6.7 Device and application profiles 44
6.8 Object dictionary 45
6.9 Synchronous communications 45
6.10 COB-ID and NODE-ID assignment 45
7 Time distribution 47

7.1 Time objects 47
7.1.1 Time code formats 47
7.1.2 Spacecraft elapsed time objects 48
7.1.3 Spacecraft universal time coordinated objects 48
7.2 Time distribution and synchronization protocols 49
7.2.1 General 49
7.2.2 Time distribution protocol 49
7.2.3 High-resolution time distribution protocol 50

8 Redundancy management 52
8.1 General 52
8.2 Node internal bus redundancy architectures 52
8.2.1 General 52
8.2.2 Parallel bus access architecture 52
8.2.3 Selective bus access architecture 52
8.3 Bus monitoring and reconfiguration management 53
8.3.1 Bus redundancy management parameters 53
8.3.2 Start-up procedure 56
8.3.3 Bus monitoring protocol 57

9 Minimal implementation of the CANopen protocol for highly asymmetrical control applications 60
9.1 COB-ID assignment 60
9.2 Object dictionary 60
9.3 Minimal set CANopen Objects 60
9.4 Minimal Set Protocol 61
9.4.1 Definitions 61
9.4.2 Use of data bytes in application layer 62
9.4.3 Minimal Set Protocol data transmission 63
9.4.4 PDO transmit triggered by telemetry request 64
9.4.5 PDO mapping 64
9.4.6 Network management objects 65
9.4.7 Special function objects 65
9.4.8 Communication error object 66
9.4.9 NMT error control objects 66
9.4.10 Miscellaneous authorized objects 66
9.5 Free COB–ID 70

10 Connectors and pin assignments 73

10.1 Overview 73
10.2 Naming convention 73
10.3 Circular connectors 73
10.3.1 MIL-C D38999 configuration B: Dual CAN Network 73
10.3.2 MIL-C D38999 configuration D: Single CAN Network 74
10.4 Sub-miniature D connectors (9-pin D-sub) 75
10.5 Sub-miniature D connectors (9-pin D-sub) – RS-485 76

11 CANopen standard applicability matrix 77
11.1 Introduction 77

Annex A (informative) Electrical connectivity 88
A.1 Transceivers 88
A.1.2 Detailed implementation for RS-485 transceiver 88
A.2 Example Implementation of a RS-485 physical layer 90
A.3 CAN Network Bus termination 93
A.4 Bus management and redundancy 93
A.4.1 Selective bus access architecture 93
A.4.2 Parallel bus access architecture 94

Bibliography 95

Figures

Figure 3-1: Bit numbering convention 17
Figure 4-1: Relationship between ISO layering, ISO 11898, CiA 301 and ECSS CAN standard definitions 20
Figure 4-2: Example of minimal implementation topology 21
Figure 4-3: Format of hearthbeat message 26
Figure 5-1: Linear multi-drop topology 28
Figure 5-2: Daisy chain topology. 29
Figure 7-1: Format for objects containing the SCET 48
Figure 7-2: Format for objects containing the Spacecraft UTC 49
Figure 8-1: Node start up procedure 56
Figure 8-2: Bus monitoring logic 58
Figure 8-3: Slave bus selection process, toggling mechanism 59
Figure 9-1: Unconfirmed Command exchange overview (example with PDO1) 61
Figure 9-2: Telemetry request exchange overview (example with PDO2) 62
Figure 10-1: Illustration of a 9-pin D-Sub connector 75
Figure A-1 : Principle of Isolated CAN Operation 88
Figure A-2 : RS-485 CAN physical interface for OBC/Bus Master 90

Figure A-3 : RS-485 CAN physical interface for nodes using single connector for redundant buses 91
Figure A-4 : RS-485 CAN physical interface nodes using dual connector for redundant buses 91
Figure A-5 : Split (left) and standard (right) Termination schemes. 93
Figure A-6 : Selective bus access architecture 94
Figure A-7 : Parallel bus access architecture....94

Tables

Table 5-1: CAN levels in ISO 11898-2:2003 33
Table 5-2 – CAN failure modes and recommended FDIR actions. 36
Table 8-1: BUS redundancy management parameters for slaves 54
Table 8-2: BUS redundancy management parameters for master 55
Table 9-1: Peer-to-Peer objects of the minimal set 61
Table 9-2: Broadcast objects of the minimal set 61
Table 9-3: PDO Communication Object description: 63
Table 9-4: PDO Communication Entry Description: 63
Table 9-5 PDO Communication Object description: 64
Table 9-6: PDO Communication Entry Description: 64
Table 9-7 : SYNC Message Object description: 65
Table 9-8: SYNC Message Entry Description: 65
Table 9-9 SYNC used with NMT master Object description: 66
Table 9-10 SYNC used with NMT master Entry Description: 66
Table 9-11: CANopen Object dictionary Data Types 67
Table 9-12: Authorized and Forbidden Object Dictionary Entries of the Communication profile 68
Table 9-13 : COB ID -Predefined connection set 71
Table 10-1 : Signal terminology 73
Table 10-2: Pin function for MIL-C D38999 configuration B 74
Table 10-3: Pin function for MIL-C D38999 configuration D 74
Table 10-4: Pin function for sub D-type with CAN Network 75
Table 10-5: Pin function for sub D-type with RS-485 CAN Network 76
Table 11-1: DiA 301 (former CIA DS301) applicability matrix 78
Table A-1 : Logic Table, RS-485 Driver implementation 92
Table A-2 : Logic Table, RS-485 Receiver implementation 92
Table A-3 : Component item values 92