ISO 5884:2018 (E)

Aerospace series — Fluid systems and components — Methods for system sampling and measuring the solid particle contamination in hydraulic fluids

Contents

Foreword

0 Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Sampling apparatus

- 4.1 General
- 4.2 Sampling apparatus characteristics
- 4.2.1 Manual sampling apparatus
- 4.2.1.1 General
- 4.2.1.2 Sample bottles
- 4.2.1.3 Sample tubing
- 4.2.2 Automated sampling apparatus
- 4.2.2.1 General
- 4.2.2.2 Field monitors
- 4.2.2.3 Laser particle counter systems
- 4.2.2.4 Portable mesh blockage monitors
- 4.3 Sample apparatus preparation
- 4.3.1 General
- 4.3.2 Solvents
- 4.3.2.1 General
- 4.3.2.2 Solvent pressure filtration (preferred method)
- 4.3.2.2.1 Apparatus
- 4.3.2.2.2 Procedure
- 4.3.2.3 Solvent vacuum filtration
- 4.3.2.3.1 Apparatus
- 4.3.2.3.2 Procedure
- 4.3.3 Cleaning procedure for sampling apparatus
- 4.3.4 Cleaning procedure for sample bottles
- 4.3.5 Checking and controlling cleaning methods

5 Sampling

- 5.1 General
- 5.2 Recommendations for sampling point location
- 5.3 Sampling frequency
- 5.4 Sampling methods
- 5.4.1 General
- 5.4.2 Sampling method A — Field monitor/PCM system
- 5.4.3 Sampling method B — Sampling valve (using sample bottles)
- 5.4.4 Sampling method C — Reservoir sampling with vacuum pump and tubing
- 5.4.5 Sampling method D — Reservoir sampling with direct bottle dipping
- 5.5 Sample marking

6 Sample analysis methods

7 Test reporting

- 7.1 General
- 7.2 Test report form

7.3 Minimum data to be included in the test report form
7.4 Example test report

Annex A (informative) Example test report template

Page count: 13