DIN EN 16602-70-38:2019-11 (E)

Space product assurance - High-reliability soldering for surface-mount and mixed technology; English version EN 16602-70-38:2019

Table of contents

European Foreword 11

Introduction 12

1 Scope 15

2 Normative references 16

3 Terms, definitions and abbreviated terms 18

3.1 Terms from other standards 18

3.2 Terms specific to the present standard 18

3.3 Abbreviated terms 20

3.4 Nomenclature 21

3.4.1 Formal verbs 21

4 Principles of reliable soldered connections 22

5 Process identification document (PID) 23

5.1 General 23

5.1.1 Purpose 23

5.1.2 Document preparation 23

5.1.3 <<deleted>> 23

5.1.4 Approval 23

5.1.5 SMT contact person 24

5.2 <<deleted>> 24

5.3 Process identification document updating 24

6 Preparatory conditions 25

6.1 Calibration 25

6.2 Facility cleanliness 25

6.3 Environmental conditions 25

6.4 Precautions against static charges 25

6.5 Lighting requirements 25

6.6 Equipment and tools 25

6.6.1 Brushes 25

6.6.2 Cutters and Pliers 26
6.6.3 Bending tools 26
6.6.4 Clinching tools....26
6.6.5 Insulation strippers....26
6.6.6 Soldering tools 26
6.6.7 Soldering irons and resistance soldering equipment 26
6.6.8 <<deleted>>....26
6.6.9 Solder baths for degolding and pretinning 26
6.7 Soldering machines and equipment....27
6.7.1 General....27
6.7.2 Dynamic wave-solder machines....27
6.7.3 Condensation (vapour phase) reflow machines....28
6.7.4 Hot gas reflow machines....28
6.7.5 <<deleted>>....28
6.7.6 Convection and radiation reflow systems 28
6.7.7 Other equipment for reflow soldering 29
6.8 Ancillary equipment 29
6.8.1 General....29
6.8.2 Solder deposition equipment....29
6.8.3 Automatic device placement equipment....29
6.8.4 <<deleted>>....29
6.8.5 Cleanliness testing equipment 30
6.8.6 Magnification aids 30
6.8.7 X-ray inspection equipment....30
6.8.8 Metallographic equipment 30
7 Material selection 31
7.1 General....31
7.2 Solder....31
7.2.1 Form 31
7.2.2 Composition....31
7.2.3 Solder paste....31
7.2.4 Maintenance of paste purity 33
7.3 Flux 33
7.3.1 Rosin based flux 33
7.3.2 Corrosive acid flux....33
7.3.3 Flux controls for wave-soldering equipment 33
7.4 Solvents....33

7.5 Flexible insulation materials 34
7.6 Terminals 34
7.7 Wires 34
7.8 Printed circuit substrates 34
7.8.1 <<deleted>> 34
7.8.2 <<deleted>> 34
7.8.3 <<deleted>> 34
7.8.4 <<deleted>> 34
7.8.5 <<deleted>> 35
7.8.6 <<deleted>> 35
7.9 Devices 35
7.9.1 General 35
7.9.2 <<deleted>> 36
7.9.3 Moisture sensitive devices 36
7.9.4 <<deleted>> 36
7.10 Adhesives, encapsulants and conformal coatings 36

8 Preparation for soldering 38
8.1 Preparation of devices and terminals 38
8.1.1 Preparation of wires and terminals 38
8.1.2 Preparation of surfaces to be soldered 38
8.1.3 Degolding and pretinning of conductors 38
8.1.4 Alloying of pure tin finish 38
8.2 Preparation of solder bit 39
8.3 Handling 39
8.4 Storage 39
8.5 Baking of PCBs and moisture sensitive devices 39

9 Mounting of devices prior to soldering 40
9.1 General requirements 40
9.2 Lead bending and cutting requirements 40
9.3 Mounting of terminals to PCBs 40
9.4 Lead attachment to through holes 40
9.5 Mounting of devices to terminals 40
9.6 Mounting of through hole connectors to PCBs 40
9.7 Surface mount requirements 41
9.7.1 General 41
9.7.2 Stress relief 41
9.7.3 Registration of devices and footprints 42

9.7.4 Lead forming 42
9.7.5 Mounting devices in solder paste 42
9.7.6 Leadless devices 43
9.7.7 Leaded devices 43
9.7.8 <<deleted>> 43
9.7.9 Stacking and bonding of heavy devices 43

10 Attachment of conductors to terminals, solder cups and cables 45

11 Soldering to printed circuit boards 46

11.1 General 46
11.2 <<deleted>> 46
11.3 Solder applications to PCBs 46
11.4 Wicking 46
11.5 Soldering of SMDs 46
11.5.1 General requirements 46
11.5.2 End-capped and end-metallized devices 47
11.5.3 Bottom terminated chip devices 49
11.5.4 Cylindrical and square end-capped devices 50
11.5.5 Castellated chip carrier devices 52
11.5.6 Flat pack and Gull-wing leaded devices with round, rectangular, ribbon leads 53
11.5.7 Devices with “J” leads 54
11.5.8 Area array devices 54
11.5.9 Devices with ribbon terminals without stress relief 56
11.5.10 L-Shape inwards devices 57
11.5.11 Stacked modules devices with leads protruding vertically from bottom 58
11.5.12 Leaded device with plane termination 59
11.5.13 Moulded magnetics 59
11.6 <<deleted>> 60
11.7 <<deleted>> 60
11.8 <<deleted>> 60

12 Cleaning of PCB assemblies 61

12.1 General 61
12.2 Ultrasonic cleaning 61
12.3 Monitoring for cleanliness 61

13 Final inspection 62

13.1 General 62

13.2 Acceptance criteria 62
13.3 Visual rejection criteria 63
13.4 X-ray rejection criterion 65
13.5 Warp and twist of populated boards 65
13.6 Inspection records 65

14 Verification procedure 66

14.1 General 66
14.2 Verification by similarity 68
14.2.1 General 68
14.2.2 Conditions for similarity 69
14.3 Verification programme 71
14.4 Electrical testing of devices 75
14.4.1 General 75
14.5 Vibration and shock 78
14.6 Temperature cycling test 78
14.7 Microsection 79
14.7.1 Microsection facilities 79
14.7.2 Microsectioning 79
14.8 <<deleted>> 95
14.9 Special verification testing for hermetic ceramic area array packages 95
14.9.1 <<deleted>> 95
14.9.2 <<deleted>> 95
14.9.3 General 95
14.9.4 Evaluation of capability samples 98
14.9.5 Verification 98
14.10 Verification acceptance and rejection criteria 99
14.11 Approval of verification 108
14.12 Withdrawal of approval status 108
14.13 Conditions for delta verification 108
14.14 Verification of cleanliness 111
14.15 Verification approval procedure 111
14.15.1 Request for verification 111
14.15.2 Technology sample 111
14.15.3 Audit of assembly processing 111
14.15.4 Verification programme 112
14.15.5 Final verification review 112
14.15.6 Certification approval of assembly line 112

15 Quality assurance 113
15.1 General 113
15.2 Data 113
15.3 Nonconformance 113
15.4 Calibration 113
15.5 Traceability 113
15.6 Workmanship standards 113
15.7 Inspection 114
15.8 Operator and inspector training and certification 114
15.9 Quality records 114

16 <<deleted and moved into clause 14.7.2 and Annex I>> 115

Annex A (informative) <<deleted>> 116

Annex B (informative) <<deleted, SMT summary table DRD created in Annex H>> 117

Annex C (informative) <<deleted>> 118

Annex D (informative) Example of an SMT audit report 119

Annex E (informative) Additional information 128
E.1 <<deleted>> 128
E.2 Melting temperatures and choice 128

Annex F (normative) Process Identification Document (PID) - DRD 129
F.1 DRD identification 129
F.1.1 Requirement identification and source document 129
F.1.2 Purpose and objective 129
F.2 Expected response 129
F.2.1 Scope and content 129
F.2.2 Special remarks 131

Annex G (normative) Verification programme report - DRD 132
G.1 DRD identification 132
G.1.1 Requirement identification and source document 132
G.1.2 Purpose and objective 132
G.2 Expected response 132
G.2.1 Scope and content 132
G.2.2 Special remarks 133

Annex H (normative) SMT summary table - DRD 134

H.1 DRD identification 134
H.1.1 Requirement identification and source document 134
H.1.2 Purpose and objective 134
H.2 Expected response 134
H.2.1 Scope and content 134
H.2.2 Special remarks 134

Annex I (informative) Visual and X-ray workmanship standards 136

I.1 Workmanship illustrations for standard SMDs 136
I.1.1 Chip components 136
I.1.2 MELF components 139
I.1.3 Gull-wing leaded devices with round, rectangular, ribbon shape 140
I.1.4 “J” leaded devices 142
I.1.5 L-shape Inward leaded component 144
I.1.6 LCC devices 144
I.1.7 Miscellaneous soldering defects 145
I.2 Workmanship illustrations for ball grid array devices 146
I.3 Workmanship illustrations for column grid array devices 148

Bibliography 151

Figures

Figure 9-1: Exposed element 43
Figure 11-1: Mounting of rectangular and square end-capped and end-metallized devices 48
Figure 11-2: Mounting of bottom terminated chip devices 49
Figure 11-3: Mounting of cylindrical end-capped devices 50
Figure 11-4: Mounting of square end-capped devices 51
Figure 11-5: Mounting of castellated chip carrier devices 52
Figure 11-6: Mounting of gull-wing leaded devices with round, rectangular, ribbon leads 53
Figure 11-7: Mounting of devices with “J” leads 54
Figure 11-8: <<deleted>> 55
Figure 11-9: Typical ceramic area array showing ball grid array configuration on left and column grid array on right (CBGA & CCGA) 55
Figure 11-10: Typical assembled CCGA device 55
Figure 11-11: Mounting of devices without stress relief 56
Figure 11-12: Mounting of devices with “L-shape inwards” leads (1 = Toe, 2 = Heel) 57
Figure 11-13: Mounting of stacked modules devices with leads protruding vertically from bottom 58

Figure 11-14: Mounting of leaded devices with leads with plane termination 59
Figure 11-15: <<deleted>> 60
Figure 14-1: Verification programme flow chart (standard flow) 74
Figure 14-2: Verification programme flow chart (electrical testing) 77
Figure 14-3: Verification programme flow chart (AAD) 97
Figure 14-4: <<deleted>> 100

Figure I-1 : Preferred solder (see also Table 11-1) 136
Figure I-2 : Acceptable, maximum solder (see also Table 11-1) 136
Figure I-3 : Acceptable, minimum Solder (see also Table 11-1) 137
Figure I-4 : Unacceptable, excessive solder (see also Table 11-1) 137
Figure I-5 : Unacceptable, poor wetting (see also Table 11-1) 137
Figure I-6 : Unacceptable, excessive tilt (see also Table 11-1) 138
Figure I-7 : Unacceptable, tombstone effect 138
Figure I-8 : Examples of Unacceptable solder joints - (see also Table 11-1) 138
Figure I-9 : Acceptable, terminal wetted along end, face and sides (see also Table 11-1) 139
Figure I-10 : Acceptable, maximum solder joint (see also Table 11-3) 139
Figure I-11 : Not Acceptable, insufficient solder joint (see also Table 11-3) 139
Figure I-12 : Unacceptable overhang 139
Figure I-13 : Examples of Gullwing leads: Acceptable 140
Figure I-14 : Examples of gull-wing device with rectangular lead: Acceptable 140
Figure I-15 : Acceptable, minimum solder joint 140
Figure I-16 : Unacceptable, insufficient heel fillet 141
Figure I-17 : Unacceptable, excessive solder 141
Figure I-18 : Unacceptable, excessive solder 141
Figure I-19 : Preferred solder joint 142
Figure I-20 : Acceptable solder joint 142
Figure I-21 : Unacceptable, excessive solder joint 143
Figure I-22 : Unacceptable, excessive degolding 143
Figure I-23 : Acceptable, preferred solder joint 144
Figure I-24 : LCC General view, acceptable solder joints 144
Figure I-25 : Examples of unacceptable soldering 145
Figure I-26 : Angled-transmission X-radiograph showing solder paste shadow due to partial reflow: Reject 146
Figure I-27 : Micrograph showing 146
Figure I-28 : Perpendicular transmission X-radiograph showing unacceptable defects 147
Figure I-29 : Perpendicular transmission X-radiograph showing non-wetted footprint 147
Figure I-30 : Underside view showing missing column 148

Figure I-31 : CGA mounted on PCB showing columns tilted < 10°: Accept 148
Figure I-32 : X-radiograph of CGA mounted on PCB showing solder bridge: Reject 149
Figure I-33 : X-radiograph of CGA showing solder fillets at base of columns: acceptable ... 149
Figure I-34 : Micrograph of CGA mounted on PCB, bent column: reject 150
Figure I-35 : Micrograph of CGA mounted on PCB 150

Tables

Table 7-1: Chemical composition of spacecraft solders 32
Table 7-2: <<deleted>> 34
Table 11-1: Dimensional and solder fillet for rectangular and square end capped devices 48
Table 11-2: Dimensional and solder fillet for bottom terminated chip devices 49
Table 11-3: Dimensional and solder fillet for cylindrical end-capped devices 50
Table 11-4: Dimensional and solder fillet for square end-capped devices 51
Table 11-5: Dimensional and solder fillet for castellated chip carrier devices 52
Table 11-6: Dimensional and solder fillet for gull-wing leaded devices with round, rectangular, ribbon leads 53
Table 11-7: Dimensional and solder fillet for devices with “J” leads 54
Table 11-8: Dimensional and solder fillet for area array devices 55
Table 11-9: Dimensional and solder fillet for devices without stress relief 56
Table 11-10: Dimensional and solder fillet for “L-shape inwards” devices 57
Table 11-11: Dimensional and solder fillet for stacked modules devices with leads protruding vertically from bottom 58
Table 11-12: Dimensional and solder fillet for leaded devices with plane termination 59
Table 14-1: Device type classification 68
Table 14-2: Device microsection location 81
Table 14-3: Critical zone definition per device type and acceptance criteria 101
Table 14-4: Conditions invoking verification 110

Table E-1 : Guide for choice of solder type 128
Table H-1 : Device type preparation and mounting configuration 135