

ISO 12334:2000-02 (E)

Aerospace - Hydraulic, pressure-compensated, variable delivery pumps - General requirements for 35000 kPa systems

| Contents | | Page |
|-----------------|-----------------------------------------|-------------|
| Foreword | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Functional requirements | 2 |
| 3.1 | Hydraulic fluid | 2 |
| 3.2 | Rated discharge pressure | 2 |
| 3.3 | Maximum full-flow pressure | 3 |
| 3.4 | Inlet pressure | 3 |
| 3.4.1 | Rated inlet pressure | 3 |
| 3.4.2 | Cavitation pressure | 3 |
| 3.4.3 | Minimum inlet pressure | 3 |
| 3.5 | Case drain pressure | 3 |
| 3.5.1 | Rated case-drain pressure | 3 |
| 3.5.2 | Case proof-pressure | 3 |
| 3.6 | Case drain flow | 3 |
| 3.7 | Rated temperature | 4 |
| 3.8 | Maximum displacement | 4 |
| 3.9 | Rated delivery | 4 |
| 3.10 | Rated speed | 4 |
| 3.11 | Endurance | 6 |
| 3.12 | Torque | 6 |
| 3.13 | Efficiency | 6 |
| 3.14 | Discharge pressure pulsations | 6 |
| 3.15 | Variable delivery control | 6 |
| 3.15.1 | General | 6 |
| 3.15.2 | Response time | 7 |
| 3.15.3 | Stability | 7 |
| 3.16 | Maximum transient pressure | 8 |
| 3.17 | Depressurization | 8 |
| 3.18 | Balance | 8 |
| 3.19 | Adjustment | 9 |
| 3.20 | Safety wire sealing | 9 |
| 3.21 | Directionally critical components | 9 |
| 3.22 | Environmental requirements | 9 |
| 3.23 | Installation requirements | 9 |
| 3.23.1 | Dimensions | 9 |
| 3.23.2 | Mass | 10 |
| 3.23.3 | Mounting | 10 |
| 3.23.4 | Drive coupling | 10 |
| 3.23.5 | Ports | 10 |
| 3.24 | Detail requirements | 11 |
| 3.24.1 | Material | 11 |
| 3.24.2 | Metals | 11 |
| 3.24.3 | Corrosion protection | 11 |
| 3.24.4 | Castings | 12 |
| 3.24.5 | Seals | 12 |
| 3.24.6 | Identification marking | 12 |
| 3.24.7 | Design and construction | 13 |

| | | |
|---------|--------------------------------------------------------------------|----|
| 3.25 | Maintainability | 13 |
| 3.25.1 | Maintenance concept | 13 |
| 3.25.2 | Useful life and storage conditions | 13 |
| 3.26 | Reliability | 13 |
| 3.26.1 | Equipment compliance | 13 |
| 3.26.2 | Requirements | 13 |
| 4 | Quality assurance provisions | 14 |
| 4.1 | Responsibility for inspection | 14 |
| 4.2 | Classification of tests | 14 |
| 5 | Qualification tests | 14 |
| 5.1 | General | 14 |
| 5.2 | Qualification procedure | 14 |
| 5.2.1 | Detail specification | 14 |
| 5.2.2 | Qualification by analogy | 14 |
| 5.2.3 | Pump qualification test report | 14 |
| 5.3 | Samples and programme of qualification tests | 15 |
| 5.4 | General conditions for qualification tests | 15 |
| 5.5 | Acceptance tests | 16 |
| 5.6 | Dimensional check | 16 |
| 5.7 | Proof-pressure and overspeed test | 16 |
| 5.8 | Calibration | 16 |
| 5.8.1 | Pump inlet pressurized | 16 |
| 5.8.2 | Flow rate and driving torque values | 16 |
| 5.8.3 | Minimum operating speed | 16 |
| 5.9 | Maximum pressure, response time and pressure pulsation tests | 16 |
| 5.9.1 | General | 16 |
| 5.9.2 | System impedance | 17 |
| 5.9.3 | Maximum pressure test | 17 |
| 5.9.4 | Determination of response time | 17 |
| 5.9.5 | Pressure pulsation test | 18 |
| 5.10 | Heat rejection test | 18 |
| 5.10.1 | Principle | 18 |
| 5.10.2 | Determination of heat rejection | 18 |
| 5.11 | Vibration tests | 18 |
| 5.11.1 | Mounting of the test pump | 18 |
| 5.11.2 | Pump operating during vibration tests | 19 |
| 5.11.3 | Resonant frequency vibration test | 19 |
| 5.11.4 | Cyclic frequency vibration test | 19 |
| 5.11.5 | Other vibration tests | 19 |
| 5.12 | Low temperature test | 19 |
| 5.13 | Endurance testing | 20 |
| 5.13.1 | Test programme | 20 |
| 5.13.2 | Filtration for normal endurance tests | 20 |
| 5.13.3 | Filter check | 20 |
| 5.13.4 | Calibration | 20 |
| 5.13.5 | Start-stop cycles | 20 |
| 5.13.6 | Pump case pressure cycles | 23 |
| 5.13.7 | Air ingestion | 23 |
| 5.13.8 | Thermal cycles | 23 |
| 5.13.9 | Thermal shock | 24 |
| 5.13.10 | Hydraulic fluid | 24 |
| 5.13.11 | Failure of parts | 24 |
| 5.14 | Cavitation test | 24 |
| 5.15 | Drive coupling shear test | 24 |
| 5.16 | Teardown inspection | 24 |
| 6 | Acceptance tests | 25 |
| 6.1 | General | 25 |
| 6.2 | Examination of the product | 25 |
| 6.3 | Test programme | 25 |

| | | |
|-------|------------------------------------------|----|
| 6.3.1 | Break-in run | 25 |
| 6.3.2 | Proof-pressure and overspeed tests | 25 |
| 6.3.3 | Teardown inspection examination | 26 |
| 6.3.4 | Break-in run | 26 |
| 6.3.5 | Functional tests | 26 |
| 6.3.6 | External leakage test | 26 |
| 6.3.7 | Pressure control test | 27 |
| 6.3.8 | Calibration | 27 |
| 6.3.9 | Filter patch test | 27 |
| 7 | Storage and packaging | 28 |