DIN EN 16603-20-06:2020-11 (E)

Space engineering - Spacecraft charging; English version EN 16603-20-06:2020

Table of contents

European Forword 9

Introduction 11

1 Scope 13

2 Normative references 14

3 Terms, definitions and abbreviated terms 15

3.1 Terms defined in other standards 15

3.2 Terms specific to the present standard 15

3.3 Abbreviated terms 18

3.4 Nomenclature 19

4 Overview 21

4.1 Plasma interaction effects 21

4.1.1 Presentation 21

4.1.2 Most common engineering concerns 21

4.1.3 Overview of physical mechanisms 22

4.2 Relationship with other standards 24

5 Protection programme 26

6 Surface material requirements 27

6.1 Overview 27

6.1.1 Description and applicability 27

6.1.2 Purpose common to all spacecraft 28

6.1.3 A special case: scientific spacecraft with plasma measurement instruments 28

6.2 General requirements 28

6.2.1 Maximum permitted voltage 28

6.2.2 Maximum resistivity 29

6.3 Electrical continuity, including surfaces and structural and mechanical parts 29

6.3.1 Grounding of surface metallic parts 29

6.3.2 Exceptions 30

6.3.3 Electrical continuity for surface materials 31
6.4 Surface charging analysis 35
6.5 Deliberate potentials 35
6.6 Testing of materials and assemblies 35
6.6.1 General 35
6.6.2 Material characterization tests 37
6.6.3 Material and assembly qualification 37
6.7 Scientific spacecraft with plasma measurement instruments 38
6.8 Verification 38
6.8.1 Grounding 38
6.8.2 Material selection 39
6.8.3 Environmental effects 39
6.8.4 Computer modelling 39
6.9 Triggering of ESD 40

7 Secondary arc requirements 41
7.1 Description and applicability 41
7.2 Solar arrays 42
7.2.1 Overview 42
7.2.2 General requirement 42
7.2.3 Testing of solar arrays 43
7.3 Other exposed parts of the power system including solar array drive mechanisms 47

8 High voltage system requirements 48
8.1 Description 48
8.2 Requirements 48
8.3 Validation 48

9 Internal parts and materials requirements 49
9.1 Description 49
9.2 General 49
9.2.1 Internal charging and discharge effects 49
9.2.2 Grounding and connectivity 49
9.2.3 Dielectric electric fields and voltages 50
9.3 Validation 51

10 Tether requirements 55
10.1 Description 55
10.2 General 55

10.2.1 Hazards arising on tethered spacecraft due to voltages generated by conductive tethers 55
10.2.2 Current collection and resulting problems 55
10.2.3 Hazards arising from high currents flowing through the tether and spacecraft structures 56
10.2.4 Continuity of insulation. 56
10.2.5 Hazards from undesired conductive paths 56
10.2.6 Hazards from electro-dynamic tether oscillations 56
10.2.7 Other effects 56
10.3 Validation 57

11 Electric propulsion requirements 58
11.1 Overview 58
11.1.1 Description 58
11.1.2 Coverage of the requirements 58
11.2 General 60
11.2.1 Spacecraft neutralization 60
11.2.2 Beam neutralization 61
11.2.3 Contamination 62
11.2.4 Sputtering 62
11.2.5 Neutral gas effects 62
11.3 Validation 63
11.3.1 Ground testing 63
11.3.2 Computer modelling characteristics 63
11.3.3 In-flight monitoring 63
11.3.4 Sputtering 63
11.3.5 Neutral gas effects 64

Annex A (normative) Electrical hazard mitigation plan - DRD 65
A.1 DRD identification 65
A.1.1 Requirement identification and source document 65
A.1.2 Purpose and objective 65
A.2 Expected response 65
A.2.1 Scope and content 65
A.2.2 Special remarks 66

Annex B (informative) Tailoring guidelines 67
B.1 Overview 67
B.2 LEO 67
B.2.1 General 67

B.2.2 LEO orbits with high inclination 68
B.3 MEO and GEO orbits 68
B.4 Spacecraft with onboard plasma detectors 68
B.5 Tethered spacecraft 69
B.6 Active spacecraft 69
B.7 Solar Wind 69
B.8 Other planetary magnetospheres 69

Annex C (informative) Physical background to the requirements 70

C.1 Introduction 70
C.2 Definition of symbols 70
C.3 Electrostatic sheaths 70
C.3.1 Introduction 70
C.3.2 The electrostatic potential 71
C.3.3 The Debye length 71
C.3.4 Presheath 72
C.3.5 Models of current through the sheath 73
C.3.6 Thin sheath – space-charge-limited model 73
C.3.7 Thick sheath – orbit motion limited (OML) model 74
C.3.8 General case 75
C.3.9 Magnetic field modification of charging currents 75
C.4 Current collection and grounding to the plasma 75
C.5 External surface charging 76
C.5.1 Definition 76
C.5.2 Processes 76
C.5.3 Effects 77
C.5.4 Surface emission processes 77
C.5.5 Floating potential 78
C.5.6 Conductivity and resistivity 79
C.5.7 Time scales 81
C.6 Spacecraft motion effects 81
C.6.1 Wakes 81
C.6.2 Motion across the magnetic field 84
C.7 Induced plasmas 85
C.7.1 Definition 85
C.7.2 Electric propulsion thrusters 86
C.7.3 Induced plasma characteristics 86
C.7.4 Charge-exchange effects 87

C.7.5 Neutral particle effects 88
C.7.6 Effect on floating potential 88
C.8 Internal and deep-dielectric charging 88
C.8.1 Definition 88
C.8.2 Relationship to surface charging 89
C.8.3 Charge deposition 90
C.8.4 Material conductivity 90
C.8.5 Time dependence 93
C.8.6 Geometric considerations 93
C.8.7 Isolated internal conductors 94
C.8.8 Electric field sensitive systems 94
C.9 Discharges and transients 95
C.9.1 General definition 95
C.9.2 Review of the process 95
C.9.3 Dielectric material discharge 96
C.9.4 Metallic discharge 98
C.9.5 Internal dielectric discharge 99
C.9.6 Secondary powered discharge 100
C.9.7 Discharge thresholds 100
Annex D (informative) Charging simulation 102
D.1 Surface charging codes 102
D.1.1 Introduction 102
D.2 Internal charging codes 104
D.2.1 DICTAT 104
D.2.2 ESADDC 104
D.2.3 GEANT-4 105
D.2.4 NOVICE 105
D.3 Environment model for internal charging 105
D.3.1 FLUMIC 105
D.3.2 Worst case GEO spectrum 105
Annex E (informative) Testing and measurement. 106
E.1 Definition of symbols 106
E.2 Solar array testing 106
E.2.1 Solar cell sample 106
E.2.2 Pre-testing of the solar array simulator (SAS) 107
E.2.3 Solar array test procedure 109
E.2.4 Other elements 113

E.2.5 The solar panel simulation device 114
E.3 Measurement of conductivity and resistivity 116
E.3.1 Determination of intrinsic bulk conductivity by direct measurement 116
E.3.2 Determination of radiation-induced conductivity coefficients by direct measurement 117
E.3.3 Determination of conductivity and radiation-induced conductivity by electron irradiation 118
E.3.4 The ASTM method for measurement of surface resistivity and its adaptation for space used materials 118

References 120

Bibliography 124

Figures

Figure 6-1: Applicability of electrical continuity requirements 32
Figure 7-1: Solar array test set-up 45
Figure C-1 : Schematic diagram of potential variation through sheath and pre-sheath. 72
Figure C-2 : Example secondary yield curve 78
Figure C-3 : Schematic diagram of wake structure around an object at relative motion with respect to a plasma 82
Figure C-4 : Schematic diagram of void region 83
Figure C-5 : Schematic diagram of internal charging in a planar dielectric 89
Figure C-6 : Dielectric discharge mechanism. 97
Figure C-7 :Shape of the current in relation to discharge starting point. 97
Figure C-8 : Example of discharge on pierced aluminized Teflon® irradiated by electrons with energies ranging from 0 to 220 keV. 98
Figure C-9 : Schematic diagram of discharge at a triple point in the inverted voltage gradient configuration with potential contours indicated by colour scale. 99
Figure E-1 : Photograph of solar cells sample – Front face & Rear face (Stentor Sample. Picture from Denis Payan - CNES®) 107
Figure E-2 : Schematic diagram of power supply test circuit 108
Figure E-3 : Example of a measured power source switch response 108
Figure E-4 : Example solar array simulator 109
Figure E-5 : Absolute capacitance of the satellite 110
Figure E-6 : Junction capacitance of a cell versus to voltage 112
Figure E-7 : The shortened solar array sample and the missing capacitances 113
Figure E-8 : Discharging circuit oscillations 114
Figure E-9 : Effect of an added resistance in the discharging circuit (SAS + resistance) 114
Figure E-10 : Setup simulating the satellite including flashover current 115

Figure E-11 : Basic arrangement of apparatus for measuring dielectric conductivity in planar samples 116
Figure E-12 : Arrangement for measuring cable dielectric conductivity and cross-section through co-axial cable 116
Figure E-13 : Arrangement for carrying out conductivity tests on planar samples under irradiation 118
Figure E-14 : Basic experimental set up for surface conductivity 119

Tables

Table 4-1: List of electrostatic and other plasma interaction effects on space systems 23
Table 7-1: Tested voltage-current combinations 42
Table 7-2: Typical inductance per unit length for cables 46
Table C-1 : Parameters in different regions in space 72
Table C-2 : Typical plasma parameters for LEO and GEO 83
Table C-3 : Plasma conditions on exit plane of several electric propulsion thrusters 87
Table C-4 : Emission versus backflow current magnitudes for several electric propulsion thrusters 87
Table C-5 : Value of Ea for several materials 91