

DIN EN 16603-50-11:2020-11 (E)

Space engineering - SpaceFibre - Very high-speed serial link; English version EN 16603-50-11:2020

Contents	Page
European Foreword	9
1 Scope	10
2 Normative references	11
3 Terms, definitions and abbreviated terms	13
3.1 Terms defined in other standards	13
3.2 Terms specific to the present standard	13
3.3 Abbreviated terms.....	26
3.4 Conventions.....	29
3.4.1 Numbers	29
3.4.2 Multiplication	29
3.4.3 Differential signals.....	29
3.4.4 Order of sending bits in symbols	29
3.4.5 Graphical representation of packets.....	30
3.4.6 State diagram notation	30
3.4.7 UML diagram notation.....	31
3.4.8 D/K notation for 8B/10B characters	32
3.5 Nomenclature	32
4 Principles	34
4.1 SpaceFibre purpose	34
4.2 SpaceFibre overview	35
5 Requirements	37
5.1 Overview	37
5.2 Protocol stack and interface architecture	37
5.2.1 General.....	37
5.2.2 Network layer	39
5.2.3 Data Link layer	39
5.2.4 Multi-Lane layer	40
5.2.5 Lane layer	40
5.2.6 Physical layer.....	41

5.2.7	Management Information Base	41
5.3	Formats	41
5.3.1	Control words and encoding/decoding	41
5.3.2	8B/10B encode/decode	42
5.3.3	Lane control words	44
5.3.4	Multi-Lane control words	51
5.3.5	Data Link control words	53
5.3.6	Receive error indication control word (RXERR)	62
5.3.7	Characters	63
5.3.8	Frames	66
5.3.9	Packets	70
5.3.10	Control word and frame precedence	70
5.3.11	K-code summary	73
5.3.12	Control word symbol summary	73
5.4	Physical layer	74
5.4.1	Physical layer responsibilities	74
5.4.2	Serialisation	75
5.4.3	Electrical physical layer	77
5.4.4	Electrical medium	88
5.4.5	Fibre optic physical layer	97
5.4.6	Fibre optic medium	103
5.5	Lane layer	112
5.5.1	Lane layer responsibilities	112
5.5.2	Lane initialisation and standby management	114
5.5.3	Data signalling rate compensation	126
5.5.4	IDLE words	126
5.5.5	Parallel loopback	127
5.5.6	Symbol synchronisation	127
5.5.7	Word synchronisation	127
5.5.8	Receive synchronisation state machine	129
5.6	Multi-Lane layer	131
5.6.1	Multi-Lane layer responsibilities	131
5.6.2	Multi-Lane link	132
5.6.3	Multi-Lane bypass	133
5.6.4	Multi-Lane distribution	133
5.6.5	Multi-Lane concentration	137
5.6.6	Lane Alignment	137

5.6.7	Alignment state diagram	141
5.6.8	Asymmetric links	144
5.6.9	Initialisation of unidirectional lanes	145
5.6.10	Hot redundant lanes.....	146
5.7	Data Link layer.....	149
5.7.1	Data Link layer responsibilities	149
5.7.2	Virtual channels	151
5.7.3	Flow control.....	153
5.7.4	Medium access controller.....	155
5.7.5	Broadcast flow control.....	163
5.7.6	Framing.....	164
5.7.7	Error recovery	177
5.7.8	Data word identification state machine	184
5.7.9	Link Reset state machine	189
5.7.10	Link reset	192
5.8	Network layer.....	194
5.8.1	Network layer responsibilities	194
5.8.2	SpaceFibre network	195
5.8.3	Virtual networks	196
5.8.4	Links	199
5.8.5	Packet format.....	199
5.8.6	Sending a packet	200
5.8.7	Receiving a packet.....	200
5.8.8	Routing switch.....	201
5.8.9	Packet addressing.....	207
5.8.10	Group adaptive routing.....	209
5.8.11	Packet multicast.....	209
5.8.12	Broadcast messages.....	210
5.8.13	SpaceFibre nodes	212
5.8.14	SpaceFibre units	213
5.9	Management Information Base	214
5.9.1	Management Information Base responsibilities	214
5.9.2	Network management	214
5.9.3	Configuration parameters.....	215
5.9.4	Status parameters.....	219
6	Service interfaces	221
6.1	Overview	221

6.2	Network layer service interface	221
6.2.1	Network layer services	221
6.2.2	Packet Transfer service	221
6.2.3	Broadcast message service	223
6.3	Data Link layer service interface	224
6.3.1	Data Link layer services	224
6.3.2	Virtual Channel service	224
6.3.3	Broadcast message service	225
6.3.4	Schedule synchronisation service	226
6.4	Physical layer service interfaces	227
6.4.1	Physical layer services	227
6.4.2	Transfer symbols service	227
6.4.3	Control service	228
6.5	Management Information Base service interface	230
6.5.1	Management Information Base services	230
6.5.2	Link Management service	230

Bibliography.....232

Figures

Figure 3-1: Convention for first bit to be sent	29
Figure 3-2: Graphical packet notation	30
Figure 3-3: State diagram style.....	30
Figure 3-4: UML notation.....	31
Figure 3-5: D/K notation for 8B/10B characters	32
Figure 4-1: Overview of SpaceFibre protocol stack	35
Figure 5-1: SpaceFibre protocol stack - single-lane.....	38
Figure 5-2: SpaceFibre protocol stack - multi-lane.....	39
Figure 5-3: Fills at the end of packets.....	65
Figure 5-4: Fills at the start and end of a packet.....	66
Figure 5-5: Data frame format for a single lane	66
Figure 5-6: Idle frame format	67
Figure 5-7: Broadcast frame format.....	68
Figure 5-8: Interfaces to the Physical layer	75
Figure 5-9: One direction of electrical Physical layer, showing series capacitors, discharge resistors, and different grounds.....	77
Figure 5-10: Serial output signals	79
Figure 5-11: Serial output test circuit.....	80

Figure 5-12: Serial eye pattern mask.....	80
Figure 5-13: Serial input signals	86
Figure 5-14: Type-A electrical flight cable assembly	89
Figure 5-15: Type-A electrical flight connector saver	90
Figure 5-16: Type-C electrical EGSE cable assembly	93
Figure 5-17: Type-C electrical EGSE to flight adaptor cable assembly	94
Figure 5-18: One direction of fibre optic Physical layer, showing fibre optic transmitter, receiver, connectors and cable.....	97
Figure 5-19: One direction of active optical cable type of fibre optic Physical layer.....	97
Figure 5-20: Electro-optical eye pattern for 1 Gbit/s to 5 Gbit/s transmitters	99
Figure 5-21: Electro-optical eye pattern for 1 Gbit/s to 10 Gbit/s transmitters	100
Figure 5-22: SpaceFibre lane comprising two Type-A fibre optic flight cable assemblies, one for each direction.....	105
Figure 5-23: Type-B fibre optic flight cable assembly with one lane.....	107
Figure 5-24: Type-B fibre optic flight cable assembly with several lanes	108
Figure 5-25: Type-B fibre optic flight cable assembly for an asymmetric link	108
Figure 5-26: Type-C flight active optical cable assembly	111
Figure 5-27: Interfaces to the Lane layer for a single lane link.....	113
Figure 5-28: Interfaces to the Lane layer for a multi-lane link.....	114
Figure 5-29: Lane initialisation state machine.....	115
Figure 5-30: Receive synchronisation state machine.....	129
Figure 5-31: Interfaces to Multi-Lane layer	132
Figure 5-32: Multi-Lane link with different number of lanes at each end	133
Figure 5-33: Words forming a row across a multi-lane link	134
Figure 5-34: Spreading data across a multi-lane link	135
Figure 5-35: PAD control words in a multi-lane link	135
Figure 5-36: Row alignment across a multi-lane link.....	140
Figure 5-37: Alignment state machine	141
Figure 5-38: Multi-Lane link incorporating some unidirectional lanes	144
Figure 5-39: Interfaces to the Data Link layer for a single lane link.....	150
Figure 5-40: Interfaces to the Data Link layer for a multi-lane link	150
Figure 5-41: Scrambler / de-scrambler	165
Figure 5-42: Example of scrambling of a short data frame.....	166
Figure 5-43: Effect of scrambling on an idle frame.....	167
Figure 5-44: Examples of CRC calculation for a short data frame	172
Figure 5-45: Illustration of bit ordering during 16-bit CRC calculation	172
Figure 5-46: Examples of CRC calculation for a broadcast frame and FCT.....	175
Figure 5-47: Illustration of bit ordering during 8-bit CRC calculation	176

Figure 5-48: Receive Error state machine	182
Figure 5-49: Data Word Identification state machine	185
Figure 5-50: Link Reset state machine	190
Figure 5-51: Interfaces to the Network layer	194
Figure 5-52: Components of a SpaceFibre network.....	195
Figure 5-53: Relationships of a SpaceFibre virtual network	197
Figure 5-54: SpaceFibre packet format	199
Figure 5-55: Components of a SpaceFibre routing switch	202
Figure 5-56: Components and specialisations of a SpaceFibre node	212
Figure 5-57: Components and specialisations of a SpaceFibre unit	214

Tables

Table 5-1: 5B/6B encoding	43
Table 5-2: 3B/4B encoding	44
Table 5-3: Lane control words	44
Table 5-4: Multi-Lane control words.....	51
Table 5-5: Data framing control words.....	53
Table 5-6: Flow control word	58
Table 5-7: Error recovery control words.....	60
Table 5-8: Receive error indication control word.....	63
Table 5-9: SpaceFibre N-Char Symbols	64
Table 5-10: Fill control character symbol	64
Table 5-11: Meaning of K-codes.....	73
Table 5-12: Meaning of control word symbols	73
Table 5-13: Serial output interface.....	77
Table 5-14: Serial eye pattern mask intervals 1 Gbit/s to 3,125 Gbit/s.....	81
Table 5-15: Serial eye pattern mask intervals above 3,125 Gbit/s to 6,25 Gbit/s	81
Table 5-16: Coefficient α for different values of BER	82
Table 5-17: Driver and receiver characteristics 1 Gbit/s to 3,125 Gbit/s.....	83
Table 5-18: Driver and receiver characteristics above 3,125 Gbit/s to 6,25 Gbit/s	84
Table 5-19: Serial input interface	85
Table 5-20: Type-A electrical flight cable assembly connector contact terminations	89
Table 5-21: Type-A electrical flight connector saver connector contact terminations	89
Table 5-22: Type-B electrical flight cable assembly connector contact terminations	92
Table 5-23: Type-C electrical EGSE cable assembly connector contact terminations	93
Table 5-24: Type-C electrical EGSE to flight adaptor cable assembly connector contact terminations	94
Table 5-25: Type-D electrical EGSE cable assembly connector contact terminations	96

Table 5-26: Electro-optical characteristics for 1 Gbit/s to 5 Gbit/s transmitters	100
Table 5-27: Electro-optical characteristics for 1 Gbit/s to 10 Gbit/s transmitters	101
Table 5-28: Electro-optical characteristics for 1 Gbit/s to 5 Gbit/s receivers.....	102
Table 5-29: Electro-optical characteristics for 1 Gbit/s to 10 Gbit/s receivers.....	103
Table 5-30: Connection of SpaceFibre lane using Type-A flight fibre optic cable assemblies	105
Table 5-31: Type-B flight fibre optic cable assembly connector contact terminations for each SpaceFibre lane	107
Table 5-32: Type-C flight active optical cable connector terminations for each SpaceFibre lane	109
Table 5-33: Type-C flight active optical cable assembly connector contact terminations for each SpaceFibre lane	110
Table 5-34: Precedence for different qualities of service	158
Table 5-35: Routing switch addresses	204
Table 5-36: SpaceFibre configuration parameters	216
Table 5-37: SpaceFibre status parameters.....	219