

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms, definitions and abbreviated terms
3.1	Term and definitions
3.2	Abbreviated terms
4	Overview
4.1	General
4.2	Battery capacity
4.3	Battery impedance
4.3.1	General
4.3.2	Electrochemical impedance spectroscopy (EIS)
4.4	Battery internal resistance
5	Specificities of spacecraft telemetry and resulting limitations
5.1	General
5.2	Signal digitization
5.3	Temperature
5.4	Voltage
5.5	Current
5.6	Sampling frequency
5.7	Synchronisation
5.8	On-board memory
6	Main methods for the evaluation of battery ageing parameters
6.1	Global method: fitting of a numerical model to in-flight data
6.1.1	General
6.1.2	Model structure
6.1.3	Data fitting
6.1.3.1	General
6.1.3.2	Simulation input
6.1.3.3	Initial conditioning
6.1.3.4	Available charge power
6.1.3.5	Weighting of an objective function
6.2	Evaluation of battery capacity
6.2.1	Direct method
6.2.2	Indirect method
6.3	Measurement of battery internal resistance
6.3.1	Direct internal resistance measurement
6.3.2	Indirect measurement of battery resistance
6.3.2.1	General
6.3.2.2	Constant current / constant voltage (CC/CV) charging phase processing
6.3.2.3	Round trip efficiency processing
6.3.3	Correlation of internal resistance to capacity
6.4	Measurement of battery spectral impedance
6.4.1	General
6.4.2	Time domain identification of a dynamic model

- 6.4.3 Derivation of impedance from frequency domain processing of transients
- 6.4.4 Derivation of impedance from frequency domain processing of disturbances
- 7 Recommendations for easing battery in-flight health assessment
  - 7.1 General recommendations
  - 7.2 Recommendations related to battery characterization prior to flight
  - 7.3 Recommendations related to spacecraft telemetry performance
  - 7.4 Recommendations related to spacecraft operations
  - 7.5 Recommendations related to data formatting
  - 7.6 Recommendations related to data processing

Page count: 54