

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Abbreviated terms |
| 5 | General requirements |
| 5.1 | General |
| 5.2 | Design requirements |
| 5.2.1 | Loads, pressures and environments |
| 5.2.2 | Strength |
| 5.2.3 | Stiffness |
| 5.2.4 | Thermal effects |
| 5.2.5 | Stress analysis |
| 5.2.6 | Fatigue analysis/damage tolerance (safe-life) analysis |
| 5.2.7 | Analysis of survivability against space debris and meteoroid impacts |
| 5.2.8 | Avoidance of accidental break-up caused by an on-board source of energy |
| 5.3 | Material requirements |
| 5.3.1 | Metallic materials |
| 5.3.1.1 | General |
| 5.3.1.2 | Metallic material selection |
| 5.3.1.3 | Metallic material evaluation |
| 5.3.1.4 | Metallic material characterization |
| 5.3.2 | Non-metallic material requirements |
| 5.4 | Fabrication and process requirements |
| 5.5 | Contamination control and cleanliness requirements |
| 5.5.1 | General contamination control requirements |
| 5.5.2 | Design considerations |
| 5.6 | Quality assurance programme requirements |
| 5.6.1 | General |
| 5.6.2 | QA programme inspection plan requirements |
| 5.6.3 | QA inspection technique requirements |
| 5.6.4 | QA inspection data requirements |
| 5.6.5 | Acceptance test requirements |
| 5.6.5.1 | General |
| 5.6.5.2 | Proof pressure test requirements |
| 5.6.5.3 | Leak test requirements |
| 5.7 | Qualification test requirements |
| 5.8 | Operation and maintenance requirements |
| 5.8.1 | Operating procedure |
| 5.8.2 | Safe operating limits |
| 5.8.3 | Inspection and maintenance |
| 5.8.4 | Repair and refurbishment |
| 5.8.5 | Storage |
| 5.8.6 | Documentation |
| 5.8.7 | Reactivation |
| 5.8.8 | Recertification |
| 5.8.8.1 | Requirements |
| 5.8.8.2 | Test after limited modification and repair |

| | |
|----------|--|
| 6 | General pressurized-system requirements |
| 6.1 | System analysis requirements |
| 6.1.1 | System pressure analysis |
| 6.1.2 | System functional analysis |
| 6.1.3 | System hazard analysis |
| 6.2 | Design features |
| 6.2.1 | Assembly |
| 6.2.2 | Routing |
| 6.2.3 | Separation |
| 6.2.4 | Shielding |
| 6.2.5 | Grounding |
| 6.2.6 | Handling |
| 6.2.7 | Special tools |
| 6.2.8 | Test points |
| 6.2.9 | Common-plug test connectors |
| 6.2.10 | Individual test connectors |
| 6.2.11 | Threaded parts |
| 6.2.12 | Friction-type locking devices |
| 6.2.13 | Internally threaded bosses |
| 6.2.14 | Retainer or snap rings |
| 6.2.15 | Snubbers |
| 6.3 | Component selection |
| 6.3.1 | Connections |
| 6.3.2 | Fluid temperature |
| 6.3.3 | Actuator pressure rating |
| 6.3.4 | Pressure rating |
| 6.3.5 | Pump selection |
| 6.3.6 | Fracture and leakage |
| 6.3.7 | Oxygen system components |
| 6.3.8 | Pressure regulators |
| 6.3.9 | Manual valves and regulators |
| 6.4 | Design pressures |
| 6.4.1 | Overpressure or underpressure |
| 6.4.2 | Back-pressure |
| 6.4.3 | Pressure isolation |
| 6.4.4 | Gas/fluid separation |
| 6.4.5 | Compressed-gas bleeding |
| 6.5 | Mechanical-environment design |
| 6.5.1 | Acceleration and shock loads |
| 6.5.2 | Torque loads |
| 6.5.3 | Vibration loads |
| 6.6 | Controls |
| 6.6.1 | Interlocks |
| 6.6.2 | Multiple safety-critical functions |
| 6.6.3 | Critical flows and pressures |
| 6.7 | Protection |
| 6.8 | Electrical |
| 6.8.1 | Hazardous atmospheres |
| 6.8.2 | Radio frequency energy |
| 6.8.3 | Grounding |
| 6.8.4 | Solenoids |
| 6.8.5 | Electric motor-driven pumps |
| 6.9 | Pressure relief |
| 6.9.1 | General requirements |
| 6.9.2 | Flow capacity |
| 6.9.3 | Sizing |
| 6.9.4 | Unmanned flight vehicle servicing |
| 6.9.5 | Automatic relief |
| 6.9.5.1 | Low safety factor |
| 6.9.5.2 | Confinement |
| 6.9.6 | Venting |
| 6.9.7 | Relief valve isolation |
| 6.9.8 | Negative-pressure protection |

- 6.9.8.1 Testing
 - 6.9.8.2 Storage and transportation
 - 6.9.9 Reservoir pressure relief
 - 6.9.10 Air pressure control
 - 6.10 Control devices
 - 6.10.1 Directional control valves
 - 6.10.2 Overtravel
 - 6.10.3 Pressure and volume control stops
 - 6.10.4 Manually operated levers
 - 6.11 Accumulators
 - 6.11.1 Accumulator design
 - 6.11.2 Accumulator gas pressure gauges
 - 6.11.3 Accumulator identification
 - 6.12 Flexible hose
 - 6.12.1 Installation
 - 6.12.2 Restraining devices
 - 6.12.3 Flexible hose stress
 - 6.12.4 Temporary installations
- 7 Specific pressure system requirements**
- 7.1 General
 - 7.2 Hydraulic systems
 - 7.2.1 Hydraulic system components
 - 7.2.1.1 Component selection and safety test
 - 7.2.1.2 Cycling
 - 7.2.1.3 Actuators
 - 7.2.1.4 Shutoff valves
 - 7.2.1.5 Variable response
 - 7.2.1.6 Fire-resistant fluids
 - 7.2.1.7 Accumulators
 - 7.2.1.8 Adjustable orifices
 - 7.2.1.9 Lock valves
 - 7.2.1.10 Hydraulic reservoir
 - 7.2.2 Pressure limit
 - 7.2.3 Cavitations
 - 7.2.3.1 Inlet pressure
 - 7.2.3.2 Fluid column
 - 7.2.4 Hydraulic lockup
 - 7.2.4.1 Emergency disengagement
 - 7.2.4.2 Emergency bypass
 - 7.2.5 Pressure relief
 - 7.2.5.1 Pump pressure relief
 - 7.2.5.2 Thermal pressure relief
 - 7.2.5.3 Location
 - 7.3 Pneumatic-system requirements
 - 7.3.1 Pneumatic-system components
 - 7.3.1.1 Component integrity
 - 7.3.1.2 Configuration
 - 7.3.1.3 Compressors
 - 7.3.1.4 Actuators
 - 7.3.1.5 Adjustable orifice restrictors
 - 7.3.2 Controls
- Annex A (informative) Recommended minimum safety factors**
- Annex B (informative) Open line force calculation factors**