

# DIN EN 16603-50-16:2022-08 (E)

## Space engineering - Time triggered Ethernet; English version EN 16603-50-16:2021

---

Contents	Page
<b>European Foreword.....</b>	<b>8</b>
<b>1 Scope.....</b>	<b>9</b>
<b>2 Normative references .....</b>	<b>10</b>
<b>3 Terms, definitions and abbreviated terms.....</b>	<b>11</b>
3.1 Terms from other standards.....	11
3.2 Terms specific to the present standard .....	11
3.3 Abbreviated terms.....	15
3.4 Nomenclature .....	17
<b>4 Overview.....</b>	<b>18</b>
4.1 Reference Model .....	18
4.2 Physical Layer .....	19
4.3 Data Link Layer .....	19
4.3.1 Data Link Layer Overview .....	19
4.3.2 Data Link Layer Functionalities .....	20
4.3.3 Time-Triggered Ethernet .....	21
4.4 Network Level.....	23
4.4.1 Network Level Overview.....	23
4.4.2 Message Processing at the Switch.....	24
4.4.3 Time-Triggered Ethernet Network Building Blocks .....	28
4.4.4 Virtual Link .....	29
4.4.5 Time-Triggered Traffic Policing .....	30
4.4.6 Rate-Constrained Traffic Policing.....	30
4.4.7 Clock Synchronization.....	31
4.5 Redundancy Concept .....	34
4.5.1 Introduction .....	34
4.5.2 TT traffic.....	35
4.5.3 RC traffic.....	35
4.6 Failure-modes.....	36
<b>5 Network Architecture .....</b>	<b>37</b>

5.1	Overview .....	37
5.1.1	Introduction .....	37
5.1.2	Single Channel Network Topology .....	37
5.1.3	Dual Channel Network Topology.....	38
5.1.4	Triple Channel Network Topology .....	39
5.1.5	Mixed Network Topology.....	40
5.1.6	Multiple Networks Topology .....	41
5.1.7	Compatibility with standard Ethernet Network .....	42
5.2	Network Topology Requirements.....	43
5.2.1	Single Network Topology .....	43
5.2.2	Multiple Networks Topology .....	45
<b>6</b>	<b>Device Services .....</b>	<b>46</b>
6.1	Overview .....	46
6.2	Media Access Control (MAC) Sublayer.....	47
6.2.1	MAC sublayer functions .....	47
6.2.2	MAC Addressing .....	47
6.2.3	Traffic Classes .....	48
6.2.4	MAC Transmit.....	49
6.2.5	MAC Receive .....	50
6.2.6	Switch Traffic Policing .....	50
6.2.7	Switch Transmit .....	51
6.2.8	Switch Frame Routing.....	52
<b>7</b>	<b>Interoperability Specification .....</b>	<b>53</b>
7.1	Overview .....	53
7.2	Device Specification .....	54
7.2.1	Device Parameters Description .....	54
7.2.2	General Requirements .....	55
7.2.3	Switch Level Specification.....	55
7.2.4	End-System Level Specification .....	59
7.2.5	Clock Synchronization.....	60
7.3	Configuration Parameters .....	61
7.3.1	Device Level and Clock Synchronization Parameters .....	61
7.4	Configuration and Scheduling guideline .....	67
7.4.1	Overview.....	67
7.4.2	Delays.....	68
7.4.3	Latencies .....	69
7.4.4	Transparent clock .....	70

7.5	Scheduling requirements .....	70
7.5.1	Delays to be identified.....	70
7.5.2	Delays compensation.....	70
7.5.3	PCF latency .....	71
7.5.4	Maximum transparent clock .....	72
7.5.5	PCF transparent clock jitter .....	72
7.5.6	Precision parameter.....	73
7.5.7	Time-Triggered minimum gap .....	73
7.5.8	Time-Triggered Switch receive window .....	73
7.5.9	Time-Triggered Switch minimum transmission .....	75
7.5.10	Time-Triggered End-System reception.....	75
<b>8</b>	<b>Network Setup and Services .....</b>	<b>76</b>
8.1	Overview .....	76
8.2	General Requirements.....	77
8.2.1	Overview.....	77
8.2.2	Internet Protocol (IP).....	77
8.2.3	UDP .....	78
8.2.4	ICMP.....	79
8.3	Dataloading via TFTP .....	80
8.3.1	Trivial File Transfer Protocol (TFTP) Overview.....	80
8.3.2	Dataloading requirements .....	81
8.4	Diagnostics and Status-Information via SNMP .....	81
8.4.1	Simple Network Management Protocol (SNMP) Overview .....	81
8.4.2	SNMP requirements.....	83
8.4.3	Diagnostic and Status-Information requirements .....	84
8.4.4	Monitoring Mode .....	88
8.5	Error management in End-System and Switch.....	88
<b>9</b>	<b>Test and verification.....</b>	<b>90</b>
9.1	Test Specification .....	90
9.2	Test references.....	90
9.2.1	Overview.....	90
9.2.2	Requirements for implementation at system level .....	91
<b>10</b>	<b>Tailoring .....</b>	<b>92</b>
10.1	Scope .....	92
10.2	Tailoring options and parameters.....	92
10.2.1	Overview.....	92

10.2.2 Step 1: Function and service selection .....	92
10.2.3 Step 2: Services configuration.....	92
10.3 IEEE 802.3 Tailoring .....	93
10.4 SAE AS6802 Tailoring .....	97
<b>Bibliography.....</b>	<b>102</b>

## Figures

Figure 3-1: Structure of a Packet.....	13
Figure 4-1: OSI Reference Model.....	18
Figure 4-2: Physical Layer Model .....	19
Figure 4-3: Data Link Layer .....	20
Figure 4-4: Time-Triggered Ethernet Services .....	21
Figure 4-5: Traffic Partitioning .....	23
Figure 4-6: Network Communication Channel .....	23
Figure 4-7: A TTE example network .....	24
Figure 4-8: Full Duplex Links.....	24
Figure 4-9: Message Processing at the Switch.....	25
Figure 4-10: Preemption.....	26
Figure 4-11: Shuffling .....	27
Figure 4-12: Media Reservation .....	27
Figure 4-13: Network Building Blocks .....	28
Figure 4-14: Network Building Blocks Examples.....	28
Figure 4-15: Virtual Link .....	29
Figure 4-16: Bandwidth Reservation.....	30
Figure 4-17: Time-Triggered Ethernet two step clock synchronization algorithm .....	31
Figure 4-18: Example of an integration PCF Frame exchange .....	34
Figure 4-19: Redundancy Communication.....	34
Figure 4-20: Redundancy Management at the Receiver.....	35
Figure 5-1: Single Channel Network Topology .....	37
Figure 5-2: Single Channel Network Topology – without cascaded Switches .....	38
Figure 5-3: Single Channel Network Topology – with cascaded Switches .....	38
Figure 5-4: Dual Channel Network Topology .....	38
Figure 5-5: Dual Channel Network Redundancy without cascaded Switches .....	39
Figure 5-6: Dual Channel Network Redundancy with cascaded Switches .....	39
Figure 5-7: Triple Channel Redundant Network Topology .....	39
Figure 5-8: Triple Channel Network Redundancy without cascaded Switches .....	40
Figure 5-9: Triple Channel Network Redundancy with cascaded Switches.....	40

Figure 5-10: Mixed Architecture.....	40
Figure 5-11: Multiple Networks Topology .....	41
Figure 5-12: Synchronization priority assignment recommendation .....	42
Figure 5-13: Time-Triggered Ethernet topology composed of standard Ethernet nodes .....	43
Figure 6-1: OSI Layer Services .....	46
Figure 6-2: Destination MAC Address .....	47
Figure 6-3: Source MAC Address.....	47
Figure 7-1: Configuration Interface Tool – IP .....	53
Figure 7-2: Example of delays at system level.....	68
Figure 7-3: Example of delays related to a device .....	69
Figure 7-4: Impact of delays on synchronization precision.....	69
Figure 7-5: Impact of delays on synchronization precision.....	71
Figure 7-6: Impact of delays on synchronization precision.....	71
Figure 8-1: Network Diagnostic and Monitoring Service Layers.....	77
Figure 8-2: FTP Message Types .....	81
Figure 8-3: Simple Network Management Protocol (SNMP) .....	82
Figure 8-4: Global SNMP architecture .....	83

## Tables

Table 6-1: Interface ID .....	48
Table 7-1: General Interoperability Parameter Table .....	54
Table 7-2: Switch Interoperability Parameter Table .....	54
Table 7-3: End-System Interoperability Parameter Table .....	55
Table 7-4: End-System Schedule Parameters.....	61
Table 7-5: End-System Output VL Parameters.....	61
Table 7-6: End-System Input VL Parameters .....	62
Table 7-7: End-System Best-Effort Filtering Parameters .....	62
Table 7-8: End-System Clock Synchronization Parameters.....	62
Table 7-9: End-System General Parameters .....	64
Table 7-10: Switch Scheduling Parameters .....	64
Table 7-11: Switch Output VL Parameters.....	65
Table 7-12: Switch Input VL Parameters .....	65
Table 7-13: Switch Best-Effort Filtering Parameters .....	65
Table 7-14: Switch Clock Synchronization Parameters.....	65
Table 7-15: Switch General Parameter.....	67
Table 7-16: Max Transparent Clock parameter table .....	72
Table 7-17: Precision parameter Table.....	73

Table 7-18: TT Switch Receive Window start and end time .....	74
Table 7-19: Time-Triggered Switch receive window Table.....	74
Table 10-1: Requirements selection .....	93
Table 10-2: Tailoring to [IEEE 802.3] - Part 3 .....	93
Table 10-3: Tailoring to [SAE AS6802] .....	97
Table A-1 : Clock Synchronization.....	98
Table A-2 : Time-Triggered Communication .....	99
Table A-3 : Dependability .....	99