

ISO 8642:2025-07 (E)

Aerospace - Self-locking nuts with maximum operating temperature greater than 425 °C - Test methods

| Contents | | Page |
|----------------|---------------------------------------------------------------------------------------------------|------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Inspections and tests | 1 |
| 4.1 | Hardness test | 1 |
| 4.1.1 | Procedure | 1 |
| 4.1.2 | Method | 2 |
| 4.2 | Bearing surface squareness test | 2 |
| 4.2.1 | Test device | 2 |
| 4.2.2 | Method | 3 |
| 4.3 | Axial load test | 4 |
| 4.3.1 | Test device | 4 |
| 4.3.2 | Method | 4 |
| 4.4 | Wrenching feature test | 5 |
| 4.4.1 | General | 5 |
| 4.4.2 | Test device | 5 |
| 4.4.3 | Method | 6 |
| 4.5 | Torque-out test | 6 |
| 4.5.1 | General | 6 |
| 4.5.2 | Test device | 7 |
| 4.5.3 | Method | 7 |
| 4.6 | Test of no rotation of the captive washer | 8 |
| 4.6.1 | General | 8 |
| 4.6.2 | Test device | 8 |
| 4.6.3 | Method | 8 |
| 4.7 | Push-out test | 8 |
| 4.7.1 | General | 8 |
| 4.7.2 | Test device | 9 |
| 4.7.3 | Method | 9 |
| 4.8 | Self-locking torque at ambient temperature | 10 |
| 4.8.1 | Test device | 10 |
| 4.8.2 | Method | 11 |
| 4.9 | Self-locking torque at ambient temperature after heat soak at maximum operating temperature | 12 |
| 4.9.1 | Test device | 12 |
| 4.9.2 | Method | 14 |
| 4.10 | Permanent set test | 15 |
| 4.10.1 | General | 15 |
| 4.10.2 | Test device | 15 |
| 4.10.3 | Method | 16 |
| 4.11 | Vibration test | 17 |
| 4.11.1 | General | 17 |
| 4.11.2 | Test device | 17 |
| 4.11.3 | Method | 19 |
| 4.12 | Swaging test | 20 |
| 4.12.1 | General | 20 |

| | |
|----------------------------------------|-----------|
| 4.12.2 Visual examination | 20 |
| Bibliography | 21 |