ISO 23933:2006-01 (E)

Aerospace - Aramid reinforced lightweight polytet rafluoroethylene (PTFE) hose assemblies, classification 135 °C/20.684 kPa (275 °F/3.000 psi) and 135 °C/21.000 kPa (275 °F/3.046 psi) - Procurement specification

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Classification 2

4 Requirements 2
4.1 Limits of application 2
4.2 Qualification 2
4.3 Materials 2
4.4 Construction 3
4.5 Inner tube requirements 4
4.6 Hose assembly 5
4.7 Fitting threads 6
4.8 Part numbering of interchangeable parts 7
4.9 Identification of products 7
4.10 Workmanship 7
4.11 Hose assembly -- Test and performance requirements 8

5 Quality assurance 12
5.1 Responsibility for inspection 12
5.2 Classification of inspections 12
5.3 Qualification inspections 12
5.4 Quality conformance inspections 15
5.5 Test conditions 16
5.6 Inspection methods 17

6 Preparation for delivery 18
6.1 Storage and packaging 18
6.2 Marking 18

7 Ordering data 18

Annex A (informative) Equivalent materials 19

Annex B (informative) Qualification procedures and fire resistance specifications 21

Bibliography 22