

ISO 1540:2006-02 (E)

Aerospace - Characteristics of aircraft electrical systems

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Requirements applicable to all systems | 10 |
| 4.1 | General | 10 |
| 4.2 | On-aircraft power sources | 10 |
| 4.3 | External power sources | 11 |
| 4.4 | Source/distribution system coordination | 11 |
| 4.5 | Utilization equipment | 11 |
| 5 | Constant frequency (CF) a.c. power system characteristics | 12 |
| 5.1 | General characteristics | 12 |
| 5.2 | Steady-state characteristics | 13 |
| 5.3 | Transient characteristics | 13 |
| 6 | Variable frequency (VF) a.c. power system characteristics | 15 |
| 6.1 | General characteristics | 15 |
| 6.2 | Consideration of CF power characteristics | 15 |
| 6.3 | Steady-state characteristics | 15 |
| 6.4 | Transient characteristics | 16 |
| 7 | D.C. power system characteristics | 19 |
| 7.1 | General characteristics | 19 |
| 7.2 | Steady-state characteristics | 19 |
| 7.3 | Transient characteristics | 20 |
| 8 | Requirements allocation | 21 |
| 9 | Utilization equipment restrictions | 21 |
| 9.1 | General | 21 |
| 9.2 | A.C. power utilization | 21 |
| 9.3 | Power factor | 21 |
| 9.4 | Load switching transients | 22 |
| 9.5 | Inrush current | 22 |
| 9.6 | Input current modulation | 22 |
| 9.7 | Input current distortion | 22 |
| 9.8 | Maximum input capacitance | 23 |
| 10 | Power quality associated assumptions and background | 24 |
| 10.1 | General | 24 |
| 10.2 | Background to the document scope | 25 |
| 10.3 | A.C. power system assumptions | 25 |
| 10.4 | A.C. source equipment assumptions | 29 |
| 10.5 | D.C. system assumptions | 31 |
| 10.6 | D.C. engine starting power quality | 32 |
| 10.7 | 270 V d.c. input power | 32 |